

Gauges Sold Separately



### Miniature

Ports .....1/4"  
SCFM .....20



### Compact

Ports .....1/4"-3/8"  
SCFM .....50



### Standard

Ports ....1/4"-3/8"-1/2"-3/4"-1"  
SCFM.... 70 -150 -425

## Filters - Mini, Compact, Modular, Standard

Body Size	Port Size	Poly Bowl	Metal Bowl
Mini	1/4"	4000/56-100	4001
Auto Drain			
Mini	1/4"	4002A	

with Sight Glass

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4006	4007
1/4"	3/8"	4026/56-300	4027/56-302-99

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	1/4"	4010A-99	4011A-99
3/8"	3/8"	4020A-99/56-305	4021A-99
3/8"	3/8"		4024A-99
			(w/ auto drain)
1/2"	1/2"	4030/56-308	4031/56-310
1/2"	3/4"	4032	4040

### Hi Flow

1"	3/4"		4041*/56-313
1"	1"		4050/56-314

\*For Auto Drain order 4046  
4096 Manual Drain Kit

### Parts & Accessories

Body Size	5 µm Element	Poly Bowl	Metal Bowl	Bowl O-Ring
Mini	4062	4073	4078	4780
<small>with Sight Glass</small>				
Mounting Bracket & Panel Nut - 4160				

### Parts & Accessories

Body Size	40 µm Element	5 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket
1/4"	4087	4088	4056	4057	4760
<b>Semi Auto Drain - 4086</b>					

### Parts & Accessories

Body Size	40 µm Element	5 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket
3/8"	4066A-99	4063A-99	4074A-99	4079A-99	4071A-99
1/2"	4093	4092	4095	4094	4772
1"	4068	4065		4272	4090

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure -  
Transparent Bowl: 150 psig (10.3 bar)  
Metal Bowl: 250 psig (17.2 bar)  
Maximum Temperature -  
Transparent Bowl: 125°F (52°C)  
Metal Bowl: 175°F (79°C)

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure -  
Transparent Bowl: 150 psig (10.3 bar)  
Metal Bowl: 250 psig (17.2 bar)  
Maximum Temperature -  
Transparent Bowl: 125°F (52°C)  
Metal Bowl: 175°F (79°C)

Body Size	Bowl O-Ring	Sight Glass	Auto Drain
3/8"	4782	4277A	4070
1/2"	4783		
1"	4781	4278	4046

**Auto Drain - 4060**  
**Manual Drain - 4096**

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure -  
Transparent Bowl: 150 psig (10.3 bar)  
Metal Bowl: 250 psig (17.2 bar)  
Maximum Temperature -  
Transparent Bowl: 125°F (52°C)  
Metal Bowl: 175°F (79°C)

# Filters, Regulators, Lubricators

Gauges Sold Separately.



### Miniature

Ports .....1/4"  
SCFM.....5



### Compact

Ports .....1/4"  
SCFM.....50



### Standard

Ports ....1/4"-3/8"-1/2"-3/4"-1"  
SCFM.... 75 -150 425

## Regulator - Filter - Lubricator

Body Size	Port Size	Poly Bowl
Mini	1/4"	4405

### Parts & Accessories

Body Size	40 µm Element	5 µm Element	Reg. Repair Kit	Rplc Knob	Bowl O-Ring	Fill Plug
Mini	4066A-99	4063A-99	4166	4790	4780	4794

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4409	4412

### Parts & Accessories

Body Size	40 µm Element	Mounting Bracket	Fill Plug	Reg. Repair Kit
1/4"	4087	4759	4798	4757

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	1/4"	4410A-99	4411A-99
3/8"	3/8"	4420A-99	4421A-99
1/2"	1/2"	4430	4431
1/2"	3/4"	4440	4441
1"	1"	4440	4450

### Parts & Accessories

Body Size	40 µm Element	5 µm Element	Mount. Bracket	Reg. Repair Kit	Fill Plug	Rplc Knob
3/8"	4066A-99	4063A-99	4071A-99	4167A	4795	4782 4792
1/2"	4093	4092	4770	4776	4796	4783 4793
1"	4068	4065	4165	4169	4797	4781

Body Size	FILTERS			LUBRICATOR	
	Poly Bowl	Metal Bowl	Poly Bowl	Metal Bowl	Bowl
Mini	4073	4078	4264	4269	

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/8" NPT (full flow)  
Outlet Range: 5 - 125 psi

Body Size	FILTERS			LUBRICATOR	
	Poly Bowl	Metal Bowl	Poly Bowl	Metal Bowl	Bowl
1/4"	4056	4057	4058	4059	

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/8" NPT (full flow)  
Outlet Range: 5 - 125 psi

Body Size	FILTERS			LUBRICATOR	
	Poly Bowl	Metal Bowl	Poly Bowl	Metal Bowl	Bowl
3/8"	4074A-99	4079A-99	4265A-99	4269	
1/2"	4095	4094	4285	4286	
1"		4272		4272	

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/4" NPT (full flow)  
Outlet Range: 5 - 125 psi