

Gauges Sold Separately



**Compact**  
Ports ..... 1/4"-3/8"  
Flow SCFM ..... 20



**Standard**  
Ports ..... 3/8"-1/2"  
Flow SCFM ..... 75 150



**Drip-Legs**  
Ports ..... 1/2"

### Coalescing Filters

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4017	4016
1/4"	3/8"	4019	4018

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	1/4"	4012A-99	
3/8"	3/8"	4022A-99	
1/2"	3/8"	4038/56-204	4023
1/2"	1/2"	4033/56-208	4037

Port Size	Poly Bowl	Metal Bowl
1/2"	4034	4035

### Parts & Accessories

Body Size	.01 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Semi Auto Drain
1/4"	4089	4056	4057	4760	4086

### Parts & Accessories

Body Size	.01µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Rplc. Sight Glass	Bowl O-Ring
1/2"	4097	4095	4094	4772	4278	4783

### Parts & Accessories

Port Size	Poly Bowl	Metal Bowl	Auto Drain
1/2"	4074A-99	4079A-99	4060

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig (10.3 bar)  
Metal Bowl: 250 psig (17.2 bar)  
Maximum Temperature –  
Transparent Bowl: 125°F (52°C)  
Metal Bowl: 150°F (66°C)

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig (10.3 bar)  
Metal Bowl: 250 psig (17.2 bar)  
Maximum Temperature –  
Transparent Bowl: 125°F (52°C)  
Metal Bowl: 150°F (66°C)

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig (10.3 bar)  
Metal Bowl: 250 psig (17.2 bar)  
Maximum Temperature –  
Transparent Bowl: 125°F (52°C)  
Metal Bowl: 150°F (66°C)



**Miniature**  
Ports ..... 1/4"  
Flow SCFM ..... 20



**Compact**  
Ports ..... 1/4"-3/8"  
Flow SCFM ..... 50



**Standard**  
Ports ..... 1/4"-3/8"-1/2"-3/4"-1"  
SCFM ..... 70 -150 -425

### Regulators

Body Size	Port Size	Without Gauge	With Gauge
Mini	1/4"	4100/4102*	4100D/56-110

Body Size	Port Size	Without Gauge
1/4"	1/4"	4119
1/4"	3/8"	4118

Body Size	Port Size	Without Gauge
3/8"	1/4"	4115A-99/56-341-99 4116-99 w/ panel nut
3/8"	3/8"	4125A-99/56-355 4126-99 w/ panel nut
1/2"	1/2"	4135/56-344
1/2"	3/4"	4145
1"	3/4"	4141
1"	1"	4155/56-346

### Parts & Accessories

Body Size	Mounting Bracket	Panel Nut	Reg. Repair Kit	Rplc. Knob
Mini	4160	4161	4166	4790

### Parts & Accessories

Body Size	Mounting Bracket w/ Panel	Panel Nut	Reg. Repair Kit	Rplc. Knob
1/4"	4760	4763	4757	4791

### Parts & Accessories

Body Size	Mounting Bracket w/Panel	Panel Nut	Reg. Repair Kit	Rplc. Knob
3/8"	4162A-99	4778	4167A	4792
1/2"	4772	4773	4776	4793
1"	4165		4169	Non-Rplc

\* Non-Repairable Regulator

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure: 300 psig  
Temperature Range –  
Mini: 0° to 150°F  
All Others: 0° to 175°F  
Gauge Port: 2-1/8" NPT (full flow)  
Outlet Range: 5 - 125 psi

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure: 300 psig  
Temperature Range: 0° to 150° F  
Gauge Port: 2-1/8" NPT (full flow)  
Outlet Range: 5 - 125 psi

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure: 300 psig  
Temperature Range: 0° to 175° F  
Gauge Port: 2-1/4" NPT (full flow)  
Outlet Range: 5 - 125 psi



Gauges Sold Separately.



### Miniature

Ports .....1/4"  
SCFM .....20



### Compact

Ports .....1/4"-3/8"  
SCFM.....50



### Standard

Ports .....1/4"-3/8"-1/2"-3/4"-1"  
SCFM..... 75 -150

## Piggyback Filter/Regulator

Body Size	Port Size	Poly Bowl
Mini	1/4"	4300/56-357

### Parts & Accessories

Body Size	40 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Reg. Repair Kit
1/4"	4062	4073	4078*	4160	4166

Body Size	Rplc. Knob	Bowl O-Ring
1/4"	4790	4780

\*Replacement metal bowl has an auto drain and no sight glass.

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/8" NPT (full flow)  
Outlet Range: 5 - 125 psi

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4312	4314
1/4"	3/8"	4317	4316

### Parts & Accessories

Body Size	40 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Reg. Repair Kit
1/4"	4087	4056	4057	4760	4757

Body Size	Rplc. Knob
1/4"	4791

### Specifications

Fluid: Compressed air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/8" NPT (full flow)  
Outlet Range: 5 - 125 psi

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	1/4"	4310A-99	4311A-99
3/8"	3/8"	4320A-99	4321A-99/56-355
1/2"	1/2"	4330/56-355	4331
1/2"	3/4"	4340	4341

### Parts & Accessories

Body Size	40 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Reg. Repair Kit
3/8"	4066A	4074A-99	4079A-99	4162A-99	4167A
1/2"	4093	4095	4094	4772	4776

Body Size	Rplc. Knob	Bowl O-Ring
3/8"	4792	4782
1/2"	4793	4783

### Specifications

Fluid: Compressed air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/4" NPT (full flow)  
Outlet Range: 5 - 125 psi

# Filters, Regulators, Lubricators

Gauges Sold Separately.



### Miniature

Ports .....1/4"  
SCFM.....5



### Compact

Ports .....1/4"  
SCFM.....50



### Standard

Ports ....1/4"-3/8"-1/2"-3/4"-1"  
SCFM.... 75 -150 425

## Regulator - Filter - Lubricator

Body Size	Port Size	Poly Bowl
Mini	1/4"	4405

### Parts & Accessories

Body Size	40 µm Element	5 µm Element	Reg. Repair Kit	Rplc Knob	Bowl O-Ring	Fill Plug
Mini	4066A-99	4063A-99	4166	4790	4780	4794

Body Size	FILTERS			LUBRICATOR	
	Poly Bowl	Metal Bowl	Poly Bowl	Metal Bowl	Bowl
Mini	4073	4078	4264	4269	

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/8" NPT (full flow)  
Outlet Range: 5 - 125 psi

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4409	4412

### Parts & Accessories

Body Size	40 µm Element	Mounting Bracket	Fill Plug	Reg. Repair Kit
1/4"	4087	4759	4798	4757

Body Size	FILTERS			LUBRICATOR	
	Poly Bowl	Metal Bowl	Poly Bowl	Metal Bowl	Bowl
1/4"	4056	4057	4058	4059	

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/8" NPT (full flow)  
Outlet Range: 5 - 125 psi

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	1/4"	4410A-99	4411A-99
3/8"	3/8"	4420A-99	4421A-99
1/2"	1/2"	4430	4431
1/2"	3/4"	4440	4441
1"	1"		4450

### Parts & Accessories

Body Size	40 µm Element	5 µm Element	Mount. Bracket	Reg. Repair Kit	Fill Plug	Rplc Knob
3/8"	4066A-99	4063A-99	4071A-99	4167A	4795	4782 4792
1/2"	4093	4092	4770	4776	4796	4783 4793
1"	4068	4065	4165	4169	4797	4781

Body Size	FILTERS			LUBRICATOR	
	Poly Bowl	Metal Bowl	Poly Bowl	Metal Bowl	Bowl
3/8"	4074A-99	4079A-99	4265A-99	4269	
1/2"	4095	4094	4285	4286	
1"		4272		4272	

### Specifications

Fluid: Compressed Air  
Maximum Inlet Pressure –  
Transparent Bowl: 150 psig  
Metal Bowl: 250 psig  
Maximum Temperature –  
Transparent Bowl: 125°F  
Metal Bowl: 175°F  
Gauge Port: 2-1/4" NPT (full flow)  
Outlet Range: 5 - 125 psi