

Hose Assemblies

Amflo No.	Color	PSI	Description
PVC - Light Weight			
522-25	Yellow	250	1/4" x 25', 1/4" Fittings
522-50	Yellow	250	1/4" x 50', 1/4" Fittings
522-100	Yellow	250	1/4" x 100', 1/4" Fittings
524-25	Blue	300	3/8" x 25', 3/8" Fittings
524-25A	Blue	300	3/8" x 25', 1/4" Fittings
524-50	Blue	300	3/8" x 50', 3/8" Fittings
524-50A	Blue	300	3/8" x 50', 1/4" Fittings
524-100	Blue	300	3/8" x 100', 3/8" Fittings
524-100A	Blue	300	3/8" x 100', 1/4" Fittings
535-50A	Blue	300	1/2" x 50', 1/4" Fittings

PVC			
554-25A with Board/Sleeves	Blue	300	3/8" x 25', 1/4" Fittings
554-50A with Board/Sleeves	Blue	300	3/8" x 50', 1/4" Fittings
554-100A with Board/Sleeves	Blue	300	3/8" x 100', 1/4" Fittings
575-50A	Day Glo Yellow	300	3/8" x 50', 1/4" Fittings
576-25A	Day Glo Orange	300	3/8" x 25', 1/4" Fittings
576-50A	Day Glo Orange	300	3/8" x 50', 1/4" Fittings
578-50A	Day Glo Green	300	3/8" x 100', 1/4" Fittings

Rubber			
512-25 Heavy Duty	Red	300	1/4" x 25', 1/4" Fittings
512-50 Heavy Duty	Red	300	1/4" x 50', 1/4" Fittings
512-100 Heavy Duty	Red	300	1/4" x 100', 1/4" Fittings
514-25 Heavy Duty	Red	300	3/8" x 25', 3/8" Fittings
514-25A Heavy Duty	Red	300	3/8" x 25', 1/4" Fittings
514-50 Heavy Duty	Red	300	3/8" x 50', 3/8" Fittings
514-50A Heavy Duty	Red	300	3/8" x 50', 1/4" Fittings
514-100 Heavy Duty	Red	300	3/8" x 100', 3/8" Fittings
514-100A Heavy Duty	Red	300	3/8" x 100', 1/4" Fittings
515-50 Heavy Duty	Red	300	1/2" x 50', 1/2" Fittings
515-50A Heavy Duty	Red	300	1/2" x 50', 3/8" Fittings
505-50A with Board/Sleeves	Red	300	1/2" x 50', 3/8" Fittings
552-50A with Board/Sleeves	Red	300	3/8" x 25', 1/4" Fittings
552-100A with Board/Sleeves	Red	300	3/8" x 50', 1/4" Fittings
555-50A with Board/Sleeves	Gray	300	3/8" x 50', 1/4" Fittings

PVC - Bulk Reels			
575-500	Day Glo Yellow	300	3/8" x 500'
576-500	Day Glo Orange	300	3/8" x 500'
578-500	Day Glo Green	300	3/8" x 500'

Rubber - Bulk Reels			
502-500 Standard Duty	Red	200	1/4" x 500'
503-500 Standard Duty	Red	200	5/16" x 500'
504-500 Standard Duty	Red	200	3/8" x 500'
505-500 Standard Duty	Red	200	1/2" x 500'
506L-500 Lock On	Gray	300	1/4" x 500'
508L-500 Lock On	Gray	300	3/8" x 500'
512-500 Heavy Duty	Red	300	1/4" x 500'
514-500 Heavy Duty	Red	300	3/8" x 500'
515-500 Heavy Duty	Red	300	1/2" x 500'



522-25



554-50A



576-50A



512-25



552-50A



555-50A

KEEP OUT OF REACH OF CHILDREN

WARNING: This product is designed for use on regulated compressed air lines or on air compressors where air pressure does not exceed 300 PSI. Do not exceed the pressure limitation of the hose and/or air operated devices being used. Failure to follow these specifications and directions exactly may result in personal injury and/or property damage.

Hose Assemblies, Air / Multi-Purpose Hose

Amflo No.	Color	PSI	Description
Lead-In and Whip Hose			
25L-24B	Gray	300	1/4" x 24" Ball Swivel Lead-In
25L-24BD	Gray	300	1/4" x 24" Display Pack
25L-60B	Gray	300	1/4" x 60" Ball Swivel Lead-In
25L-60BD	Gray	300	1/4" x 60" Display Pack
28L-24B	Gray	300	1/4" x 24" Lead-In with Valve
28L-24BD	Gray	300	1/4" x 24" Display Pack
28L-60B	Gray	300	1/4" x 60" Lead-In with Valve
37L-24B	Gray	300	3/8" x 24" Lead-In, 1/4" (M) x 1/4" (F)
37L-30B	Gray	300	3/8" x 30" Lead-In, 1/4" Ball Swivel
37L-30BD	Gray	300	3/8" x 30" Display Pack
37L-72B	Gray	300	3/8" x 72" Lead-In, 1/4" Ball Swivel
37L-72BD	Gray	300	3/8" x 72" Display Pack
39-30B	Blue	300	3/8" x 30" PVC Lead-In Hose
39-30G	Green	300	3/8" x 30" PVC Lead-In Hose
39-30O	Orange	300	3/8" x 30" PVC Lead-In Hose
39-30Y	Yellow	300	3/8" x 30" PVC Lead-In Hose
39-30R	Red	300	3/8" x 30" PVC Lead-In Hose



28L-24B



37L-30B

Camel No.	Amflo No.	Hose ID	Hose OD	PSI Rating
-----------	-----------	---------	---------	------------

Air and Water Hose

Smooth red cover is very tough and resistant to oil and grease. Use barbed type fittings or reusable hose fittings.

* Actual length may vary from reel to reel.

Standard Duty Hose

502-500*	1/4"	.531	250
503-500*	5/16"	.625	250
504-500*	3/8"	.688	250
505-500*	1/2"	.844	250

Heavy Duty Hose

Smooth red cover is tough and resistant to oil and grease. Hose has same qualities as standard duty hose but has higher PSI ratings.

512-500*	1/4"	.531	300
514-500*	3/8"	.688	300
515-500*	1/2"	.844	300

Amflo No.	Size and Length
-----------	-----------------

Lock-On Hose

Special hose designed for lock-on fittings which are much quicker to use and do not need ferrules. Cut hose to length and push in fitting. The special weave of the hose grips fitting and holds it securely beyond burst strength of the hose itself. Doesn't require crimping.

Warning: Use only fittings made specifically for Lock-On hose. Conventional barb type will not hold securely. Working pressure 250 PSI.


506L-100	1/4" x 100'
508L-100	3/8" x 100'
506L-500	1/4" x 500'
508L-500	3/8" x 500'

Camel No.	Amflo No.
-----------	-----------

Other Hose

Signal Bell Hose. Durable rubber hose, 200 PSI. Black.

57-411	494-100
	494-500 Heavy-Duty, Bulk Reel



29-130

Heavy-Duty Polypropylene Shelf Bins

Durable bins for bulk products. May be used on shelves or with gondolas in the display area. Convenient hopper front. Has wide label slot. Reinforced sides, water and oil resistant. 12 pack.

Dimensions: 11-5/8" long x 6-5/8" wide x 4" high.

29-130 29-130

