

Couplers & Plugs

61-564



C9-03



CP10



61-574



C20



61-578



C20-42L



C20-44



C21



CP21-44



COUPLERS

PLUGS

Thread Type	NPT Size	Type Metal	Camel No.	Amflo No.	Camel No.	Amflo No.
-------------	----------	------------	-----------	-----------	-----------	-----------

1/2" Automotive Standard Series Type "F"

Plated steel couplers have hardened steel balls and stainless steel springs. Coupler plugs are heat treated to reduce wear on critical mating surfaces. **Maximum working pressure 300 PSI.**

Male	3/8"	Steel		C9-03	61-474	CP9-03
Male	1/2"	Steel	61-564	C9	61-568	CP9
Female	3/8"	Steel	61-472	C10-23	61-475	CP10-23
Female	1/2"	Steel	61-563	C10	61-569	CP10
Hose Barb	1/2"	Steel		C10-45		CP9-45

1/4" Industrial Interchange Series Type "D"

Plated steel couplers have hardened steel balls and stainless steel springs. Coupler plugs are heat treated to reduce wear on critical mating surfaces. The Industrial Interchange Series couplers interchange with Aro, Foster, Milton as well as units produced by other manufacturers. **Maximum working pressure 300 PSI.**

Male	1/4"	Steel	61-574	C21	61-578	CP21
Male	1/4"	Brass	61-715	C21B		CP21B
Male	3/8"	Steel		C21-03	61-535	CP21-03
Male	3/8"	Brass		C21-03B		CP21-03B
Female	1/4"	Steel	61-573	C20	61-579	CP20
Female	1/4"	Brass	61-717	C20B		CP20B
Female	3/8"	Steel		C20-23		CP20-23
Female	3/8"	Brass	61-718	C20-23B		CP20-23B
Hose Barb	1/4"	Steel		C20-42		CP21-42
Hose Barb	1/4"	Brass	61-719	C20-42B		
Hose Barb	3/8"	Steel		C20-44		CP21-44
Hose Barb	3/8"	Brass	61-720	C20-44B		CP21-44B
Lock-On Barb	1/4"	Steel		C20-42L		CP21-42L
Lock-On Barb	3/8"	Steel		C20-44L		CP21-44L
Female	1/4"	Steel			(.302-32) 61-023	CP22

See price sheet for packaging options.

Camel No. Amflo No.

1/4" Industrial Interchange Series Type "D" Coupler and Plug Set

Retail pack of one female 1/4" NPT coupler and one male 1/4" NPT plug on blister card.

61-572 C20AU

Thread Type	NPT Size	Type Metal	COUPLERS		PLUGS	
			Camel No.	Amflo No.	Camel No.	Amflo No.

1/4" Industrial Interchange (Push-to-Connect) Type "D"

Male	1/4"	Steel	61-011	C41
Female	1/4"	Steel	61-013	C40

3/8" Industrial Series Type "E"

WARNING: Couplers and Plugs listed in this section are intended for use on compressed air lines only. All have a maximum rated working pressure of 300 PSI.

Male	1/4"	Steel		C25-02		CP25-02
Male	3/8"	Steel	61-483	C25-04	61-484	CP25-04
Male	1/2"	Steel		C26-22		CP26-22
Female	1/4"	Steel		C26	61-485	CP26
Female	3/8"	Steel	61-482	C26-24		CP26-24
Female	1/2"	Steel		C26-42		
Hose Barb	1/4"	Steel		C26-44		CP25-44
Hose Barb	3/8"	Steel		C26-45		CP25-45
Hose Barb	1/2"	Steel		C26-42L		CP25-42L
Lock-On Barb	1/4"	Steel		C26-44L		CP25-44L

1/2" Industrial Interchange

WARNING: Couplers and Plugs listed in this section are intended for use on compressed air lines only. All have a maximum rated working pressure of 300 PSI.

Male	3/8"	Steel		C9-03	61-133	CP17-03
Male	1/2"	Steel	61-564	C9	61-134	CP17
Female	3/8"	Steel	61-472	C10-23	61-136	CP18-23
Female	1/2"	Steel	61-563	C10	61-137	CP18
Female	1/2"	Steel	61-471	C10R		
Hose Barb	1/2"	Steel		C10-45		CP17-45



See price sheet for packaging options.

WARNING: Use only on compressed air lines at a maximum pressure of 300 PSI. For safety, do not exceed the pressure limitation of the hose and/or air operated device you are using. Not for use with food stuffs or ingestible products. If this product has a hose barb, make sure hose barb size matches the inside diameter of the hose you are using. All hose barb fittings must be secured to the hose with a hose clamp or crimped-on ferrule. Failure to follow these directions exactly may cause product to fail and may result in injury and/or property damage.