


FOR-SEAL[®]

Introduction




Tube O.D.	1/4	3/8	1/2	5/8	3/4
Thread	9/16-18	11/16-16	13/16-16	1-14	1 3/16-12

Tube O.D.	7/8	1	1-1/4	1-1/2
Thread	1 3/16-12	1 7/16-12	1 11/16-12	2-12

Tube Preparation And Cleaning

Figure 1

1. Establish the length of tubing required allowing 1/16" cut-off factor for each connection.
2. Cut the tubing to proper length keeping ends reasonably square. A fine tooth hack saw or cut-off saw works well for this job. The use of a tubing cutter is not recommended due to possible collapse of the tube end, retarding the capillary action required for proper braze flow.



Note: Subtract 1/16" from tube length for each connection.

3. Clean the end of the tube with an alkaline cleaner to remove all traces of oil or grease. Deburr the end of the tube with a file and polish the outside of the tube down to bare metal with clean emery paper. Oil and grease residue must be removed first to avoid working the oily residue into the tube surface.
4. After polishing, wipe off any metal particles using a clean solvent if necessary. Avoid touching the tube end after final cleaning as this may leave greasy spots which will braze poorly.

Clean the tailpiece with an alkaline cleaner.



Typical Application: High pressure, hydraulic, pneumatic and chemical processing.

Pressure^{*}: Working pressure to 6000 PSI (1-1/4" and 1-1/2"); maximum 4000 PSI).

Sealing Method: O-ring.

Vibration Rating: Excellent resistance.

Material: 12L14 steel

Plating: All fittings are zinc-plated, except brazed parts which are oil dipped.

Used With: Steel tubing (tubing for brazing must be non-coated).

Advantages: Tubing is brazed for permanent leakproof connection.

Conformance: An exclusive item with Weatherhead[®] meets SAE J1453.

Ordering Information: Use catalog number.

Label Set: FS-2400

NOTE: See page 377 for new hydraulic o-ring assortment.

* Pressure ratings shown are the pressure ratings for the fitting and are not necessarily the pressure rating applicable in an assembly with hydraulic hose. The applicable pressure rating for an assembly with hydraulic hose is the lower value specified for the hose and the fitting.

Fluxing and Brazing Cleanup

Flux may be cleaned up using hot water and wire brush, using care not to scratch the tailpiece sealing surface.

1. Assemble proper size braise ring into counterbore of tailpiece. The correct size brazing will be slightly smaller than the inside diameter of the counterbore.
2. Clamp the tube securely in a vise, slide nut on tube, with threads pointing outward. Coat the tube end with flux and several inches of the tube outside diameter.
3. Coat the tailpiece liberally with flux including the counterbore and braise ring.



4. In a well ventilated area, apply heat uniformly to the tailpiece and the tube end. Watch the flux. The flux becomes completely clear when it is close to the proper brazing temperature. When ring melts, the tailpiece will settle down onto the end.

NOTE: General working knowledge of Acetylene torch brazing techniques is recommended.

5. Remove tube assembly from vise and check braise joint.
6. The braise alloy will flow down through the joint and should form a continuous fillet at the tube to tailpiece joint.

NOTE: Do not overheat. Excessive heat will only cause scaling and charred flux and make the parts more difficult to clean up.



Torque Requirements

Tube O.D.	1/4	3/8	1/2	5/8	3/4	1	1-1/4	1-1/2
Torque Ft-Lb. For-Seal SW. Nut	10-12	18-20	32-35	46-50	65-70	92	125	150
Torque Ft-Lb O-Ring Boss Straight Thread O-Ring Locknut Torque	14-16	24-26	50-60	72-80	125 135	200 220	210 280	270 360


Thread Chart

Rated pressures are for low surge, static type applications.

Tube O.D.	1/4	3/8	1/2	5/8	3/4	1	1-1/4	1-1/2
For-Seal Thread	9/16-18	11/16-16	13/16-16	1-14	1-3/16-12	1-7/16-12	1-11/16-12	2-12
Maximum PSI	6000	6000	6000	6000	6000	6000	4000	4000
Adjustable Fittings PSI	6000	6000	6000	6000	6000	5000	4000	3000

FOR-SEAL®


Tailpiece Silver Braze (Ref. SAE No. 520115)



TUBE O.D.	CATALOG NUMBER	D	D1	C1
1/4	4165x4	.256	.172	.374
3/8	4165x6	.381	.264	.374
1/2	4165x8	.506	.378	.374
5/8	4165x10	.631	.484	.413
3/4	4165x12	.757	.609	.551
1	4165x16	1.007	.811	.610
1-1/4	4165x20	1.257	1.024	.610
1-1/2	4165x24	1.507	1.260	.610


Oil Dipped

FOR-SEAL® Cadmium Free Braze Ring




TUBE O.D.	CATALOG NUMBER	WIRE DIA.	O.D.
1/4	4640x4	.046	.250
3/8	4640x6	.046	.375
1/2	4640x8	.046	.500
5/8	4640x10	.046	.625
3/4	4640x12	.062	.750
1	4640x16	.062	1.000
1-1/4	4640x20	.062	1.250
1-1/2	4640x24	.062	1.500

Bulkhead Nut (Ref. SAE No. 520118)




TUBE O.D. A	CATALOG NUMBER	HEX C	L
1/4	4924x4	13/16	.27
3/8	4924x6	1	.31
1/2	4924x8	1-1/8	.35
5/8	4924x10	1-5/16	.41
3/4	4924x12	1-1/2	.41
1	4924x16	1-3/4	.41
1-1/4	4924x20	2	.41
1-1/2	4924x24	2-3/8	.41

Nut
(Ref. SAE No. 520110)




TUBE O.D.	CATALOG NUMBER	HEX C	D	L
1/4	4105x4	11/16	.412	.58
3/8	4105x6	13/16	.531	.67
1/2	4105x8	15/16	.652	.83
5/8	4105x10	1-1/8	.829	.93
3/4	4105x12	1-3/8	.950	1.02
1	4105x16	1-5/8	1.144	1.10
1-1/4	4105x20	1-7/8	1.415	1.10
1-1/2	4105x24	2-1/4	1.727	1.10

Cap
(Ref. SAE No. 520112)



TUBE O.D.	CATALOG NUMBER	HEX C	L
1/4	4129x4	11/16	.67
3/8	4129x6	13/16	.75
1/2	4129x8	15/16	.90
5/8	4129x10	1-1/8	1.00
3/4	4129x12	1-3/8	1.10
1	4129x16	1-5/8	1.17
1-1/4	4129x20	1-7/8	1.17
1-1/2	4129x24	2-1/4	1.17


Plug
(Ref. SAE No. 520109)



TUBE O.D.	CATALOG NUMBER	HEX C	D	L
1/4	4229x4	5/8	.172	.659
3/8	4229x6	3/4	.264	.751
1/2	4229x8	7/8	.378	.854
5/8	4229x10	1-1/16	.484	1.020
3/4	4229x12	1-1/4	.609	1.080
1	4229x16	1-1/2	.811	1.100
1-1/4	4229x20	1-3/4	1.024	1.100
1-1/2	4229x24	2-1/8	1.260	1.100


FOR-SEAL o-ring included.

Union (Ref. SAE No. 520101)



TUBE O.D.	TUBE O.D.	CATALOG NUMBER	HEX C	D	D1	L
1/4	1/4	4305x4	5/8	.172	.172	1.08
3/8	1/4	4305x6x4	3/4	.264	.172	1.17
3/8	3/8	4305x6	3/4	.264	.264	1.22
1/2	3/8	4305x8x6	7/8	.378	.264	1.33
1/2	1/2	4305x8	7/8	.378	.378	1.39
5/8	1/2	4305x10x8	1-1/16	.484	.378	1.57
5/8	5/8	4305x10	1-1/16	.484	.484	1.68
3/4	1/2	4305x12x8	1-1/4	.609	.378	1.69
3/4	5/8	4305x12x10	1-1/4	.609	.484	1.80
3/4	3/4	4305x12	1-1/4	.609	.609	1.86
1	3/4	4305x16x12	1-1/2	.812	.609	1.92
1	1	4305x16	1-1/2	.812	.812	1.94
1-1/4	1-1/4	4305x20	1-3/4	1.024	1.024	2.02
1-1/2	1-1/2	4305x24	2-1/8	1.260	1.260	2.09

Bulkhead Union (Ref. SAE No. 520601)




TUBE O.D.	CATALOG NUMBER	HEX C	D	I	L
3/8	4325x6	1	.264	1.34	2.09
1/2	4325x8	1-1/8	.378	1.44	2.30
3/4	4325x12	1-1/2	.609	1.64	2.72
1	4325x16	1-3/4	.812	1.66	2.76
1-1/4	4325x20	2	1.024	1.66	2.76
1-1/2	4325x24	2-3/8	1.260	1.66	2.76

For bulkhead nut, see page 257.

Straight Thread O-Ring Connector

(Ref. SAE No. 520120)





MALETUBE O.D.	MALE PORT SIZE	CATALOG NUMBER	HEX C	D	D1	L
1/4	1/4	4315x4	5/8	.172	.172	1.133
1/4	3/8	4315x4x6	11/16	.172	.172	1.202
3/8	1/4	4315x6x4	3/4	.264	.172	1.343
3/8	3/8	4315x6	3/4	.264	.264	1.252
3/8	1/2	4315x6x8	7/8	.378	.264	1.378
3/8	5/8	4315x6x10	1-1/16	.264	.484	1.530
1/2	3/8	4315x8x6	7/8	.378	.264	1.472
1/2	1/2	4315x8	7/8	.378	.378	1.441
1/2	5/8	4315x8x10	1	.378	.484	1.590
1/2	3/4	4315x8x12	1-1/4	.378	.609	1.748
5/8	5/8	4315x10	1-1/16	.484	.484	1.700
3/4	3/4	4315x12	1-1/4	.609	.609	1.918
3/4	1	4315x12x16	1-1/2	.609	.609	1.960
1	3/4	4315x16x12	1-1/2	.812	.609	2.138
1	1	4315x16	1-1/2	.811	.811	1.978
1	1-1/4	4315x16x20	1-7/8	.812	1.709	2.058
1-1/4	1	4315x20x16	1-3/4	1.024	.843	2.278
1-1/4	1-1/4	4315x20	1-7/8	1.024	1.024	2.058
1-1/2	1-1/2	4315x24	2-1/8	1.260	1.260	2.125

For replacement Straight Thread O-ring, see page 254.

Straight Thread O-Ring Extended

(Ref. SAE No. 520122)





MALETUBE O.D.	MALE PORT SIZE	CATALOG NUMBER	HEX C	D	I	L
3/8	3/8	4316x6	3/4	.264	1.46	2.27
1/2	1/2	4316x8	7/8	.378	1.75	2.67
3/4	3/4	4316x12	1-1/4	.609	2.52	3.76
1	1	4316x16	1-1/2	.811	2.87	4.14
1-1/4	1-1/4	4316x20	1-7/8	1.024	3.41	4.76
1-1/2	1-1/2	4316x24	2-1/8	1.260	3.82	5.26

For replacement Straight Thread O-ring, see page 254.


FOR-SEAL®

Male 37° to Female FOR-SEAL®




FEMALE TUBE O.D.	MALE TUBE SIZE	CATALOG NUMBER	HEX C	HEX C1	D	L
1/4	1/4	4213x4	11/16	5/8	.172	1.50
3/8	3/8	4213x6	13/16	3/4	.297	1.62
1/2	1/2	4213x8	15/16	7/8	.392	1.90
5/8	5/8	4213x10	1-1/8	1-1/16	.484	2.25
3/4	3/4	4213x12	1-3/8	1-1/4	.609	2.48
1	1	4213x16	1-5/8	1-1/2	.811	2.84

Male FOR-SEAL® Male Pipe Adapter




TUBE O.D.	MALE PIPE SIZE	CATALOG NUMBER	HEX C	D	D1	L
3/8	3/8	4205x6x6	3/4	.264	.406	1.30
1/2	3/8	4205x8	7/8	.378	.406	1.45
1/2	1/2	4205x8x8	7/8	.378	.484	1.64
5/8	1/2	4205x10	1-1/16	.484	.531	1.82
3/4	1/2	4205x12x8	1-1/4	.406	.484	1.87
3/4	3/4	4205x12	1-1/4	.609	.719	1.94
3/4	1	4205x12x16	1-3/8	.609	.938	1.87
1	1	4205x16	1-1/2	.811	.938	2.19
1-1/4	1-1/4	4205x20	1-3/4	1.024	1.250	2.30

45° Male Elbow



MALE TUBE O.D.	MALE PIPE THREAD	CATALOG NUMBER	D	D1	M	N	ACROSS FLATS
1/4	1/8	4355x4	.172	.188	.63	.64	9/16
3/8	1/4	4355x6	.264	.281	.74	.86	3/4
1/2	3/8	4355x8	.378	.406	.80	.95	7/8
5/8	1/2	4355x10	.484	.531	.92	1.17	1-1/16
3/4	3/4	4355x12	.609	.719	1.02	1.20	1-5/16
1	1	4355x16	.812	.939	1.18	1.48	1-5/8
1-1/4	1-1/4	4355x20	1.026	1.252	1.26	1.67	1-5/8
1-1/2	1-1/2	4355x24	1.262	1.502	1.45	1.77	1-7/8


Straight Thread O-Ring Connector 45° Elbow
(Ref. SAE No. 520320)



MALETUBE O.D.	MALE PORT SIZE	CATALOG NUMBER	D	D1	M	M1	ACROSS FLATS
1/4	1/4	4365x4	.172	.172	.63	1.18	9/16
1/4	3/8	4365x4x6	.172	.264	.68	1.30	3/4
3/8	1/4	4365x6x4	.264	.172	.74	1.22	3/4
3/8	3/8	4365x6	.264	.264	.74	1.30	3/4
3/8	1/2	4365x6x8	.264	.390	.74	1.43	3/4
1/2	3/8	4365x8x6	.378	.264	.80	1.27	3/4
1/2	1/2	4365x8	.378	.390	.80	1.43	3/4
1/2	5/8	4365x8x10	.378	.484	.82	1.76	1-1/16
1/2	3/4	4365x8x12	.378	.609	.87	1.97	1-3/16
5/8	1/2	4365x10x8	.484	.390	.92	1.59	1-1/16
5/8	5/8	4365x10	.484	.484	.92	1.76	1-1/16
5/8	3/4	4365x10x12	.484	.609	.94	1.97	1-3/16
3/4	5/8	4365x12x10	.609	.484	1.02	1.81	1-3/16
3/4	3/4	4365x12	.609	.609	1.02	1.97	1-5/16
3/4	1	4365x12x16	.609	.811	1.16	2.06	1-5/16
1	3/4	4365x16x12	.811	.609	1.12	2.03	1-7/16
1	1	4365x16	.811	.811	1.18	2.06	1-1/2
1	1-1/4	4365x16x20	.811	1.081	1.26	2.11	1-5/8
1-1/4	1-1/4	4365x20	1.024	1.081	1.26	2.11	1-5/8
1-1/2	1-1/2	4365x24	1.260	1.312	1.45	2.11	1-7/8

For replacement straight thread O-ring, see page 254.


45° Bulkhead Elbow
(Ref. SAE No. 520201)



MALETUBE O.D.	CATALOG NUMBER	D	M	M1	ACROSS FLATS
1/4	4375x4	.172	.63	1.73	9/16
3/8	4375x6	.264	.74	1.91	3/4
1/2	4375x8	.378	.80	2.01	3/4
5/8	4375x10	.484	.92	2.23	1-1/16
3/4	4375x12	.609	1.02	2.39	1-3/16
1	4375x16	.811	1.18	2.57	1-7/16
1-1/4	4375x20	1.045	1.26	2.64	1-11/16
1-1/2	4375x24	1.312	1.45	2.64	1-7/8


For Bulkhead Nut, see page 257.

Union 90° Elbow
(Ref. SAE No. 520201)



MALE TUBE O.D.	CATALOG NUMBER	D	M	ACROSS FLATS
1/4	4505x4	.172	.85	9/16
3/8	4505x6	.264	.98	3/4
1/2	4505x8	.378	1.10	3/4
5/8	4505x10	.484	1.31	1-1/16
3/4	4505x12	.609	1.47	1-3/16
1	4505x16	.811	1.64	1-7/16
1-1/4	4505x20	1.045	1.76	1-5/8
1-1/2	4505x24	1.312	1.92	1-7/8
2	4505x32	-	-	-


Bulkhead Union 90° Elbow
(Ref. SAE No. 520701)



MALE TUBE O.D.	PORT SIZE	CATALOG NUMBER	D	D1	M	M1	I	ACROSS FLATS
1/4	1/4	4525x4	.172	.172	.89	1.85	1.24	9/16
3/8	3/8	4525x6	.264	.264	1.02	2.05	1.34	3/4
1/2	1/2	4525x8	.378	.378	1.14	2.18	1.44	7/8
5/8	5/8	4525x10	.484	.484	1.36	1.36	1.44	1-1/16
3/4	3/4	4525x12	.609	.609	1.52	2.64	1.60	1-5/16
1	1	4525x16	.811	.811	1.67	2.80	1.64	1-5/8
1-1/4	1-1/4	4525x20	1.024	1.024	1.79	2.97	1.66	1-7/8
1-1/2	1-1/2	4525x24	1.260	1.260	1.95	3.13	1.66	1-7/8

For bulkhead nut, see page 257.


90° Male Elbow



MALE TUBE O.D.	PORT SIZE	CATALOG NUMBER	D	D1	M	N	ACROSS FLATS
1/4	1/8	4405x4	.172	.188	.85	.78	9/16
3/8	1/4	4405x6	.264	.281	.80	1.09	3/4
1/2	3/8	4405x8	.378	.406	1.10	1.22	3/4
5/8	1/2	4405x10	.484	.531	1.31	1.47	1-1/16
3/4	3/4	4405x12	.609	.719	1.47	1.59	1-5/16
1	1	4405x16	.812	.939	1.64	1.97	1-5/8
1-1/4	1-1/4	4405x20	1.026	1.252	1.76	2.38	1-5/8
1-1/2	1-1/2	4405x24	1.262	1.502	1.92	2.64	1-7/8

Straight Thread O-Ring 90° Elbow


(Ref. SAE No. 520220)



MALE TUBE O.D.	PORT SIZE	CATALOG NUMBER	D	D1	M	M1	ACROSS FLATS
1/4	1/4	4515x4	.172	.172	.85	1.29	9/16
1/4	5/16	4515x4x5	.172	.234	.85	1.29	9/16
1/4	3/8	4515x4x6	.172	.264	.92	1.45	3/4
1/4	1/2	4515x4x8	.172	.390	.97	1.60	3/4
3/8	1/4	4515x6x4	.264	.172	.98	1.37	3/4
3/8	5/16	4515x6x5	.264	.234	.98	1.37	3/4
3/8	3/8	4515x6	.264	.264	.98	1.45	3/4
3/8	1/2	4515x6x8	.264	.390	1.04	1.60	3/4
3/8	5/8	4515x6x10	.264	.484	1.15	1.97	3/4
3/8	3/4	4515x6x12	.264	.609	1.25	2.17	1-3/16
1/2	5/8	4515x8x10	.378	.484	1.21	1.97	1-1/16
1/2	3/4	4515x8x12	.378	.484	1.32	2.17	1-1/16
1/2	3/8	4515x8x6	.378	.264	1.10	1.44	3/4
1/2	1/2	4515x8	.378	.390	1.10	1.60	3/4
5/8	5/8	4515x10	.484	.484	1.31	1.97	1-1/16
5/8	3/4	4515x10x12	.484	.609	1.41	2.17	1-3/16
5/8	1/2	4515x10x8	.484	.390	1.31	1.80	1-1/16
3/4	5/8	4515x12x10	.609	.484	1.47	2.01	1-5/16
3/4	3/4	4515x12	.609	.609	1.47	2.17	1-5/16
3/4	1	4515x12x16	.609	.811	1.62	2.35	1-5/16
3/4	1/2	4515x12x8	.609	.390	1.47	1.84	1-3/16
1	3/4	4515x16x12	.811	.609	1.64	2.32	1-5/8
1	7/8	4515x16x14	.811	.609	1.64	2.32	1-5/8
1	1	4515x16	.811	.811	1.64	2.35	1-5/8
1	1-1/4	4515x16x20	.811	1.081	1.76	2.45	1-5/8
1-1/4	1	4515x20x16	1.024	.811	1.76	2.42	1-5/8
1-1/4	1-1/4	4515x20	1.024	1.081	1.76	2.45	1-7/8
1-1/4	1-1/2	4515x20x24	1.024	1.312	1.92	2.59	1-7/8
1-1/2	1-1/4	4515x24x20	1.312	1.081	1.92	2.59	1-7/8
1-1/2	1-1/2	4515x24	1.312	1.312	1.92	2.59	1-7/8


For replacement straight thread O-ring, see page 176.

90° Elbow Straight Thread Swivel - Long




MALE TUBE O.D.	MALE PORT SIZE	CATALOG NUMBER	D	D1	M	N	ACROSS FLATS
1/4	1/4	4515x4L	.172	.180	.85	2.23	9/16
3/8	3/8	4515x6L	.264	.300	.98	2.61	3/4
1/2	1/2	4515x8L	.378	.398	1.10	2.95	3/4
5/8	5/8	4515x10L	.484	.498	1.31	3.51	1-1/16
3/4	3/4	4515x12L	.609	.616	1.47	3.97	1-3/16
1	1	4515x16L	.812	.852	1.64	4.51	1-7/16
1-1/4	1-1/4	4515x20L	1.026	1.090	1.76	4.98	1-5/8
1-1/2	1-1/2	4515x24L	1.262	1.326	1.92	5.48	1-7/8

90° Straight Thread Swivel (Ref. SAE No. 520281)





FEMALE TUBE O.D.	PORT SIZE	CATALOG NUMBER	D	D1	M	M1	HEX C	ACROSS FLATS
1/4	1/4	4535x4	.165	.180	1.04	1.29	11/16	9/16
3/8	3/8	4535x6	.264	.300	1.15	1.45	13/16	3/4
1/2	1/2	4535x8	.258	.398	1.49	1.60	15/16	7/8
5/8	5/8	4535x10	.453	.498	1.62	1.97	1-1/8	1-1/16
3/4	3/4	4535x12	.547	.616	1.82	2.17	1-3/8	1-3/8
1	1	4535x16	.783	.852	2.10	2.35	1-5/8	1-5/8
1-1/4	1-1/4	4535x20	1.026	1.090	2.29	2.45	1-7/8	1-5/8
1-1/2	1-1/2	4535x24	1.262	1.326	2.41	2.59	2-1/4	1-7/8

Union Tee (Ref. SAE No. 520401)



MALE TUBE O.D. A	MALE TUBE O.D. B	MALE TUBE O.D. C	CATALOG NUMBER	D	D1	M	M1	M2	ACROSS FLATS
1/4	1/4	1/4	4705x4	.172	.172	.85	.85	.85	9/16
3/8	3/8	3/8	4705x6	.264	.264	.98	.98	.98	3/4
3/8	3/8	1/2	4705x6x8x8	.264	.378	1.04	1.04	1.10	3/4
1/2	3/8	1/2	4705x8x8x8	.264	.378	.98	.98	1.10	3/4
1/2	1/2	1/2	4705x8	.378	.378	1.10	1.10	1.10	3/4
5/8	5/8	5/8	4705x10	.484	.484	1.31	1.31	1.31	1-1/16
3/4	3/4	3/4	4705x12	.609	.609	1.47	1.47	1.47	1-3/16
1	1	1	4705x16	.811	.811	1.64	1.64	1.64	1-5/8
1-1/4	1-1/4	1-1/4	4705x20	1.024	1.024	1.76	1.76	1.76	1-5/8
1-1/2	1-1/2	1-1/2	4705x24	1.260	1.260	1.92	1.92	1.92	1-7/8



Straight Thread Branch Tee
(Ref. SAE No. 520429)



TUBE O.D.	PORT SIZE	CATALOG NUMBER	D	D1	M	M1	ACROSS FLATS
1/4	1/4	4715x4	.172	.172	.85	1.29	9/16
3/8	3/8	4715x6	.264	.264	.98	1.45	3/4
3/8	1/2	4715x6x8	.264	.391	1.04	1.60	7/8
1/2	3/8	4715x8x6	.378	.264	1.10	1.44	3/4
1/2	1/2	4715x8	.378	.390	1.10	1.60	3/4
5/8	5/8	4715x10	.484	.484	1.31	1.97	1-1/16
3/4	3/4	4715x12	.609	.609	1.47	2.17	1-3/16
3/4	1	4715x12x16	.609	.812	1.62	2.35	1-5/8
1	1	4715x16	.811	.845	1.64	2.35	1-5/8
1-1/4	1	4715x20x16	1.046	.845	1.76	2.45	1-15/16
1-1/4	1-1/4	4715x20	1.046	1.081	1.76	2.45	1-7/8
1-1/2	1-1/2	4715x24	1.260	1.313	1.92	2.59	1-7/8

For replacement straight thread O-ring, see page 254.

Straight Thread Run Tee
(Ref. SAE No. 520428)




MALE TUBE O.D. A	MALE TUBE O.D. B	MALE TUBE O.D. C	CATALOG NUMBER	D	D1	M	M1	ACROSS FLATS
1/4	1/4	1/4	4716x4	.172	.172	.85	1.29	9/16
1/4	1/4	3/8	4716x4x6	.172	.264	1.39	1.45	3/4
3/8	3/8	3/8	4716x6	.264	.264	.98	1.45	3/4
1/2	1/2	1/2	4716x8	.378	.391	1.10	1.60	7/8
5/8	5/8	5/8	4716x10	.484	.484	1.31	1.97	1-1/16
3/4	3/4	3/4	4716x12	.609	.609	1.47	2.17	1-3/16
3/4	3/4	1	4716x12x16	.609	.812	1.62	2.32	1-7/16
3/4	1	3/4	4716x12x16x12	.609	.812	1.62	2.35	1-7/16
1	1	3/4	4716x16x12	.812	.609	1.64	2.35	1-7/16
1	1	1	4716x16	.812	.845	1.64	2.35	1-7/16
1-1/4	1-1/4	1-1/4	4716x20	1.046	1.081	1.76	2.45	1-7/8
1-1/2	1-1/2	1-1/2	4716x24	1.313	1.313	1.92	2.59	1-7/8

For replacement straight thread O-ring, see page 254.

FOR-SEAL®


Bulkhead Run Tee (Ref. SAE No. 520958)



TUBE O.D.	CATALOG NUMBER	D	I	M	M1	M2	ACROSS FLATS
1/4	4726x4	.172	1.24	.89	.89	1.85	9/16
3/8	4726x6	.264	1.34	1.02	1.02	2.05	3/4
1/2	4726x8	.378	1.44	1.14	1.14	2.18	3/4
5/8	4726x10	.484	1.60	1.36	1.36	2.48	1-1/16
3/4	4726x12	.609	1.64	1.52	1.52	2.65	1-3/16
1	4726x16	.812	1.66	1.67	1.67	2.80	1-7/16
1-1/4	4726x20	1.024	1.66	1.79	1.79	2.97	1-5/8
1-1/2	4726x24	1.260	1.66	1.95	1.95	3.13	1-7/8


For Bulkhead Nut, see page 257.

Male FOR-SEAL® Cross



TUBE O.D.	CATALOG NUMBER	D	M	ACROSS FLATS
1/4	4955x4	.172	.89	9/16
3/8	4955x6	.264	1.02	3/4
1/2	4955x8	.378	1.14	7/8
5/8	4955x10	.484	1.36	1-1/16
3/4	4955x12	.609	1.52	1-5/16
1	4955x16	.812	1.67	1-5/8
1-1/4	4955x20	1.026	1.79	1-5/8
1-1/2	4955x24	1.262	1.95	1-7/8

O-Ring, FOR-SEAL®



Material: Buna N, 90 Durometer

Temperature: -40°F to +250°F (-40°C to +121°C)

Standard o-ring complies with SAE specification SAE J515 Type CH

TUBE O.D.	CATALOG NUMBER	W	I.D.
1/4	4629x4	.070 ± .005	.301 ± .005
3/8	4629x6	.070 ± .005	.364 ± .005
1/2	4629x8	.070 ± .005	.489 ± .005
5/8	4629x10	.070 ± .005	.614 ± .005
3/4	4629x12	.070 ± .005	.739 ± .005
1	4629x16	.070 ± .006	.926 ± .006
1-1/4	4629x20	.070 ± .006	1.176 ± .006
1-1/2	4629x24	.070 ± .010	1.489 ± .010