

Hose - Medium Pressure

H069 General Purpose
Hose Truck Hose
SAE 100R5, SAE J1402 TYPE II, I,
DOT AIII, ABS



ABS¹

Typical Application: General purpose truck and hydraulic hose. For use in air brake, fuel, grease lines, high temperature petroleum oils and medium pressure hydraulic applications. -16 thru -48 sizes are not SAE or DOT approved for air brake applications.

Inner Tube: Nitrile

Reinforcement: 1 Fiber Braid - 1 Steel Braid

Cover: Fiber Braid

Temp. Range: -40°F to +212°F (-40°C to +100°C)

Air Brake: -40°F to +200°F (-40°C to +93°C)

¹Sizes -4 thru -12 only

CATALOG NUMBER	HOSE I.D.	HOSE O.D.	WORKING PRESS. (PSI)	MIN. BURST PRESS. (PSI)	MIN. BEND RADIUS	INCH. MERC. VAC. ("HG)	WT. PER 100 FT.	AVAIL. LENGTHS	HOSE END
H06904	3/16	33/64	3,000	12,000	3	25	16	50'	
H06904-250R								250'	
H06905	1/4	37/64	3,000	12,000	3-3/8	25	20	50'	
H06905-250R								250'	
H06906	5/16	43/64	2,250	9,000	4	25	23	50'	
H06906-250R								250'	
H06908	13/32	49/64	2,000	8,000	4-5/8	25	27	50'	
H06908-250R								250'	
H06910	1/2	59/64	1,750	7,000	5-1/2	25	36	50'	
H06910-250R								250'	
H06912	5/8	1-5/64	1,500	6,000	6-1/2	25	44	50'	
H06912-250R								250'	
H06916	7/8	1-15/64	800	3,200	7-3/8		46	50'	
H06916-250R								250'	
H06920	1-1/8	1-1/2	625	2,500	9		51	50'	
H06920-150								150'	
H06924	1-3/8	1-3/4	500	2,000	10-1/2		62	50'	
H06924-100								150'	
H06932	1-13/16	2-7/32	350	1,400	13-1/4		85	50'	
H06932-100								100	
H06940	2-3/8	2-7/8	350	1,400	24		143	50'	
H06948	3	3-9/16	200	800	33		209	50'	

C-O-C
069 'E' Series
(except size
-32, -40 & -48)
Pages
100-103

Field
Attachable
069 'D' & 'T'
Pages
218-219

Field
Attachable
247 'N' Series
(sizes -4 to
-16)
Pages
230-235

¹See pages 29-30 for applicable service pressures, required fire sleeves and qualified hose ends.

Equipment Assortments

SR3100W • Weatherhead Air Conditioning Assortment



Air Conditioning Assortment Kit; containing the most popular steel air conditioning hose ends for use with H757 air conditioning hose.

Included in Kit:

(various sizes)

- Bumped Tube O-Ring Male Swivels
- Bumped Tube O-Ring Male Swivel 90° Tube Elbows
- O-Ring Assortment
- Stackable Sturdy Steel Case (18" x 12" x 3")

CATALOG NUMBER	QTY.	CATALOG NUMBER	QTY.	CATALOG NUMBER	QTY.	CATALOG NUMBER	QTY.
75706E-Z47	4	75706E-Z87	4	75708E-Z08	4	ZW74706	4
75708E-Z49	4	75708E-Z89	4	75710E-Z10	4	ZW74708	4
75710E-Z51	4	75710E-Z91	4	75712E-Z12	4	ZW74710	4
75712E-Z51	4	75712E-Z91	4	75708E-Z66	4	ZW74712	4
75712E-Z53	4	75712E-Z93	4	75708E-Z68	4		
		75706E-Z06	4	75710E-Z70	4		

FF12139 • E-Z Clip System™



The E-Z Clip System is designed for assembly with Weatherhead Multi-Refrigerant hose GH134. It's engineered connection exceeds SAE J2064 and has been vibration and impulse tested.

Note: The E-Z Clip System has been designed to work exclusively with Weatherhead GH134 Hose.

Kit Contents Components

PART NUMBER	DESCRIPTION	QTY/PER KIT
1F40104-size	Clips	20 each size
1F40105-size	Cages	10 each size
FT1357	Assy. Tool	1
T-135	Hose Cutter	1
T-135B	Replacement Blade	1

BL-456 • Barb-Tite® Fittings and Hose Assortment



Making up an air line – oil line – transmission or power steering return line? The BL-456 assortment puts Eaton Barb-Tite® fittings and 1/4", 5/16", and 3/8" I.D. 350 PSI maximum operating pressure H101 hose at your fingertips for quick and easy assembly. Simply push ends on hose, and you have a hose assembly. No clamps required!

Measure the hose on top of the cabinet with the rule provided and then select the proper hose ends from the assortment in the two metal drawers. Within minutes the hose assembly is ready for installation.

Size: 15" wide, 16-1/2" high, 13-3/16" deep
16 Compartments in each drawer.

CATALOG NUMBER	QUANTITY	CATALOG NUMBER	QUANTITY	CATALOG NUMBER	QUANTITY	CATALOG NUMBER	QUANTITY
10004B-102	4	10004B-B04	4	10005B-C02	4	10006B-606	4
10004B-104	4	10004B-B05	4	10005B-C04	4	10006B-B06	4
10004B-304	4	10004B-Y04	4	10005B-Y05	4	10006B-Y06	4
10004B-305	4	10005B-102	4	10006B-102	4	H10104	25'
10004B-405	4	10005B-104	4	10006B-104	4	H10105	25'
10004B-604	4	10005B-405	4	10006B-106	4	H10106	25'
10004B-A04	4	10005B-B05	4	10006B-306	4	FS-501	1
10004B-A05	4	10005B-B06	4	10006B-406	4	BL-456X	1