

Hose - Medium Pressure

H166 Truck Hose
SAE J1402 TYPE AII DOT AII



Typical Application: General purpose truck hose. For use in air brake, fuel, diesel fuel and high temperatures petroleum oil applications.

Inner Tube: Nitrile

Reinforcement: 1 Fiber Braid - 1 Stainless Steel Braid

Cover: Fiber Braid

Temp. Range:

Air Brake: -40°F to +160°F (-40°C to +93°C)

Hydraulic Fluid: -40°F to +250°F (-40°C to +100°C)

*16 and 20 sizes not SAE or DOT approved for air brake applications.

CATALOG NUMBER	HOSE I.D.	HOSE O.D.	WORKING PRESS. (PSI)	MIN. BURST PRESS. (PSI)	MIN. BEND RADIUS	INCH. MERC. VAC. ("HG)	WT. PER 100 FT.	AVAIL. LENGTHS	HOSE END
H16604	3/16	33/64	1,500	6,000	1-1/2	25	11	50'	
H16604-250R								250'	
H16605	1/4	37/64	500	2,000	1-3/4	25	13	50'	
H16605-250R								250'	C-O-C 069 'E' Series Pages 100-103
H16606	5/16	43/64	500	2,000	2	25	18	50'	
H16606-250R								250'	Field Attachable 069 'D' Series Pages 218-219
H16608	13/32	49/64	500	2,000	2-5/16	25	21	50'	
H16608-250R								250'	
H16610	1/2	59/64	450	1,800	2-3/4	25	29	50'	
H16610-250R								250'	
H16612	5/8	1-5/64	450	1,800	3-1/4	25	37	50'	
H16612-250R								250'	247 'N' Series except -20 size) Pages 230-235
H16616*	7/8	1-15/64	250	1,000	4	25	38	50'	
H16616-250R*								250'	
H16620*	1-1/8	1-33/64	250	1,000	5-1/2	25	46	50'	

H209 General Purpose Hose



Typical Application: General hydraulic and pneumatic service; high temperature industrial cleaning and car wash applications.

Inner Tube: Nylon 11

Reinforcement: 1 Fiber Braid

Cover: Polyurethane

Temp. Range: -40°F to +200°F (-40°C to +93°C)

CATALOG NUMBER	HOSE I.D.	HOSE O.D.	WORKING PRESS. (PSI)	MIN. BURST PRESS. (PSI)	MIN. BEND RADIUS	WT. PER 100 FT.	AVAIL. LENGTHS	HOSE END
H20904-500R	1/4	29/64	2,250	9,000	1-1/2	5	500'	
H20905-500R	5/16	1/2	1,750	7,000	1-3/4	6	500'	
H20906-250R	3/8	9/16	1,350	5,400	2-1/2	7	250'	C-O-C 'E' Series Pages 92-99
H20908-250R	1/2	45/64	1,000	4,000	3-1/2	9	250'	

Equipment Assortments

Fleet Hose and Fitting Assortment



These assortments are ideal for servicing that fleet account. The DOT-approved hose and fittings will enable the user to make up cham-

ber lines, connect to glad-hand couplings, and provide routing for air brake lines. The general purpose H069 provides for fuel, oil, water,

power steering, and transmission lines. A self-contained assortment in a super cabinet, all set up for easy serviceability!

FA-100 • Fleet Hose and Fitting Assortment (with Cabinet)

CATALOG NUMBER	QUANTITY	CATALOG NUMBER	QUANTITY	CATALOG NUMBER	QUANTITY
H06904	50'	24706N-106	5	24710N-608	5
H06906	50'	24706N-406	5	24710N-610	2
H06908	50'	24706N-604	5	33806-A	20
H06910	50'	24706N-605	5	33806-B	5
H16606	50'	24706N-606	5	33806B-Y06	5
H16608	50'	24706N-608	5	33806B-Y24	5
H33806	50'	24706N-756	5	33806B-Y26	2
24704N-102	5	24706N-B06	5	33806B-Y28	5
24704N-104	5	24708N-106	5	33806B-Y34	5
24704N-604	5	24708N-108	5	33806B-Y36	5
24704N-B04	5	24708N-406	5	33806B-Y38	5
24705N-104	5	24708N-608	5	FH-15X	1
24705N-605	5	24710B-Y58	2	HD-1X	1
24705N-B05	5	24710B-Y60	5		
24706N-104	5	24710N-108	5		

FA-100-CO • Fleet Hose and Fitting Assortment (Contents Only)

CATALOG NUMBER	QUANTITY	CATALOG NUMBER	QUANTITY	CATALOG NUMBER	QUANTITY
H06904	50'	24706N-106	5	24710N-608	5
H06906	50'	24706N-406	5	24710N-610	2
H06908	50'	24706N-604	5	33806-A	20
H06910	50'	24706N-605	5	33806-B	5
H16606	50'	24706N-606	5	33806B-Y06	5
H16608	50'	24706N-608	5	33806B-Y24	5
H33806	50'	24706N-756	5	33806B-Y26	2
24704N-102	5	24706N-B06	5	33806B-Y28	5
24704N-104	5	24708N-106	5	33806B-Y34	5
24704N-604	5	24708N-108	5	33806B-Y36	5
24704N-B04	5	24708N-406	5	33806B-Y38	5
24705N-104	5	24708N-608	5		
24705N-605	5	24710B-Y58	2		
24705N-B05	5	24710B-Y60	5		
24706N-104	5	24710N-108	5		

HA-574 • Fuel Hose Merchandiser



Now you can make those custom hose assemblies in minutes for instant service on fuel and oil line replacements. The attractive HA-574 includes H057 hose in all popular sizes for low pres-

sure fuel, EEC and PCV lines. Weatherhead H057 low pressure fuel line hose has Nitrile inner tube, fiber braid reinforcement, and Hypalon cover for long life compatibility with gasohol,

leaded and unleaded fuels. The HC-574X rack can be easily installed on pegboard, wall, or metal shelving with the included hardware.

CATALOG NUMBER	QUANTITY	DESCRIPTION
H05703	25'	Hose
H05704	25'	Hose
H05705	25'	Hose
H05706	25'	Hose
HC-574X	1	Rack + 4 Dowels