

## Equipment

### Hose Cutting Equipment



Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on page 3.

#### T-80 • Coll-O-Cut® Portable Hand- Powered Cutter



Portable! Efficient!  
Economical! No outside power source needed. Quick, clean cuts through all fiber, 1 and 2 wire braid hose up to 1" I.D.

Ideal companion for the T-465 Portable Coll-O-Crimp Machine. Completely portable hose assembly capabilities – only from Eaton.

**Weight:** 15 lbs

**Replacement Blade:**  
T-1080

#### T-60A • Portable Cutter



An excellent heavy-duty cutting machine. The T-60A is a portable power saw that can cut all hoses, including wire-reinforced. Includes three abrasive blades.

**Replacement Blade:**  
T-1060A 14" diameter

**Motor:** 3-1/2 H.P.,  
110/115 volts

**Amps:** 15

**Weight:** 45 lbs.

**RPM:** 3500

**Note:** 3 blades are mounted on shaft for shipping purposes. Remove prior to use.

#### T-10B • Hose Cutting Machine



The T-10B hose cutting machine assures quick, clean, right angle cuts, eliminating ragged and frayed cut ends which make hose assembly difficult and are a possible cause of premature hose failure. A powerful 1 H.P. motor and belt-driven blade cut all low, medium and high pressure fabric and wire-braided hose from 3/16" through 1-1/4" I.D. 2 wire hose. Specifically designed for cutting hose, the T-10B is a natural companion to the T-400-1 Coll-O-Crimp and T-300 hose assembly machines.

The T-10B is shipped complete with a 7" smooth edge cutting wheel capable of cutting one-wire hose through 1-1/4", T-1047. To receive T-10B with a scalloped blade T-1047-1 capable of cutting two-wire hose through 1-1/4" instead of standard smooth blade, order T-10B-1.

**Replacement Blades:**

T-1047 (Smooth)

T-1047-1 (Scalloped)

**Replacement Belt for  
T-10B & T-10C:**

T-10-V1 Belt

**Motor:** 1 H.P., 3450 RPM,  
115, 60 cycle, single phase

**Size:** 13" wide, 24" long, 17" high

**Weight:** 85 lbs.

**Amps Drawn:** 115 volts – 15

**Replacement Parts:**

T-10-D Hose/Dowel

T-10-H Handle

T-10-P Pusher

## Equipment

### Hose Cutting Equipment



Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on page 3.

#### T-9-1 & T-9-3 • Hose Cutting Machine



The T-9-1 and T-9-3 provide the capability for cutting multi-spiral and braided wire-reinforced hose through 2" I.D. This machine is a perfect companion for the T-440 Coll-O-Crimp II Plus. Includes scalloped blade.

**Note:** The T-9-1 and T-9-3 are shipped less a line cord and plug. An electrician is recommended for direct electrical hook-up.

#### T-9-1:

**Motor:** 3 H.P., 230 volts, 60 cycle, single phase

**Size:** 24" wide, 24" deep, 24" high

**Weight:** Approx. 255 lbs.

**Amps Drawn:**  
At 230 volts – 17

#### T-9-3:

**Motor:** 3 H.P., 230 volts, 60 cycle, 3 phase

**Size and Weight:**  
Same as T-9-1

**Amps Drawn:**  
At 230 volts – 8

#### Replacement Blade:


T-75-14 Scalloped

T-75-17 Carborundum

T-75-11 Smooth

**Guard:** T-9-G

#### T-70 • Hose Cutting Machine



This cutting machine easily handles all one and two braided wire hose through 4" I.D., up to 2" I.D. 4-spiral and up to 1-1/2" I.D. 6 multi-spiral reinforced hose. That makes this machine ideal for cutting most hydraulic and pneumatic hoses as well as a variety of industrial fluid transfer hoses. The T-70 uses a 14" cutting blade for cutting all 1 & 2 wire braid and through 2" 4 spiral hose. The

scalloped toothed blade is for cutting industrial transfer hoses through 4" and the smooth beveled blade for cutting hose with a wire braid cover. T-70 includes a scalloped blade.

#### Replacement Blade:

T-1070 Steel Scalloped

T-1071 Steel Scalloped Toothed

T-1072 Steel Smooth Beveled

**Motor:** 4.2 H.P., 110/115 volts, single phase

**Size:** 22" wide, 19" deep, 25" high

**Weight:** Approx. 65 lbs.  
**Amps Drawn:** 115 volts – 20

#### Hose Cutting and Skiving Wheels



CATALOG NUMBER	TYPE	BLADE DIA.	HOLE DIA.	MACHINE USED ON
<b>Cutting Wheels</b>				
T-1042	Carborundum	8"	5/8"	T-10A
T-1047	Steel Smooth	7"	5/8"	T-10B & T-10C
T-1047-1	Steel Scalloped	7"	5/8"	T-10B & T-10C
T-1060	Carborundum	12"	1"	T-60
T-1060A	Carborundum	14"	1"	T-60A
T-1070	Steel Scalloped	14"	1"	T-70
T-1071	Steel Scalloped Toothed	14"	1"	T-70
T-1072	Steel Smooth Beveled	14"	1"	T-70
T-1080	Carborundum	8"	1"	T-80
T-75-11	Steel Smooth	10"	3/4"	T-9/T-75
T-75-14	Steel Scalloped	10"	3/4"	T-9/T-75
T-75-17	Carborundum	10"	3/4"	T-9/T-75
<b>Skiving Wheels</b>				
T-1040	Wire	6"	5/8"	T-10
T-1046	Wire	8"	5/8"	T-10A
T-75-12	Wire	8"	1"	T-75
<b>Belts</b>				
T-76-B	Reinforced	1"		Old T-76/T-76-1