

## Equipment

### Coll-O-Crimp Pumps

#### T-402-2 • Air/Hydraulic Pump



For use with T-400-1.

(Some models have air port on right side)

**Note:** It is recommended that a filter, regulator, lubricator and air pressure gauge be installed in the air line as close as possible to the pump. Filter, Regulator and Lubricator units not included.

#### Pump Specifications:

**Dimensions:** 5-1/4" high, 12-1/2" long, 5" wide

**Weight:** 18 lbs.

**Operation Pressure:** 4000-4200 PSI

**Reservoir Capacity:** 1 pint

**Hydraulic Oil:** Use Enerpac Oil ONLY

**Outlet Port Size:** 3/8" NPT

**Inlet (Air) Port Size:** 1/4" NPT

**Inlet Air Pressure Required:** 60 to 120 PSI

**Filter:** F23A3T02

**Regulator:** R23RGL02

**Lubricator:** L43MPL02

#### T-403-2 • Hand Pump



For use with T-400-1.

#### Pump Specifications:

**Dimensions:** 7 high, 21" long, 4-3/4" wide

**Weight:** 9 lbs.


**Operation Pressure:** 4000-4200 PSI

**Reservoir Capacity:** 1 qt.

**Outlet Port Size:** 3/8"

**NPT Hydraulic Oil:** Use Enerpac Oil ONLY

#### T-411 • Electric Pump (220 volt)



For repair and replacement items for the following pumps please contact an Enerpac Distributor at [www.enerpac.com](http://www.enerpac.com): T-402-2, T-403-2, T-460-2, T-462-2, T-480-2, T-480-3, T-481-110 & T-482-2.

**Replacement pump for T-410-1 C-O-C II Press ONLY.**

#### Replacement Parts:

CATALOG NUMBER	DESCRIPTION
<b>Newer Pumps:</b>	
T-421-FP	220v 4 wire Female electrical receptacle. See page 245 for illustration.
<b>Older T-411 Pumps:</b>	
T-411-B	By-pass module
T-411-G	Release Handle Spring (Models prior to 1982)
T-411-S	Micro-Switch (Models prior to 1982)
<b>Older T-401-1 Pumps:</b>	
T-401-1B	Replacement Gasket between motor and square reservoir
T-401-1BC	Breather Cap for Fenner-Stone pumps
T-401-1G	Relief Handle Spring (Models prior to 1982)
T-401-1S	Toggle Switch
T-401-SVF	Fenner Shuttle Valve
140-06761	Relay for T-421U or T-421U-BC pumps

## Equipment

### Coll-O-Crimp Pumps

#### T-462-2 • Air/Hydraulic Pump



For use with T-462.

The Weatherhead T-462-2 power unit is a air/hydraulic pump designed for use with the T-462 portable system. Ideal if you have the availability of compressed air in your shop or in the field via a portable compressor.

#### Pump Specifications:

**Dimensions:** 4" high, 13" long

**Weight:** 8 lbs.

**Operation Pressure:** 0-10,000 PSI

**Reservoir Capacity:** 10 cu in.

**Relief Valve Setting:** 10,000 PSI

**Hydraulic Oil:** Use Enerpac Oil ONLY

Regulator to be set for 100-120 PSI inlet air.

#### T-480-2 • Two-Stage Hand Pump



For use with T-480-HP.

#### Pump Specifications:

**Dimensions:** 7-3/16" high x 21-1/64" long x 4-3/4" wide

**Weight:** 9 lbs.

**Operation Pressure:** 0-10,000 PSI

**Hydraulic Oil:** Use Enerpac Oil ONLY

#### T-480-3 • Turbo Air/ Hydraulic Pump



For use with T-480-TA.

#### Pump Specifications:

**Dimensions:** 8-1/4" High x 12-3/8" long x 8" wide

**Weight:** 16-1/2 lbs.

**Operation Pressure:** 0-10,000 PSI

**Hydraulic Oil:** Use Enerpac Oil ONLY

For repair and replacement items for the following pumps please contact an Enerpac Distributor at [www.enerpac.com](http://www.enerpac.com): T-402-2, T-403-2, T-460-2, T-462-2, T-480-2, T-480-3, T-481-110 & T-482-2.