Equipment

Coll-O-Crimp Super IT-420



Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on page 3.



The Coll-O-Crimp Super I is a versatile machine ideal for your shop, factory, construction, and mine locations. Big capacity combined with lever activated crimping gives you wide coverage and a quick and simple way to make factory-quality hose assemblies.

Capacity: 3/16" I.D. 1 fiber braid through 1-1/4" 6 spiral hose; for hoses other than 4 and 6 spiral, conversion tooling is required. See pages 284-287 for details.

Mounting: Bench or C-40X cabinet.

See pages 296-299 for cabinet (not included).

Size: 22" high, 10" wide, 20-1/2" deep

Weight: 210 lbs.

Pump Required (sold separately): T-421U or T-421U-110 T-420-1 · Coll-O-Crimp Super I Press ONLY Includes T-420-M Instructions

A CAUTION

The Coll-O-Crimp power source has the pressure relief valve set at 4000 to 4200 PSI. Damage to the press will result if higher pressures are used and warranty will be voided.

T-420-N • Coll-O-Crimp Super I Package Includes one each of the following:

CATALOG NUMBER	DESCRIPTION	
T-420-1	Coll-O-Crimp Super I Press and T-420-M Instructions	
T-421U	220v Electric Pump	
T-400-2C	'U' Series Collet- 1/4"	
T-400-3C	'U' Series Collet- 3/8"	
T-400-4C	'U' Series Collet- 1/2"	
T-400-5C	'U' Series Collet- 3/4"	
T-400-6C	'U' Series Collet- 1"	
T-400-10	Spacer Ring- Black	
T-400-11	Spacer Ring- Silver	
T-400-62	Spacer Ring Yellow	
T-410-22	36" Pump to Press Hose Assembly	
T-420-25	Adapter Ring for T-400 Series Collets	
T-420-4CN	430 'U' Series Collet- 1/2"	
T-420-5CN	430 'U' Series Collet-3/4"	
T-420-6CN	430 'U' Series Collet- 1"	
T-420-7CN	430 'U' Series Collet- 1-1/4"	

T-420N-110 • Coll-O-Crimp Super I Package

CATALOG	DESCRIPTION
T-420-1	Coll-O-Crimp Super I Press and T-420-M Instructions
T-421U-110	110v Electric Pump
T-400-2C	'U' Series Collet- 1/4"
T-400-3C	'U' Series Collet- 3/8"
T-400-4C	'U' Series Collet- 1/2"
T-400-5C	'U' Series Collet- 3/4"
T-400-6C	'U' Series Collet- 1"
T-400-62	Spacer Ring-Yellow
T-400-10	Spacer Ring- Black
T-400-11	Spacer Ring- Silver
T-410-22	36" Pump to Press Hose Assembly
T-420-25	Adapter Ring for T-400 Series Collets
T-420-4CN	430 'U' Series Collet- 1/2"
T-420-5CN	430 'U' Series Collet-3/4"
T-420-6CN	430 'U' Series Collet- 1"
T-420-7CN	430 'U' Series Collet- 1-1/4"

Insert - Base Plate

T-420-26

Coll-O-Crimp Super I Repair and Replacement Items				
CATALOG NUMBER	DESCRIPTION	CATALOG NUMBER	DESCRIPTION	
T-420-1M	Micro-Switch for T-420-1 Press	T-420-G	Linkage Assembly	
140-0677	Tool Locator Bracket	T-420-2R	Rack	
T-420-B	Pusher Bolt and Washers	T-420-2K	Pinion Shaft Assembly	
T-420-E	Shroud Decal	T-420-2S	Replacement Pinion Gear Shaft	
T-420-H	Handle	T-420-2G	Replacement Pinion Gear	
T-420-L	Light Bulb	T-400-G	1.5 oz. Tube High Efficiency * Grease	
T-420-LA	Light Assembly	T-421U-BC	Breather Cap for T-421U Pump	
T-420-LS	Light Switch	140-06745	Pusher Wear Plates includes (1) Left and (1) Right	
T-420-M	Instructions for T-420-1	140-06748	Pusher Wear Plates Screws (1)	
T-420-P	Pusher Set (2) with Wear Plates and Screws	See pages 364 for replacement pumps.		
T-420-S	Press Shroud with Decals	Refer to pages 356-367 for Coll-O-Crimp tooling, tooling packages and pumps.		

347

Refer to safety information regarding Coll-O-Crimp crimping procedures on pages 349-350.

Equipment

Coll-O-Crimp T-440



Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on page 3.



The Coll-O-Crimp II Plus is ideal for factory, high performance machine operations, construction and mine locations. This machine offers the capabilities of crimping all of the crimp style hose ends Weatherhead offers. With this coverage, this heavy-duty crimper can handle all of your crimping needs.

Capacity: 3/16* I.D. 1 fiber braid through 2" 6 spiral hose; for hoses other than 4 and 6 spiral, conversion tooling is required. See page 356-361 for details.

Mounting: Bench

Size: 27" high, 12" wide, 21" deep

Weight: 450 lbs.

Pump Required (sold separately): T-441, see page 347.

Reference pages 356-367 for Coll-O-Crimp tooling, tooling packages and pumps.

Note: Seal kits for T-410 and T-440 are not sold separately. Crimpers must be sent in and torqued by Weatherhead,

Refer to safety information regarding Coll-O-Crimp crimping procedures on pages 349-350.

CATALOG

A CAUTION

The Coll-O-Crimp power source has the pressure relief valve set at 5000 PSI. Damage to the press will result if higher pressures are used and warranty may be voided.

Note: These packages include tooling to crimp H430 hose. For additional tooling order from pages 356-361.

Note: For T-410 press, use T-410-BB switch.

T-440-N • Coll-O-Crimp II Plus Package

Includes one each of the following:

MOMBER	DESCRIPTION		
T-440-1	C-O-C II Plus Press, T-440-M Instructions and 140-06741 Switch		
T-441	220v 2-stage Electric Pump		
T-410-4CN	430 'U' N/S Collet - 1/2" I.D.		
T-410-5CN	5CN 430 'U' N/S Collet – 3/4" I.D.		
T-410-6CN	430 "U" N/S Collet - 1" I.D.		
T-410-7CN	430 'U' N/S Collet - 1-1/4" I.D.		
T-410-8N	430 'U' N/S Collet - 1-1/2° I.D.		
T-410-9N	430 'U' N/S Collet - 2" I.D.		
T-410-22	36" Pump to Press Hose Assembly		

Repair & Replacement Items:

CATALOG	DESCRIPTION
T-410-26R	Base Plate Insert (7") (T-440-1)
T-410-26	Base Plate Insert (6") (T-410-1)
T-410-28	Tool Locator Bracket
T-410-B	Pusher Bolt and Washers
T-410-E	Shroud Decal
T-440-M	Instructions for T-440-1
T-410-P	Pusher Set (2) for T-410-1 and T-440-1
T-410-1M	Microswitch for T-410-1 & T-440-1
T-421-FP	4 prong female electrical outlet See page 245 for illustration.
T-400-G	1.5 oz. Tube High Efficiency * Grease
140-06741	Pump Switch for the T-440-1 crimper using T-441 pump
T-410-BB	Pump Switch for T-410-1 crimper using T-421U or T- 421U-110 pump only