

Equipment

Coll-O-Crimp Portable T-465



Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on page 3.

Portable Coll-O-Crimp



Reference pages 356-366 for Coll-O-Crimp tooling, tooling packages and pumps.

Refer to safety information regarding Coll-O-Crimp crimping procedures on page 331.

The Portable Coll-O-Crimp is a completely PORTABLE hose assembly system. NO ELECTRICAL POWER SOURCE IS NEEDED. Hand pump powered, lightweight, vise or stand mounted, this crimper is ideal for your portable crimping needs.

Capacity: 3/16" I.D. 1 fiber braid through 1-3/8" I.D. 1 wire hose and 1-1/4" 2 wire hose

Mounting: Vise/Stand

Size: 12-1/2" high, 8-1/2" wide, 5-1/2" deep

Weight: 31 lbs.

The vise bracket, die ring, pusher, decal and instruction kit are components of the T-465 Portable Coll-O-Crimp Press.

Pump Required (sold separately): T-460-2

T-465 • Portable Coll-O-Crimp Press ONLY



CAUTION

Use T-460-2 10,000 PSI hand pump only.



CAUTION

The Coll-O-Crimp power source has the pressure relief valve set at 10000 PSI. Damage to the press will result if higher pressures are used and warranty will be voided.

T-465-HP • Portable Coll-O-Crimp Package

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-465	Portable Coll-O-Crimp Press
T-460-2	Hand Pump (10,000 PSI)
T-450-3	Quick Disconnect Hose Assembly

For replacement pump see page 363-365.

T-465 HPU • Portable Coll-O-Crimp Package

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-465-HP	Portable Coll-O-Crimp Package
T-400-2C	'U' Series Collet - 1/4"
T-400-3C	'U' Series Collet - 3/8"
T-400-4C	'U' Series Collet - 1/2"
T-400-10	Black Spacer Ring
T-400-62	Yellow Spacer Ring

T-465-HP80 • Portable Coll-O-Crimp Package

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-465-HP	See above for contents.
T-80	Coll-O-Cut Portable Saw

T-465 HPU80 • Portable Coll-O-Crimp Package

Includes one each of the following:

CATALOG NUMBER	DESCRIPTION
T-465-HPU	See above for contents.
T-80	Coll-O-Cut Portable Saw

Equipment

Hose Cutting Equipment



Refer to safety information regarding Coll-O-Crimp hose, hose fittings and assembly equipment compatibility on page 3.

T-80 • Coll-O-Cut® Portable Hand- Powered Cutter



Portable! Efficient!
Economical! No outside power source needed. Quick, clean cuts through all fiber, 1 and 2 wire braid hose up to 1" I.D.

Ideal companion for the T-465 Portable Coll-O-Crimp Machine. Completely portable hose assembly capabilities – only from Eaton.

Weight: 15 lbs

Replacement Blade:
T-1080

T-60A • Portable Cutter



An excellent heavy-duty cutting machine. The T-60A is a portable power saw that can cut all hoses, including wire-reinforced. Includes three abrasive blades.

Replacement Blade:
T-1060A 14" diameter

Motor: 3-1/2 H.P.,
110/115 volts

Amps: 15

Weight: 45 lbs.

RPM: 3500

Note: 3 blades are mounted on shaft for shipping purposes. Remove prior to use.

T-10B • Hose Cutting Machine



The T-10B hose cutting machine assures quick, clean, right angle cuts, eliminating ragged and frayed cut ends which make hose assembly difficult and are a possible cause of premature hose failure. A powerful 1 H.P. motor and belt-driven blade cut all low, medium and high pressure fabric and wire-braided hose from 3/16" through 1-1/4" I.D. 2 wire hose. Specifically designed for cutting hose, the T-10B is a natural companion to the T-400-1 Coll-O-Crimp and T-300 hose assembly machines.

The T-10B is shipped complete with a 7" smooth edge cutting wheel capable of cutting one-wire hose through 1-1/4", T-1047. To receive T-10B with a scalloped blade T-1047-1 capable of cutting two-wire hose through 1-1/4" instead of standard smooth blade, order T-10B-1.

Replacement Blades:

T-1047 (Smooth)

T-1047-1 (Scalloped)

**Replacement Belt for
T-10B & T-10C:**

T-10-V1 Belt

Motor: 1 H.P., 3450 RPM,
115, 60 cycle, single phase

Size: 13" wide, 24" long, 17" high

Weight: 85 lbs.

Amps Drawn: 115 volts – 15

Replacement Parts:

T-10-D Hose/Dowel

T-10-H Handle

T-10-P Pusher