


▲ Refer to safety information regarding tubing selection on page 1.

Adapters can be used to adapt standard steel brake lines to the different size ports used in dual master cylinders. The tube O.D. is the outside diameter of the steel brake line. Thread size can be determined by measuring with a U.S. or Metric screw pitch gauge. See page 16.



**STANDARD INVERTED FLARE TUBE AND THREAD SIZE**

Tube Size	1/8	3/16	1/4	5/16	3/8	7/16	1/2	5/8	3/4	7/8	1
Thread Size	5/16-28	3/8-24	7/16-24	1/2-20	5/8-18	11/16-18	3/4-18	7/8-18	1-1/16-16	1-3/16-16	1-5/16-16

Standard Tube Nut (Steel)	Tube Size	Catalog Number	Long Tube Nut (Steel)	Tube O.D.	Thread Size	Catalog Number			
	<p>*11/16-18 Thread</p>	1/8 3/16 1/4 5/16 3/8 3/8 7/16 1/2 5/8 3/4 7/8 1		105x2 105x3 105x4 105x5 105x6 105x6x7* 105x7 105x8 105x10 105x12 105x14 105x16		3/16 1/4	3/8-24 7/16-24	7896x3 7896x4	
Dual Master Cylinder Adapter	Inverted Male Thread	Inverted Female Thread	Catalog Number	Dual Master Cylinder Adapter			Inverted Male Thread (Exceptions Noted)	Inverted Female Thread (Exceptions Noted)	Catalog Number
	3/16	3/16	1441				3/16(9/16-18)	3/16	7911
	5/16	3/16	7897	† Seat may be used for 3/16", 1/4", 5/16" Tube Connection with 1/2-20 Thread. *Seals On Hex Face (E)			3/16(1/2-20)	3/16	7913
							3/16(9/16-20)	3/16	7910
							3/16	1/4	7828
							1/4	3/16	7818
							7/16-20	1/4	7732*
							1/4 (9/16-18)	1/4	7908
							1/4	5/16†	7917
							5/16	3/16	7817*
							5/16	3/16	7909
							5/16	3/16(9/16-18)	7912
							5/16	1/4	7727*
							5/16	1/4	7829
							5/16	5/16	1074*
							5/16	3/8	7915
							3/8 NPTF	5/16	7771
							3/8	5/16	7916



## SS-88 • BRASS PIPE ASSORTMENT

Assortment contains 59 of the fastest moving brass pipe fittings.

**SIZE:** 11" wide, 1-3/4" high, 6-3/4" deep. **WEIGHT:** 3-1/2 lbs.

Catalog Number	Qty.	Catalog Number	Qty.	Catalog Number	Qty.
3152x2	5	3326x2	5	3400x2	5
3152x4	5	3326x4	5	3400x4	2
3152x6	2	3326x6	2	3400x6	2
3220x4x2	2	3350x2	5	3500x2	2
3220x6x4	2	3350x4	4	3500x4	2
3300x2	5	3350x6	2	BF-40X	1
3300x4	2				



## BF-40 • HYDRAULIC BRAKE FITTINGS ASSORTMENT

The BF-40 assortment of fast moving hydraulic brake fittings is a must for any shop doing brake service work. Contains the adapters needed to convert large size ports in master cylinders to accept standard steel brake lines plus the brass tees used in the installation of electric towed trailer brakes.

Assortment is organized in a compact, handy plastic box for easy selection.

**SIZE:** 11" wide, 1-3/4" high, 6-3/4" deep. **WEIGHT:** 4 lbs. (approx.)

Catalog Number	Qty.	Catalog Number	Qty.	Catalog Number	Qty.
7818	2	7901	2	7911	2
7828	2	7904	2	7912	2
7829	2	7905	2	7913	2
7897	2	7906	2	7914	2
7898	2	7908	2	7917	2
7900	2	7910	2	7933	2
				BF-40X	1



## BF-41 • HYDRAULIC BRAKE LINE ADAPTER ASSORTMENT

The BF-41 assortment contains the adapters needed to convert the oversize master cylinder ports to accept the inverted flare nut used on standard replacement steel brake lines. The adapters eliminate the need to cut line, install oversize nut and double flare tubing as well as converting the port to standard size threads for the life of the car. Extra standard nuts and the unions needed to connect two steel brake lines when a non-standard length is required are also included in the assortment. The contents including the illustrations of parts are shown on the inside cover of the box.

**SIZE:** 11" wide, 1-3/4" high, 6-3/4" deep. **WEIGHT:** 4 lbs. (approx.)

Catalog Number	Qty.	Catalog Number	Qty.	Catalog Number	Qty.
105x3	10	302x4	5	7896x3	5
105x4	10	302x5	5	7896x4	5
105x5	10	302x6	2	7897	2
105x6	5	7818	2	7908	2
105x6x7	2	7828	2	7917	2
302x3	5	7829	2	BF-40X	1