


90° Elbow - For-Seal® Female Swivel to Male Straight Thread O-Ring


(Ref. SAE No. 520281)



Tube O.D.	Port Size	Catalog Number	D	D1	M	M1	Hex C	Across Flats
1/4	1/4	4535x4	.165	.180	1.04	1.29	11/16	9/16
3/8	3/8	4535x6	.264	.300	1.15	1.45	13/16	3/4
1/2	1/2	4535x8	.358	.398	1.49	1.60	15/16	7/8
5/8	5/8	4535x10	.453	.498	1.62	1.97	1-1/8	1-1/16
3/4	3/4	4535x12	.547	.616	1.82	2.17	1-3/8	1-3/8
1	1	4535x16	.783	.852	2.10	2.35	1-5/8	1-5/8
1-1/4	1-1/4	4535x20	1.026	1.090	2.29	2.45	1-7/8	1-5/8
1-1/2	1-1/2	4535x24	1.262	1.326	2.41	2.59	2-1/4	1-7/8

Union Tee


(Ref. SAE No. 520401)



Tube O.D. A	Tube O.D. B	Tube O.D. C	Catalog Number	D	D1	M	M1	M2	Across Flats
1/4	1/4	1/4	4705x4	.172	.172	.85	.85	.85	9/16
3/8	3/8	3/8	4705x6	.264	.264	.98	.98	.98	3/4
3/8	3/8	1/2	4705x6x6x8	.264	.378	1.04	1.04	1.10	3/4
1/2	3/8	1/2	4705x6x6x8	.264	.378	.98	.98	1.10	3/4
1/2	1/2	1/2	4705x8	.378	.378	1.10	1.10	1.10	3/4
5/8	5/8	5/8	4705x10	.484	.484	1.31	1.31	1.31	1-1/16
3/4	3/4	1/4	4705x12x12x4	.609	.172	1.47	1.47	1.19	1-5/16
3/4	3/4	3/8	4705x12x12x6	.609	.264	1.47	1.47	1.25	1-5/16
3/4	3/4	3/4	4705x12	.609	.609	1.47	1.47	1.47	1-3/16
1	1	3/4	4705x16x16x12	.811	.609	1.64	1.64	1.62	1-5/8
1	1	1	4705x16	.811	.811	1.64	1.64	1.64	1-5/8
1-1/4	1-1/4	1	4705x20x20x16	1.024	.811	1.76	1.76	1.76	1-5/8
1-1/4	1-1/4	1-1/4	4705x20	1.024	1.024	1.76	1.76	1.76	1-5/8
1-1/2	1-1/2	1-1/2	4705x24	1.260	1.260	1.92	1.92	1.92	1-7/8

Straight Thread Branch Tee

(Ref. SAE No. 520429)




Tube O.D.	Port Size	Catalog Number	D	D1	M	M1	Across Flats
1/4	1/4	4715x4	.172	.172	.85	1.29	9/16
3/8	3/16	4715x6x6x3	.264	.130	.98	1.26	3/4
3/8	3/8	4715x6	.264	.264	.98	1.45	3/4
3/8	1/2	4715x6x6x8	.264	.391	1.04	1.60	7/8
1/2	3/8	4715x6x8x6	.378	.264	1.10	1.44	3/4
1/2	1/2	4715x8	.378	.390	1.10	1.60	3/4
5/8	5/8	4715x10	.484	.484	1.31	1.97	1-1/16
3/4	3/4	4715x12	.609	.609	1.47	2.17	1-3/16
3/4	1	4715x12x12x16	.609	.812	1.62	2.35	1-5/8
1	1	4715x16	.811	.845	1.64	2.35	1-5/8
1-1/4	1	4715x20x20x16	1.046	.845	1.76	2.45	1-15/16
1-1/4	1-1/4	4715x20	1.046	1.081	1.76	2.45	1-7/8
1-1/2	1-1/2	4715x24	1.260	1.313	1.92	2.59	1-7/8

For replacement straight thread O-ring, see page 147.

Straight Thread O-Ring

Steel
Fittings


90° Elbow Extra Long - Male JIC 37° to Straight Thread O-Ring



Replacement O-rings page 194.


Tube O.D.	Port Size	Catalog Number	D	D1	M	N	Across Flats
3/8	3/8	TF5515x6LL	.297	.297	1.06	2.08	5/8
1/2	1/2	TF5515x8LL	.391	.391	1.25	2.50	13/16
5/8	5/8	TF5515x10LL	.484	.484	1.45	3.25	15/16
3/4	3/4	TF5515x12LL	.609	.609	1.66	3.34	1-1/8

90° Elbow - For-Seal® Female Swivel to Male Straight Thread O-Ring (Ref. SAE No. 520281)



Tube O.D.	Port Size	Catalog Number	D	D1	M	M1	Hex C	Across Flats
1/4	1/4	4535x4	.165	.180	1.04	1.29	11/16	9/16
3/8	3/8	4535x6	.264	.300	1.15	1.45	13/16	3/4
1/2	1/2	4535x8	.358	.398	1.49	1.60	15/16	7/8
5/8	5/8	4535x10	.453	.498	1.62	1.97	1-1/8	1-1/16
3/4	3/4	4535x12	.547	.616	1.82	2.17	1-3/8	1-3/8
1	1	4535x16	.783	.852	2.10	2.35	1-5/8	1-5/8
1-1/4	1-1/4	4535x20	1.026	1.090	2.29	2.45	1-7/8	1-5/8
1-1/2	1-1/2	4535x24	1.262	1.326	2.41	2.59	2-1/4	1-7/8

90° Elbow - For-Seal® to Straight Thread O-Ring (Ref. SAE No. 520220)




Tube O.D.	Port Size	Catalog Number	D	D1	M	M1	Across Flats
1/4	1/4	4515x4	.172	.172	.85	1.29	9/16
1/4	5/16	4515x4x5	.172	.234	.85	1.29	9/16
1/4	3/8	4515x4x6	.172	.264	.92	1.45	3/4
1/4	1/2	4515x4x8	.172	.390	.97	1.60	3/4
3/8	1/4	4515x6x4	.264	.172	.98	1.37	3/4
3/8	5/16	4515x6x5	.264	.234	.98	1.37	3/4
3/8	3/8	4515x6	.264	.264	.98	1.45	3/4
3/8	1/2	4515x6x8	.264	.390	1.04	1.60	3/4
3/8	5/8	4515x6x10	.264	.484	1.15	1.97	3/4
3/8	3/4	4515x6x12	.264	.609	1.25	2.17	1-3/16
1/2	3/8	4515x8x6	.378	.264	1.10	1.44	3/4
1/2	1/2	4515x8	.378	.390	1.10	1.60	3/4
1/2	5/8	4515x8x10	.378	.484	1.21	1.97	1-1/16
1/2	3/4	4515x8x12	.378	.484	1.32	2.17	1-1/16
5/8	1/2	4515x10x8	.484	.390	1.31	1.80	1-1/16
5/8	5/8	4515x10	.484	.484	1.31	1.97	1-1/16
5/8	3/4	4515x10x12	.484	.609	1.41	2.17	1-3/16
3/4	1/2	4515x12x8	.609	.390	1.47	1.84	1-3/16
3/4	5/8	4515x12x10	.609	.484	1.47	2.01	1-5/16
3/4	3/4	4515x12	.609	.609	1.47	2.17	1-5/16
3/4	1	4515x12x16	.609	.811	1.62	2.35	1-5/16
1	3/4	4515x16x12	.811	.609	1.64	2.32	1-5/8
1	7/8	4515x16x14	.811	.609	1.64	2.32	1-5/8
1	1	4515x16	.811	.811	1.64	2.35	1-5/8
1	1-1/4	4515x16x20	.811	1.081	1.76	2.45	1-5/8
1-1/4	1	4515x20x16	1.024	.811	1.76	2.42	1-5/8
1-1/4	1-1/4	4515x20	1.024	1.081	1.76	2.45	1-7/8
1-1/4	1-1/2	4515x20x24	1.024	1.312	1.92	2.59	1-7/8
1-1/2	1-1/4	4515x24x20	1.312	1.081	1.92	2.59	1-7/8
1-1/2	1-1/2	4515x24	1.312	1.312	1.92	2.59	1-7/8

Replacement Straight Thread O-rings page 194.
Replacement For-Seal O-rings page 163.

• Available in stainless steel.

Ermeto® Straight Thread O-Ring Branch Tee

Stainless Steel No. 7727x
(Ref. SAE No. 080429)




Replacement O-rings see below.

Tube O.D.	Port Size	Catalog Number	D	M	N	Across Flats
1/4	1/4	7715x4	.203	.89	1.03	7/16
3/8	3/8	7715x6	.281	1.05	1.25	9/16
1/2	1/2	7715x8	.422	1.25	1.45	3/4

For-Seal® to Straight Thread O-Ring Branch Tee

(Ref. SAE No. 520429)




For replacement straight thread O-ring, see below.
For replacement FOR-SEAL® O-ring, see page 163.

Tube O.D.	Port Size	Catalog Number	D	D1	M	M1	Across Flats
1/4	1/4	4715x4	.172	.172	.85	1.29	9/16
3/8	3/8	4715x6	.264	.264	.98	1.45	3/4
3/8	1/2	4715x6x8	.264	.391	1.04	1.60	3/4
1/2	1/2	4715x8	.378	.390	1.10	1.60	3/4
5/8	5/8	4715x10	.484	.484	1.31	1.97	1-1/16
3/4	3/4	4715x12	.609	.609	1.47	2.17	1-3/16
1	1	4715x16	.811	.811	1.64	2.35	1-1/16

For-Seal® to Straight Thread Run Tee


(Ref. SAE No. 520428)



For replacement straight thread O-ring, see below.
For replacement FOR-SEAL® O-ring, see page 163.

Tube O.D. A	Tube O.D. B	Port Size C	Catalog Number	D	D1	M	M1	Across Flats
1/4	1/4	1/4	4716x4	.172	.172	.85	1.29	9/16
1/4	3/8	1/4	4716x4x4x6	.172	.264	1.39	1.45	3/4
3/8	3/8	3/8	4716x6	.264	.264	.98	1.45	3/4
1/2	1/2	1/2	4716x8	.378	.391	1.10	1.60	7/8
5/8	5/8	5/8	4716x10	.484	.484	1.31	1.97	1-1/16
3/4	3/4	3/4	4716x12	.609	.609	1.47	2.17	1-3/16
3/4	1	3/4	4716x12x12x16	.609	.812	1.62	2.32	1-7/16
3/4	3/4	1	4716x12x16x12	.609	.812	1.62	2.35	1-7/16
1	3/4	1	4716x16x16x12	.812	.609	1.64	2.35	1-7/16
1	1	1	4716x16	.812	.812	1.64	2.35	1-7/16
1-1/4	1-1/4	1-1/4	4716x20	1.046	1.046	1.76	2.45	1-7/8
1-1/2	1-1/2	1-1/2	4716x24	1.313	1.313	1.92	2.59	1-7/8

Straight Thread O-Ring



Material: Buna-N, 90 Durometer

Temperature Range: -40°F to +250°F
(-40°C to +121°C)

Standard O-ring complies with SAE specification J515 Type CH.

Port Size	Catalog Number	W	I.D.
1/16	7629x1	.058 ± .003	.185 ± .005
1/8	7629x2	.064 ± .003	.239 ± .005
3/16	7629x3	.064 ± .003	.301 ± .005
1/4	7629x4	.072 ± .003	.351 ± .005
5/16	7629x5	.072 ± .003	.414 ± .005
3/8	7629x6	.078 ± .003	.468 ± .005
7/16	7629x7	.082 ± .003	.530 ± .005
1/2	7629x8	.087 ± .003	.644 ± .005
5/8	7629x10	.097 ± .003	.755 ± .005
3/4	7629x12	.116 ± .004	.924 ± .006
7/8	7629x14	.116 ± .004	1.048 ± .006
1	7629x16	.116 ± .004	1.171 ± .006
1-1/4	7629x20	.118 ± .004	1.475 ± .010
1-1/2	7629x24	.118 ± .004	1.720 ± .010
2	7629x32	.118 ± .004	2.337 ± .010

• Available in stainless steel.