


Straight Thread O-Ring Run Tee

(Ref. SAE No. 520428)




For replacement straight thread O-ring, see page 147.

Tube O.D.	Port Size	Tube O.D.	Catalog Number	D	D1	M	M1	M2	Across Flats
A	B	C							
1/4	1/4	1/4	4716x4	.172	.172	.85	1.29	.85	9/16
1/4	1/4	3/8	4716x4x4x6	.172	.264	1.39	1.45	1.39	3/4
3/8	3/8	3/8	4716x6	.264	.264	.98	1.45	.98	3/4
1/2	1/2	1/2	4716x8	.378	.391	1.10	1.60	1.10	7/8
5/8	5/8	5/8	4716x10	.484	.484	1.31	1.97	1.31	1-1/16
3/4	3/4	3/4	4716x12	.609	.609	1.47	2.17	1.47	1-3/16
3/4	3/4	1	4716x12x12x16	.609	.812	1.62	2.32	1.64	1-7/16
3/4	1	3/4	4716x12x16x12	.609	.812	1.62	2.35	1.62	1-7/16
1	1	3/4	4716x16x16x12	.812	.609	1.64	2.35	1.62	1-7/16
1	1	1	4716x16	.812	.845	1.64	2.35	1.64	1-7/16
1-1/4	1-1/4	1-1/4	4716x20	1.046	1.081	1.76	2.45	1.76	1-7/8
1-1/2	1-1/2	1-1/2	4716x24	1.313	1.313	1.92	2.59	1.92	1-7/8

Bulkhead Run Tee


(Ref. SAE No. 520958)



For Bulkhead Nut, see page 157.


Tube O.D.	Catalog Number	D	I	M	M2	Across Flats
1/4	4726x4	.172	1.24	.89	1.85	9/16
3/8	4726x6	.264	1.34	1.02	2.05	3/4
1/2	4726x8	.378	1.44	1.14	2.18	3/4
5/8	4726x10	.484	1.60	1.36	2.48	1-1/16
3/4	4726x12	.609	1.64	1.52	2.65	1-3/16
1	4726x16	.812	1.66	1.67	2.80	1-7/16
1-1/4	4726x20	1.024	1.66	1.79	2.97	1-5/8
1-1/2	4726x24	1.260	1.66	1.95	3.13	1-7/8

Male For-Seal® Cross



Tube O.D.	Catalog Number	D	M	Across Flats
1/4	4955x4	.172	.89	9/16
3/8	4955x6	.264	1.02	3/4
1/2	4955x8	.378	1.14	7/8
5/8	4955x10	.484	1.36	1-1/16
3/4	4955x12	.609	1.52	1-5/16
1	4955x16	.812	1.67	1-5/8
1-1/4	4955x20	1.026	1.79	1-5/8
1-1/2	4955x24	1.262	1.95	1-7/8

O-Ring, For-Seal®





Material: Buna N, 90 Durometer
 Temperature: -40°F to +250°F (-40°C to +121°C)
 Standard o-ring complies with SAE specification SAE J515 Type CH

Tube O.D.	Catalog Number	W	I.D.
1/4	4629x4	.070 ± .005	.301 ± .005
3/8	4629x6	.070 ± .005	.364 ± .005
1/2	4629x8	.070 ± .005	.489 ± .005
5/8	4629x10	.070 ± .005	.614 ± .005
3/4	4629x12	.070 ± .005	.739 ± .005
1	4629x16	.070 ± .006	.926 ± .006
1-1/4	4629x20	.070 ± .006	1.176 ± .006
1-1/2	4629x24	.070 ± .010	1.489 ± .010

Ermeto® Straight Thread O-Ring Branch Tee

Stainless Steel No. 7727x
(Ref. SAE No. 080429)




Replacement O-rings see below.

Tube O.D.	Port Size	Catalog Number	D	M	N	Across Flats
1/4	1/4	7715x4	.203	.89	1.03	7/16
3/8	3/8	7715x6	.281	1.05	1.25	9/16
1/2	1/2	7715x8	.422	1.25	1.45	3/4

For-Seal® to Straight Thread O-Ring Branch Tee

(Ref. SAE No. 520429)




For replacement straight thread O-ring, see below.
For replacement FOR-SEAL® O-ring, see page 163.

Tube O.D.	Port Size	Catalog Number	D	D1	M	M1	Across Flats
1/4	1/4	4715x4	.172	.172	.85	1.29	9/16
3/8	3/8	4715x6	.264	.264	.98	1.45	3/4
3/8	1/2	4715x6x8	.264	.391	1.04	1.60	3/4
1/2	1/2	4715x8	.378	.390	1.10	1.60	3/4
5/8	5/8	4715x10	.484	.484	1.31	1.97	1-1/16
3/4	3/4	4715x12	.609	.609	1.47	2.17	1-3/16
1	1	4715x16	.811	.811	1.64	2.35	1-1/16

For-Seal® to Straight Thread Run Tee


(Ref. SAE No. 520428)



For replacement straight thread O-ring, see below.
For replacement FOR-SEAL® O-ring, see page 163.

Tube O.D. A	Tube O.D. B	Port Size C	Catalog Number	D	D1	M	M1	Across Flats
1/4	1/4	1/4	4716x4	.172	.172	.85	1.29	9/16
1/4	3/8	1/4	4716x4x4x6	.172	.264	1.39	1.45	3/4
3/8	3/8	3/8	4716x6	.264	.264	.98	1.45	3/4
1/2	1/2	1/2	4716x8	.378	.391	1.10	1.60	7/8
5/8	5/8	5/8	4716x10	.484	.484	1.31	1.97	1-1/16
3/4	3/4	3/4	4716x12	.609	.609	1.47	2.17	1-3/16
3/4	1	3/4	4716x12x12x16	.609	.812	1.62	2.32	1-7/16
3/4	3/4	1	4716x12x16x12	.609	.812	1.62	2.35	1-7/16
1	3/4	1	4716x16x16x12	.812	.609	1.64	2.35	1-7/16
1	1	1	4716x16	.812	.812	1.64	2.35	1-7/16
1-1/4	1-1/4	1-1/4	4716x20	1.046	1.046	1.76	2.45	1-7/8
1-1/2	1-1/2	1-1/2	4716x24	1.313	1.313	1.92	2.59	1-7/8

Straight Thread O-Ring



Material: Buna-N, 90 Durometer

Temperature Range: -40°F to +250°F
(-40°C to +121°C)

Standard O-ring complies with SAE specification J515 Type CH.

Port Size	Catalog Number	W	I.D.
1/16	7629x1	.058 ± .003	.185 ± .005
1/8	7629x2	.064 ± .003	.239 ± .005
3/16	7629x3	.064 ± .003	.301 ± .005
1/4	7629x4	.072 ± .003	.351 ± .005
5/16	7629x5	.072 ± .003	.414 ± .005
3/8	7629x6	.078 ± .003	.468 ± .005
7/16	7629x7	.082 ± .003	.530 ± .005
1/2	7629x8	.087 ± .003	.644 ± .005
5/8	7629x10	.097 ± .003	.755 ± .005
3/4	7629x12	.116 ± .004	.924 ± .006
7/8	7629x14	.116 ± .004	1.048 ± .006
1	7629x16	.116 ± .004	1.171 ± .006
1-1/4	7629x20	.118 ± .004	1.475 ± .010
1-1/2	7629x24	.118 ± .004	1.720 ± .010
2	7629x32	.118 ± .004	2.337 ± .010

• Available in stainless steel.