


Male JIC 37° SAE to Female For-Seal®



Female Tube O.D.	Male 37° Tube Size	Catalog Number	Hex C1	Hex C	D	D1	L
1/4	1/4	4213x4	11/16	5/8	.172	.165	1.50
3/8	3/8	4213x6	13/16	3/4	.297	.264	1.62
1/2	1/2	4213x8	15/16	7/8	.397	.358	1.90
5/8	5/8	4213x10	1-1/8	1-1/16	.484	.453	2.25
3/4	3/4	4213x12	1-3/16	1-1/4	.609	.547	2.48
1	1	4213x16	1-5/8	1-1/2	.811	.783	2.84

Straight Thread O-Ring Connector

 Stainless Steel No. **5327x**

(Ref. SAE No. 070120)

Example assembly No. C5315x4




Tube O.D.	Port Size	Catalog Number	Hex C	D	D1 Opt.	I	L
1/8	1/8	C5315x2-	7/16	.062	.062*	.45	1.06
3/16	3/16	C5315x3	1/2	.125	.125*	.48	1.10
1/4	1/4	C5315x4-	9/16	.172	.172*	.55	1.23
1/4	5/16	C5315x4x5-	5/8	.172	.234*	.55	1.23
1/4	3/8	C5315x4x6-	11/16	.172	.297*	.55	1.29
1/4	1/2	C5315x4x8-	7/8	.172	.391*	.55	1.37
5/16	1/4	C5315x5x4	5/8	.234	.172	.55	1.23
5/16	5/16	C5315x5	5/8	.234	.234*	.55	1.23
5/16	3/8	C5315x5x6	11/16	.234	.297*	.55	1.29
3/8	1/4	C5315x6x4	11/16	.297	.172	.56	1.27
3/8	5/16	C5315x6x5	11/16	.297	.234	.56	1.27
3/8	3/8	C5315x6-	11/16	.297	.297*	.56	1.30
3/8	1/2	C5315x6x8-	7/8	.297	.391*	.56	1.38
3/8	5/8	C5315x6x10	1	.297	.484*	.56	1.50
1/2	3/8	C5315x8x6	13/16	.391	.297	.66	1.44
1/2	1/2	C5315x8-	7/8	.391	.391*	.66	1.48
1/2	5/8	C5315x8x10-	1	.391	.484*	.66	1.60
1/2	3/4	C5315x8x12-	1-1/4	.391	.609*	.66	1.76
5/8	1/2	C5315x10x8	1	.484	.391	.76	1.64
5/8	5/8	C5315x10-	1	.484	.484*	.76	1.70
5/8	3/4	C5315x10x12	1-1/4	.484	.609*	.76	1.86
5/8	1	C5315x10x16	1-1/2	.484	.844*	.76	1.89
3/4	1/2	C5315x12x8	1-1/4	.609	.391	.86	1.94
3/4	5/8	C5315x12x10	1-1/8	.609	.484	.86	1.88
3/4	3/4	C5315x12-	1-1/4	.609	.609*	.86	1.97
3/4	7/8	C5315x12x14	1-3/8	.609	.718*	.86	1.96
3/4	1	C5315x12x16	1-1/2	.609	.844*	.86	1.99
3/4	1-1/4	C5315x12x20	1-7/8	.609	1.078*	.86	2.08
7/8	7/8	C5315x14	1-3/8	.719	.719*	.89	1.99
1	5/8	C5315x16x10	1-1/2	.844	.484	.91	2.07
1	3/4	C5315x16x12	1-1/2	.844	.609	.91	2.04
1	1	C5315x16-	1-1/2	.844	.844*	.91	2.04
1	1-1/4	C5315x16x20	1-7/8	.844	1.078*	.91	2.12
1-1/4	1	C5315x20x16	1-7/8	1.078	.844	.96	2.33
1-1/4	1-1/4	C5315x20	1-7/8	1.078	1.078*	.96	2.17
1-1/4	1-1/2	C5315x20x24	2-1/8	1.078	1.312*	.96	2.24
1-1/2	1-1/4	C5315x24x20	2-1/8	1.312	1.078*	1.08	2.53
1-1/2	1-1/2	C5315x24	2-1/8	1.312	1.312*	1.08	2.37
1-1/2	2	C5315x24x32	2-3/4	1.312	1.781*	1.08	2.53
2	1-1/2	C5315x32x24	2-3/4	1.781	1.312*	1.33	2.81
2	2	C5315x32	2-3/4	1.781	1.781	1.33	2.78

 *Optional counterbore for D1.
 Replacement O-rings page 183.

Straight Thread O-Ring Extended Connector

(Ref. SAE No. 070122)

Example assembly No. C5316x4



Tube O.D.	Port Size	Catalog Number	Hex C	D	I	L
1/4	1/4	C5316x4	9/16	.172	1.39	2.08
3/8	3/8	C5316x6	11/16	.297	1.56	2.31
1/2	3/8	C5316x8x6	7/8	.297	1.56	2.38
1/2	1/2	C5316x8	7/8	.391	1.88	2.70
5/8	5/8	C5316x10	1	.484	2.09	3.04
3/4	3/4	C5316x12	1-1/4	.609	2.50	3.61
1	1	C5316x16	1-1/2	.844	2.84	3.98
1-1/4	1-1/4	C5316x20	1-7/8	1.078	3.47	4.69

Replacement O-rings page 183.

* Available in stainless steel.

Straight Thread O-Ring


Steel
Fittings

Straight Thread O-Ring Connector to Male JIC 37°

Stainless Steel No. 5327x

(Ref. SAE No. 070120)

Example assembly No. C35315x4




Replacement O-rings page 213.

Straight Thread O-Ring Extended Connector to Male JIC 37°

(Ref. SAE No. 070122)

Example assembly No. C35316x4



Replacement O-rings page 194.

Tube O.D.	Port Size	Catalog Number	Hex C	D	D1 Opt.	I	L
1/8	1/8	C5315x2-	7/16	.062	.062	.45	1.06
3/16	3/16	C5315x3	1/2	.125	.125	.48	1.10
1/4	1/4	C5315x4	9/16	.172	.172	.55	1.23
1/4	5/16	C5315x4x5*	5/8	.172	.234	.55	1.23
1/4	3/8	C5315x4x6	11/16	.172	.172	.55	1.29
1/4	1/2	C5315x4x8	7/8	.172	.391	.55	1.38
5/16	1/4	C5315x5x4	9/16	.234	.172	.55	1.23
5/16	5/16	C5315x5	5/8	.234	.234	.55	1.23
5/16	3/8	C5315x5x6	11/16	.234	.297	.55	1.30
3/8	1/4	C5315x6x4	5/8	.297	.172	.56	1.33
3/8	5/16	C5315x6x5	5/8	.297	.234	.56	1.30
3/8	3/8	C5315x6*	11/16	.297	.297	.56	1.30
3/8	1/2	C5315x6x8*	7/8	.297	.391	.56	1.38
3/8	5/8	C5315x6x10	1	.297	.484	.56	1.50
1/2	3/8	C5315x8x6	13/16	.391	.297	.66	1.44
1/2	1/2	C5315x8*	7/8	.391	.391	.66	1.48
1/2	5/8	C5315x8x10*	1	.391	.484	.66	1.60
1/2	3/4	C5315x8x12*	1-1/4	.391	.609	.66	1.76
5/8	1/2	C5315x10x8	15/16	.484	.391	.76	1.67
5/8	5/8	C5315x10*	1	.484	.484	.76	1.70
5/8	3/4	C5315x10x12	1-1/4	.484	.609	.76	1.86
5/8	1	C5315x10x16	1-1/2	.484	.844	.76	1.89
3/4	1/2	C5315x12x8	1-1/8	.609	.391	.86	1.94
3/4	5/8	C5315x12x10	1-1/8	.609	.484	.86	1.88
3/4	3/4	C5315x12*	1-1/4	.609	.609	.86	1.97
3/4	7/8	C5315x12x14	1-3/8	.609	.718	.86	1.97
3/4	1	C5315x12x16	1-1/2	.609	.844	.86	1.99
3/4	1-1/4	C5315x12x20	1-7/8	.609	1.078	.86	2.08
7/8	7/8	C5315x14	1-3/8	.718	.718	.89	1.99
1	5/8	C5315x16x10	1-3/8	.844	.484	.91	1.95
1	3/4	C5315x16x12	1-3/8	.844	.609	.91	2.04
1	1	C5315x16*	1-1/2	.844	.844	.91	2.04
1	1-1/4	C5315x16x20	1-7/8	.844	1.078	.91	2.12
1-1/4	1	C5315x20x16	1-11/16	1.078	.844	.96	2.20
1-1/4	1-1/4	C5315x20	1-7/8	1.078	1.078	.96	2.17
1-1/4	1-1/2	C5315x20x24	2-1/8	1.078	1.312	.96	2.25
1-1/2	1-1/4	C5315x24x20	2	1.312	1.078	1.08	2.34
1-1/2	1-1/2	C5315x24	2-1/8	1.312	1.312	1.08	2.37
1-1/2	2	C5315x24x32	2-3/4	1.312	1.781	1.08	2.53
2	1-1/2	C5315x32x24	2-5/8	1.781	1.312	1.33	2.78
2	2	C5315x32	2-3/4	1.784	1.784	1.33	2.78

STEEL

* Available in stainless steel.