


90° Elbow - Female JIC 37° Swivel to Male Straight Thread O-Ring


For replacement Straight Thread O-rings, see page 183.


Tube O.D.	Port Size	Catalog Number	Hex C	Hex C1	L	D
1/4	1/4	C5216x4x4	9/16	9/16	1.32	.17
1/4	3/8	C5216x4x6	11/16	11/16	1.37	.17
3/8	3/8	C5216x6x6	11/16	11/16	1.51	.30
3/8	1/2	C5216x6x8	11/16	7/8	1.58	.30
1/2	3/8	C5216x8x6	7/8	3/4	1.62	.30
1/2	1/2	C5216x8x8	7/8	7/8	1.61	.39
5/8	5/8	C5216x10x10	1	1	1.96	.48
3/4	3/4	C5216x12x12	1-1/4	1-1/4	2.17	.61
1	1	C5216x16x16	1-1/2	1-1/2	2.30	.84
1-1/4	1-1/4	C5216x20x20	2	1-7/8	2.47	1.08
1-1/2	1-1/2	C5216x24x24	2-1/8	2-1/8	2.63	1.31
2	2	C5216x32x32	2-3/4	2-3/4	2.95	1.78

Female JIC 37° Swivel to Female Pipe


Tube O.D.	Female Pipe	Catalog Number	Hex C	Hex C1	L	D
1/4	1/4	C5256x4x4	9/16	3/4	1.32	.172
3/8	3/8	C5256x6x6	11/16	7/8	1.63	.297
1/2	1/2	C5256x8x8	7/8	1-1/8	1.81	.391
3/4	3/4	C5256x12	1-1/4	1-1/4	2.08	.609
1	1	C5256x16	1-1/2	1-1/2	2.62	.844


**45° Male Elbow
Stainless Steel No. 5367x
(Ref. SAE No. 070302)**

Example assembly No. C35355x4




Tube O.D.	Male Pipe Thread	Catalog Number	D	D1	M	N	Across Flats
1/8	1/8	C5355x2	.062	.188	.66	.52	7/16
3/16	1/8	C5355x3	.125	.188	.66	.52	7/16
1/4	1/8	C5355x4	.172	.188	.72	.64	7/16
1/4	1/4	C5355x4x4	.172	.281	.83	.86	9/16
5/16	1/8	C5355x5	.234	.188	.77	.67	9/16
5/16	1/4	C5355x5x4	.234	.281	.83	.86	9/16
3/8	1/8	C5355x6x2	.297	.188	.83	.69	9/16
3/8	1/4	C5355x6	.297	.281	.83	.86	9/16
3/8	3/8	C5355x6x6	.297	.406	.98	.95	3/4
3/8	1/2	C5355x6x8	.297	.531	1.06	1.17	7/8
1/2	1/4	C5355x8x4	.391	.281	.98	.95	3/4
1/2	3/8	C5355x8	.391	.406	.98	.95	3/4
1/2	1/2	C5355x8x8	.391	.531	.99	1.17	7/8
5/8	3/8	C5355x10x6	.484	.406	1.11	1.00	7/8
5/8	1/2	C5355x10	.484	.531	1.11	1.17	7/8
3/4	1/2	C5355x12x8	.609	.531	1.28	1.20	1-1/16
3/4	3/4	C5355x12	.609	.719	1.28	1.20	1-1/16
1	3/4	C5355x16x12	.844	.719	1.47	1.27	1-5/16
1	1	C5355x16	.844	.938	1.47	1.48	1-5/16
1-1/2	1-1/2	C5355x24	1.312	1.500	1.78	1.77	1-7/8
1/8	1/8	TF5355x2	.062	.188	.66	.52	7/16
1/4	1/8	TF5355x4	.172	.188	.72	.64	1/2
1/4	1/4	TF5355x4x4	.172	.281	.81	.86	5/8
5/16	1/8	TF5355x5	.234	.188	.76	.64	9/16
5/16	1/4	TF5355x5x4	.234	.281	.83	.86	5/8
3/8	1/8	TF5355x6x2	.297	.188	.81	.66	5/8
3/8	1/4	TF5355x6	.297	.281	.82	.86	5/8
3/8	3/8	TF5355x6x6	.297	.406	.91	.95	13/16
3/8	1/2	TF5355x6x8	.297	.531	1.03	1.17	15/16
1/2	1/4	TF5355x8x4	.391	.281	.98	.94	13/16
1/2	3/8	TF5355x8	.391	.406	.98	.95	13/16
1/2	1/2	TF5355x8x8	.391	.531	1.12	1.17	15/16
5/8	3/8	TF5355x10x6	.484	.406	1.11	1.06	15/16
5/8	1/2	TF5355x10	.484	.531	1.11	1.17	15/16
5/8	3/4	TF5355x10x12	.484	.719	1.26	1.20	1-1/8
3/4	1/2	TF5355x12x8	.609	.531	1.28	1.17	1-1/8
3/4	3/4	TF5355x12	.609	.719	1.28	1.20	1-1/8
3/4	1	TF5355x12x16	.609	.938	1.42	1.48	1-3/8
1	3/4	TF5355x16x12	.844	.719	1.47	1.28	1-3/8
1	1	TF5355x16	.844	.938	1.47	1.48	1-3/8
1-1/4	1-1/4	TF5355x20	1.078	1.250	1.59	1.67	1-3/4
1-1/2	1-1/2	TF5355x24	1.312	1.500	1.78	1.77	2
2	2	TF5355x32	1.781	1.938	2.22	2.11	2-5/8

• Available in stainless steel.

JIC 37° Female Swivel to
Straight Thread O-Ring

Tube O.D.	Port Size	Catalog Number	Hex C	Hex C1	L	D
1/4	1/4	C5216x4x4	9/16	.56	.95	.172
1/4	3/8	C5216x4x6	9/16	.69	1.00	.172
3/8	3/8	C5216x6x6	11/16	.69	1.11	.297
3/8	1/2	C5216x6x8	11/16	.88	1.18	.297
1/2	3/8	C5216x8x6	7/8	3/4	1.71	.297
1/2	1/2	C5216x8x8	7/8	.88	1.17	.391
5/8	5/8	C5216x10x10	1	1.00	1.45	.484
3/4	3/4	C5216x12x12	1-1/4	1.25	1.61	.609
1	1	C5216x16x16	1-1/2	1.50	1.69	.844
1-1/4	1-1/4	C5216x20x20	2	1.88	1.82	1.078
1-1/2	1-1/2	C5216x24x24	2-1/8	2.12	1.88	1.312
2	2	C5216x32x32	2-3/4	2.75	2.01	1.781

Replacement O-rings page 194.

45° Elbow - Male Straight
Thread O-Ring to Male JIC 37°
(Ref. SAE No. 070320)
Example assembly No. C35365x4

Tube O.D.	Port Size	Catalog Number	D	D1	M	N	Across Flats
1/4	1/4	C5365x4	.172	.172	.72	1.05	7/16
5/16	5/16	C5365x5*	.234	.234	.77	1.05	9/16
3/8	3/8	C5365x6	.297	.297	.83	1.14	5/8
1/2	1/2	C5365x8	.391	.391	.98	1.30	3/4
1/2	5/8	C5365x8x10	.391	.484	.99	1.52	7/8
5/8	5/8	C5365x10	.484	.484	1.11	1.52	7/8
3/4	5/8	C5365x12x10	.609	.484	1.28	1.57	1-1/16
3/4	3/4	C5365x12	.609	.609	1.28	1.73	1-1/16
1	1	C5365x16	.844	.844	1.47	1.86	1-5/16
1-1/4	1-1/4	C5365x20	1.078	1.078	1.59	1.91	1-5/8
1-1/2	1-1/2	C5365x24*	1.312	1.312	1.78	1.91	1-7/8
1/4	1/4	TF5365x4	.172	.172	.72	1.05	1/2
5/16	5/16	TF5365x5	.234	.234	.77	1.05	9/16
3/8	3/8	TF5365x6	.297	.297	.83	1.14	5/8
3/8	1/2	TF5365x6x8	.297	.391	.87	1.30	13/16
1/2	3/8	TF5365x8x6	.391	.297	.98	1.17	13/16
1/2	1/2	TF5365x8	.391	.391	.98	1.30	13/16
1/2	5/8	TF5365x8x10	.391	.484	.99	1.52	15/16
5/8	1/2	TF5365x10x8	.484	.391	1.09	1.41	15/16
5/8	5/8	TF5365x10	.484	.484	1.09	1.52	15/16
3/4	5/8	TF5365x12x10	.609	.484	1.30	1.58	1-1/8
3/4	3/4	TF5365x12	.609	.609	1.28	1.73	1-1/8
3/4	1	TF5365x12x16	.609	.844	1.45	1.86	1-3/8
7/8	7/8	TF5365x14	.718	.718	1.39	1.80	1-1/4
1	3/4	TF5365x16x12	.844	.609	1.47	1.86	1-3/8
1	1	TF5365x16	.844	.844	1.47	1.86	1-3/8
1-1/4	1-1/4	TF5365x20	1.078	1.078	1.59	1.91	1-3/4
1-1/2	1-1/2	TF5365x24	1.312	1.312	1.78	1.91	2
2	2	TF5365x32	1.781	1.781	2.22	1.86	2-5/8

Replacement O-rings page 194.

*Special order only.