

 Refer to safety information on page 1 & 2.

Coiled Air Brake Tube Assemblies



*Each catalog number contains a coiled red assembly and a coiled blue assembly.

Conforms to SAE J844 Type B and SAE J1131.

Conforms to DOT FMVSS 571.106.

Maximum Working Pressure 150 PSI. Minimum Burst: 950 PSI.

Temperature Range -40°F to +200°F.

Brass end fittings with spring guards and 1/2" male pipe connections.


Spring guards zinc plated for maximum corrosion resistance.

Color coding, red for emergency and blue for service, provides you with error free installation.

Preassembled for immediate installation.

Catalog Number	Tube O.D.	Male Pipe	Working Length	Pigtail Length
W1206*	1/2	1/2	12'	6"
W1212*	1/2	1/2	12'	12"
W1512*	1/2	1/2	15'	12"

Gladhand Couplings



- Die cast aluminum body
- Conforms to SAE J318
- Connects to 1/2" pipe
- Includes seal

Catalog Number

W79850	SERVICE (Signal) (Blue clip; Connects only to service)
W79851	EMERGENCY (Supply line) (Red clip; Connects only to emergency)
W76150	UNIVERSAL (Connects to all three styles)


Gladhand Seal

For use with W79850, W79851, W76150.



Catalog Number

W14630



AB-45 • AIR BRAKE FITTINGS ASSORTMENT

This assortment of draincocks, shutoffs and air brake fittings for use with 1/4", 3/8", 1/2" copper tubing is a must for jobbers and fleet service shops. Provides excellent coverage for air brake tube and hose service requirements. The large plastic drawers and the illustrated labels for the 15 drawer cabinet included in assortment make positive part selection simple and quick.

AB-45 Contents

Catalog Number	Quantity	Catalog Number	Quantity	Catalog Number	Quantity	Catalog Number	Quantity
1360x6	20	1368x6	10	145	10	6747	1
1360x8	20	1368x6x2	5	33806-A	20	6748	1
1360x10	10	1368x6x6	5	33806-B	5	6749	1
1360x12	10	1368x8	5	33806B-Y06	2	FH-15X	1
1361x6	20	1368x10	5	33806B-Y24	5	FS-800	1
1361x8	5	1369x4x4	5	33806B-Y28	5	W05465	5
1361x10	5	1369x6	10	33806B-Y34	5	W14630	10
1362x4	5	1369x8	5	33806B-Y38	5	W15310	5
1362x6	10	1380x6	5	6707	1	W76150	5
1362x8	5	1390x6	5	6708	1	W79850	3
1362x10	5	1391x6	5	6709	1	W79851	3



AB-28 • AIR BRAKE FITTINGS ASSORTMENT

The 1/4", 3/8", 1/2" brass air brake fittings for use with copper tubing provide excellent coverage for fleets, independent repair shops and farm implement dealers doing service work.

With the AB-28 assortment you also receive a cabinet with clear plastic drawers plus illustrated, color-coded labels that assure fast, positive identification and selection of replacement fittings.

AB-28 Contents

Catalog Number	Quantity	Catalog Number	Quantity	Catalog Number	Quantity	Catalog Number	Quantity
1360x4	20	1361x10	5	1368x8	5	33806B-Y28	5
1360x6	20	1361x12	5	1369x4	5	33806B-Y34	5
1360x8	20	1362x6	5	1369x6	10	33806B-Y38	5
1360x10	10	1362x8	5	145	10	CL-16-2	1
1360x12	10	1362x10	5	33806-A	20	FC-16X	1
1361x4	5	1368x4	5	33806B-Y06	2	W14630	10
1361x6	20	1368x6	10	33806B-Y24	5	W15310	5
1361x8	5	1368x6x6	5				