

Truck, Bus Valves



32-200



32-204



32-205



32-600

Camel No. Schrader No. TR No. Effective Length Hex Nut

Straight Clamp-in Valve

For use in one piece drop center rims with 5/8" diameter side mount valve holes.


| | | | | | |
|------------|----------|--|-----|--------|-------|
| 32-200-2* | | | 500 | 2" | 595-4 |
| 32-200-10 | 595-10 | | 500 | 2" | 595-4 |
| 32-200-100 | 595-100 | | 500 | 2" | 595-4 |
| 32-200-250 | | | 500 | 2" | 595-4 |
| 32-201-10 | 570-10 | | 570 | 3-1/8" | 595-4 |
| 32-201-100 | 570-100 | | 570 | 3-1/8" | 595-4 |
| 32-201-250 | | | 570 | 3-1/8" | 595-4 |
| 32-202-2* | | | 571 | 3-3/8" | 595-4 |
| 32-202-10 | 571-10 | | 571 | 3-3/8" | 595-4 |
| 32-202-100 | 571-100 | | 571 | 3-3/8" | 595-4 |
| 32-202-250 | | | 571 | 3-3/8" | 595-4 |
| 32-203-10 | 572-10 | | 572 | 3-3/4" | 595-4 |
| 32-203-100 | 572-100 | | 572 | 3-3/4" | 595-4 |
| 32-203-250 | | | 572 | 3-3/4" | 595-4 |
| 32-204-2* | | | 573 | 4-3/8" | 595-4 |
| 32-204-10 | 573-10 | | 573 | 4-3/8" | 595-4 |
| 32-204-100 | 573-100 | | 573 | 4-3/8" | 595-4 |
| 32-204-250 | | | 573 | 4-3/8" | 595-4 |
| 32-205-10 | 501-10 | | 501 | 1-1/2" | 595-4 |
| 32-205-100 | 501-100 | | 501 | 1-1/2" | 595-4 |
| 32-205-250 | | | 501 | 1-1/2" | 595-4 |
| 32-207-10 | 5538-10 | | 575 | 1-1/8" | 595-4 |
| 32-207-100 | 5538-100 | | 575 | 1-1/8" | 595-4 |
| 32-207-250 | | | 575 | 1-1/8" | 595-4 |
| 32-208-50 | 574-10 | | 574 | 5" | 595-4 |
| 32-208-100 | 574-100 | | 574 | 5" | 595-4 |
| 32-208-250 | | | 574 | 5" | 595-4 |

These valves may be bent to the desired configuration in accordance with tubeless valve dimension chart in section eight (8) of Tire and Rim Book, made to order.

*Display pack

Import Truck Tubeless Valves (ETRO)

Used on Volvo, Mack and Iveco imported trucks. Fits .382 dia. (9.7mm) rim hole. Includes O ring, nut, core and cap. 10 pack. (See chart on right.)



| Camel No. | Michelin No. | Schrader No. | Etro No. | DIN NO. | A* | B* | C* | D |
|-----------|--------------|--------------|----------|---------|--------|---------|---------|-----|
| -- | -- | 1080 | -- | 65MS9.7 | .98/25 | .98/25 | | 27° |
| 32-600-10 | 964 | 1083 | V3-20-1 | 41MS9.7 | .98/25 | | 1.42/36 | 0° |
| 32-604-10 | 1500 | 1129 | V3-20-7 | 65MS9.7 | .98/25 | 1.97/50 | | 27° |
| 32-608-10 | 1485 | 1130 | V3-20-4 | 87MS9.7 | .98/25 | 2.36/60 | | 27° |
| -- | -- | 1131 | -- | 95MS9.7 | .98/25 | 2.76/70 | | 27° |
| 32-612-10 | 1437 | 1132 | V3-20-6 | | .98/25 | 3.35/85 | | 27° |

* Inches and Millimeters



Schrader No. Effective Length Packaging

Chrome Truck Valves

Chrome Plated Clamp-In Type Truck and Bus Tubeless Tire Valves. For .625" side hole valve mountings.

| | | |
|------------------|--------|-------------|
| 501CR-100 | 1-1/2" | 100 per box |
| 572CR-100 | 3-3/4" | 100 per box |
| 573CR-100 | 4-3/8" | 100 per box |

Camel No. TR No. Length

Tube/Screw on Valves

33-150-5 TR 150 Hand Bendable Valve. Used in light truck tubes. May be applied with vulcanizer or cement. Effective length 3-1/2" shank diameter .615". Available in packs of 5 and 100.

Standard Tube Convertible Valves. Valves can be bent as needed. May be applied with heat vulcanization or Universal Cement.

| | | |
|-------------------|------|----------|
| 33-304-5 | 77A | 4-29/32" |
| 33-306-5 | 78A | 5-25/32" |
| 33-306-10 | 78A | 5-25/32" |
| 33-310-5 | 175A | 5-9/32" |
| 33-310-100 | 175A | 5-9/32" |
| 33-314-5 | 179A | 6-11/32" |

Replacement Hex Nut. For use with standard convertible valves for truck tires.

33-075 (25 pk.) Schrader No. **595-4** (1000 pk.)

Screw-On Repair Valves. Convertible from single bend to double bend. Includes bridge washer. These repair valves permit replacing damaged cured-in or cured-on valves without cutting out old valve base. Schrader 7799 VALVE HOLDING TOOL is recommended for gauging cut-off length of damaged valve to proper length for attaching these valves. Dimensions are the same as original valves. Repair valves are supplied in single-bend form with bridge washers.

| | | |
|------------------|-------|---------|
| 33-000-10 | 1075A | 3" |
| 33-004-10 | 1077A | 4-1/8" |
| 33-006-10 | 1078A | 5" |
| 33-006-50 | 1078A | 5" |
| 33-010-2 | 1175A | 4-1/2" |
| 33-010-10 | 1175A | 4-1/2" |
| 33-012-10 | 1177A | 3-3/4" |
| 33-014-5 | 1179A | 5-9/16" |

Camel No. Michelin No. Bend Length

Michelin Type Truck Tube Repair Valves

Includes standard valve core which fits housings manufactured to I.S.O. specifications.

33-118-5 751 Single 5-1/4"

33-399 Special flat washers must be used with repair valves. (above). 5 pack.

Camel No. Schrader No.

Specialty Truck Valves

Oval Slot Valve. Designed for Firestone 16 x 6 KS and 16 x 6-1/2 LS wheels. Completely assembled with grommets, washers, hex nut, valve core and valve cap. 10 pack. (See caution below)

32-400-10 1161

CAUTION: Due to production techniques, the rim valve hole should be checked for burrs and cleaned if necessary.

