

Camel No.	Amflo No.	Schrader No.	Operating Pressure Range (PSI)	Operating Temp. Range (°F)	Opening Pressure (PSIG)	Sealing Material Plug / Plunger	Pack Size
-----------	-----------	--------------	--------------------------------	----------------------------	-------------------------	---------------------------------	-----------

Standard Valve Cores

These valve cores all have .206"-36 threads and are compatible with existing USA, ETRTO and ISO standards.

Recommended for all truck, bus and commercial applications. Meets specification ZZ-V-25 and TR C-1.

		5405V	0-200 psia peaks of 300	-65 to +300 peaks of +400	90	Red Teflon	White Silicone	100
--	--	--------------	----------------------------	------------------------------	----	---------------	-------------------	-----

General purpose valve use. Meets specifications ZZ-V-25 and TR-C-1.

38-790-4	945D**		0-200 psia peaks of 300	-40 to +225	60	Green Teflon	Black Nitrile	4*
-----------------	---------------	--	----------------------------	-------------	----	-----------------	------------------	----

38-790-100	945-100	8500TV	0-200 psia peaks of 300	-40 to +225	60	Green Teflon	Black Nitrile	100
-------------------	----------------	---------------	----------------------------	-------------	----	-----------------	------------------	-----



5405

Special Valve Cores

Aircraft shock strut and hydraulic accumulator use. Meets specifications AN-809-1 and MIL-C-5499.

		2300TV	0-2000 psig (oiled) 70-2000 psig (dry)	0 to +165	100+	Molded Nitrile	Black Nitrile	100
--	--	---------------	---	-----------	------	-------------------	------------------	-----

Hydraulic accumulator use.

		9914A	0-2000 psig (oiled) 70-2000 psig (dry)	0 to +165	70	Natural Teflon	Black Nitrile	100
--	--	--------------	---	-----------	----	-------------------	------------------	-----



38-790/8500

Airplane

General purpose high-pressure, heat-resisting applications. Meets specification MIL-V-27317 and TRC-4.

		6035	0-400 psig peaks of 500	-65 to +350 peaks of +500	70	Natural Teflon	White Silicone	100
--	--	-------------	----------------------------	------------------------------	----	-------------------	-------------------	-----

Large Bore Core

This valve core has .305"-32 threads and is compatible with existing USA standards for large bore valve housings.

General purpose. Meets specification TR-C-2.

37-828-10		6231	0-200 psia	-65 to +300	55	Natural Teflon	White Silicone	100
------------------	--	-------------	------------	-------------	----	-------------------	-------------------	-----

* 5 pack.

** Display pack.

CAUTION: These products should not be used in applications which do not fully comply with recommended operating specifications. For use other than specified, or with media other than air or inert gases when not specified, consult for manufacturer approval.



9914A



← Plunger Pin

← Plug Gasket

← Spring Inside

← Plunger Seat Washer



6035

Valve Caps



7572



2316C

Camel No.	Amflo No.	Schrader No.	TR Number	Sealing Washer Material	Operating Pressure Range (PSIA)	Operating Temperature Range (°F)	Pack Size	Description	Finish
-----------	-----------	--------------	-----------	-------------------------	---------------------------------	----------------------------------	-----------	-------------	--------

Standard Valve Caps

Fit .305"-32 Threads on Standard Type Valves

38-772-4*			VC3	Nitrile	0-200	-40 to +165	4*	Same as No. 7572V	N/P
38-772-100	941-100	7572V	VC3	Nitrile	0-200	-40 to +165	100	Dome-shaped top and guide on skirt for easy application to valve threads.	N/P
		7572B	VC3	Nitrile	0-200	-40 to +165	100	Same as No. 7572V	Black
		7572S		Nitrile	0-200	-40 to +165	100	Same as No. 7572V, but has shorter skirt.	N/P
38-600-4*			VC2	Nitrile	0-200	-40 to +165	4*	Same as No. 2316C	N/P
38-600-100	940-100		VC2	Nitrile	0-200	-40 to +165	100	All purpose cap with screw-driver top for removing and inserting valve cores. Has guide on skirt for easy application to valve threads.	N/P
		2316C	VC2	Nitrile	0-200	-40 to +165	100		Black

Heavy Duty and Heat Resisting Caps

		440V		Nitrile	0-250	-40 to +200	100	Heavy-duty cap with special heat resistant rubber washer. Has guide on skirt for easy application to valve threads.	N/P
		2525	VC 5	Neoprene	0-5000	-65 to +160	100	Made from hexagon rod for wrench application. Maximum torque 10 inch-pounds. Has special sealing washer for high pressure use. Conforms to Military Spec. MIL-C-5000 and MS-20813.	Yellow
38-712-4*				Nitrile	0-250	-40 to +200	4*	Same as No. 5998	Chrome
38-712-100	949-100	5998		Nitrile	0-250	-40 to +200	100	For use on chrome sleeve and high performance valves.	Chrome

Plastic Caps

38-505*	943D**		VC 8		0-100	0 to +100	4*	Same as No. 660V	Black
38-505-100	943-100	660V	VC 8		0-100	0 to +100	100	Black flexible plastic cap has no sealing unit.	Black
		1155			0-200	-40 to 165	100 ¹		Black
38-505-500			VC 8		0-100	0 to +100	500	Same as No. 660V	Black

* Display pack. **5 pack. ¹Has sealing unit. For use on cars, trucks and commercial applications.

CAUTION: These products should not be used in applications which do not fully comply with recommended operating specifications. For use other than specified, or with media other than air or inert gases when not specified, consult for manufacturer approval.



38-712



1155



7572S



38-505



2525