

Inflator Gauges, Hoses & Pressure Equalizer

Camel No. Amflo No.

Master Air & Replacement Hose

| | | |
|-------------------------------|--------------|---|
| Standard Bore Inflating Gauge | 3910S | Inflates and checks pressure of passenger cars, motorcycles and trucks. Has a five foot hose length. Dual calibrated 10 to 170 PSI and .7 to 12 bar. Calibrated in two pound increments. 1 per box. |
| Replacement Hose | 3911 | |

110

1120

3910S

Replacement Hose Assemblies for Air Line Inflators Gauges. Hose assemblies on this page have standard 3/8" - 24 UNF male threads and will fit inflator gauges in addition to many other products. Hose is flexible, oil and ozone resistant rubber. 1 pack.

| | | |
|---------------|--------------|--|
| 40-701 | 110 | 12" whipend no chuck 1/4" NPT swivel end. |
| 40-704 | 1120D | 12" hose with straight chuck. Display package. |
| 40-706 | | 72" hose with lock-on chuck and bleed valve. |
| 40-762 | | 12" hose with lock-on chuck. |
| 40-763 | 161 | 36" hose with ball foot lock-on chuck and bleed valve. |
| | | 72" hose with ball foot lock-on chuck and bleed valve. |
| 40-765 | 116 | 36" hose with bleed valve and lock-on chuck. |
| | 113 | 12" hose with dual foot chuck. |
| | 153 | Replacement indicator bar for (150 series) inflator gauge. 1 pack. |
| | 159 | Replacement valve unit for (150 series) inflator gauge. 1 pack. |

161

116

Visualizer II® Pressure Equalizer

Visualizer II, - Dual Tire Pressure Equalizer - Extend Tread Life up to 30%

Visualizer II, state-of-the-art tire pressure equalizer allows air to flow freely between dual tires to maintain equal inflation. Visualizer II connects tire valves to an equalization module that equalizes pressure between inside and outside tires. Unit allows vehicle operator to visually check for correct tire pressure.

- Chrome plated housing
- Heavy-duty construction
- Factory preset tire inflation levels
- Provides accurate callibration
- Easy installation
- Single valve inflation
- Automatic safety cut-off
- Color-coded pressure indicators
- Stainless steel braided hose with nickel-plated fittings

Eliminate costly maintenance and wear problems. Install Visualizer II dual tire equalizer on tractors, trailers and medium-duty trucks, even ones with chrome hub caps. Visualize the benefits of proper and balanced dual tire inflation on your fleet.

- Increases fuel mileage
- Reduces blowout risk
- Decreases tire maintenance
- No valve core removal required
- Extends tread life
- Improves traction
- System removal not required for tire service

Unit is color-coded to provide proper inflation information. RED under inflation, GREEN indicates proper inflation and YELLOW over inflation.













Without Visualizer II
As tires heat up, tire pressures increase unequally



With Visualizer II
Equal tire pressures maintained for optimal performance



Visualizer II offers specialized kits to meet the requirements of most vehicles.

| Kit No. | Description | |
|-------------|--|---|
| 1125 Kit 3 | Stainless steel replacement hose kit. |  |
| 1125 Kit 5 | Center axle mount for Fruehauf Pro Par trailer axles. |  |
| 1125 Kit 6 | Strap bracket for Mack, International tractors and others with 3/4" axle bolts. |  |
| 1125 Kit 10 | Tractor and trailer axles with hubodometer. |  |
| 1125 Kit 11 | General-purpose trailer bracket for axles with 5/16" axle hub bolt holes. |  |
| 1125 Kit 12 | 5/8" universal application strap bracket |  |
| 1125 Kit 13 | Center hub mount for tractor and truck axles with 1/2" bolt holes. | |
| 1125 Kit 14 | Center hub mount for tractor and truck axles with 9/16" bolt holes. | |
| 1125 Kit 15 | Center hub mount for most tractor and trailer axles with 5/8" hub bolt holes including Kenworth, Peterbilt, Navistar and others. |  |
| 1125 Kit 16 | Center hub mount for tractor and truck axles with 3/4" bolt holes including Mack, International, GMC and others. |  |
| 1125 Kit 18 | Wheel mount for all wheels with hub-piloted wheel bolts and chrome hub caps or hubodometer with 7/8" bolt holes. | |
| 1125 Kit 19 | Wheel mount for all wheels with stud piloted wheel bolts and chrome hub caps or hubodometer with 1 1/8" bolt holes. |  |
| 1125 Kit 21 | For truck and trailer axles with oil seals. |  |

How to Order Visualizer II®

Visualizer II is available in 5 pound increments – from 60 psi to 120 psi.

- Specify the psi setting required: 1125-60, 1125-65, 1125-70, 1125-75, 1125-80, 1125-85, 1125-90, 1125-95, 1125-100, 1125-105, 1125-110, 1125-115 or 1125-120.
- Includes two hoses to connect both tires to Visualizer II.
- For more Visualizer II information, contact Schrader-Bridgeport customer service.

LIMITED WARRANTY: Schrader-Bridgeport warrants its products to be free from defects in material and workmanship for a period of 30 days from the date of purchase. This warranty shall be null and void if product is improperly installed or altered.