

Gauges Sold Separately



Compact
Ports 1/4"-3/8"
Flow SCFM 20



Standard
Ports 3/8"-1/2"
Flow SCFM 75 150



Drip-Legs
Ports 1/2"

Coalescing Filters

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4017	4016
1/4"	3/8"	4019	4018

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	1/4"	4012A-99	
3/8"	3/8"	4022A-99	
1/2"	3/8"	4038/56-204	4023
1/2"	1/2"	4033/56-208	4037

Port Size	Poly Bowl	Metal Bowl
1/2"	4034	4035

Parts & Accessories

Body Size	.01 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Semi Auto Drain
1/4"	4089	4056	4057	4760	4086

Parts & Accessories

Body Size	.01µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Rplc. Sight Glass	Bowl O-Ring
1/2"	4097	4095	4094	4772	4278	4783

Parts & Accessories

Port Size	Poly Bowl	Metal Bowl	Auto Drain
1/2"	4074A-99	4079A-99	4060

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure –
Transparent Bowl: 150 psig (10.3 bar)
Metal Bowl: 250 psig (17.2 bar)
Maximum Temperature –
Transparent Bowl: 125°F (52°C)
Metal Bowl: 150°F (66°C)

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure –
Transparent Bowl: 150 psig (10.3 bar)
Metal Bowl: 250 psig (17.2 bar)
Maximum Temperature –
Transparent Bowl: 125°F (52°C)
Metal Bowl: 150°F (66°C)

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure –
Transparent Bowl: 150 psig (10.3 bar)
Metal Bowl: 250 psig (17.2 bar)
Maximum Temperature –
Transparent Bowl: 125°F (52°C)
Metal Bowl: 150°F (66°C)



Miniature
Ports 1/4"
Flow SCFM 20



Compact
Ports 1/4"-3/8"
Flow SCFM 50



Standard
Ports 1/4"-3/8"-1/2"-3/4"-1"
SCFM 70 -150 -425

Regulators

Body Size	Port Size	Without Gauge	With Gauge
Mini	1/4"	4100/4102*	4100D/56-110

Body Size	Port Size	Without Gauge
1/4"	1/4"	4119
1/4"	3/8"	4118

Body Size	Port Size	Without Gauge
3/8"	1/4"	4115A-99/56-341-99 4116-99 w/ panel nut
3/8"	3/8"	4125A-99/56-355 4126-99 w/ panel nut
1/2"	1/2"	4135/56-344
1/2"	3/4"	4145
1"	3/4"	4141
1"	1"	4155/56-346

Parts & Accessories

Body Size	Mounting Bracket	Panel Nut	Reg. Repair Kit	Rplc. Knob
Mini	4160	4161	4166	4790

Parts & Accessories

Body Size	Mounting Bracket w/ Panel	Panel Nut	Reg. Repair Kit	Rplc. Knob
1/4"	4760	4763	4757	4791

Parts & Accessories

Body Size	Mounting Bracket w/Panel	Panel Nut	Reg. Repair Kit	Rplc. Knob
3/8"	4162A-99	4778	4167A	4792
1/2"	4772	4773	4776	4793
1"	4165		4169	Non-Rplc

* Non-Repairable Regulator

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure: 300 psig
Temperature Range –
Mini: 0° to 150°F
All Others: 0° to 175°F
Gauge Port: 2-1/8" NPT (full flow)
Outlet Range: 5 - 125 psi

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure: 300 psig
Temperature Range: 0° to 150° F
Gauge Port: 2-1/8" NPT (full flow)
Outlet Range: 5 - 125 psi

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure: 300 psig
Temperature Range: 0° to 175° F
Gauge Port: 2-1/4" NPT (full flow)
Outlet Range: 5 - 125 psi

Gauges Sold Separately.



Compact

Ports1/4"
SCFM 50



Standard

Ports1/4"-3/8"-1/2"-3/4"
SCFM..... 75 -150

Combination Units Filter - Regulator

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4512	4513

Parts & Accessories

Body Size	40 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Reg. Repair Kit	Rplc. Knob
1/4"	4087	4056	4057	4759	4757	4791

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure – Transparent Bowl: 150 psig
Metal Bowl: 250 psig
Maximum Temperature – Transparent Bowl: 125°F
Metal Bowl: 175°F
Gauge Port: 2-1/8" NPT (full flow)
Outlet Range: 5 - 125 psi

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	1/4"	4510A-99	
3/8"	3/8"	4520A-99	
1/2"	1/2"	4530	4531
1/2"	3/4"	4540	4541

Parts & Accessories

Body Size	40 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Reg. Repair Kit	Bowl O-Ring	Rplc. Knob
3/8"	4060A	4074A-99	4079A-99	4071A-99	4167A	4782	4792
1/2"	4093	4095	4094	4770	4776	4783	4793

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure – Transparent Bowl: 150 psig
Metal Bowl: 250 psig
Maximum Temperature – Transparent Bowl: 125°F
Metal Bowl: 175°F
Gauge Port: 2-1/4" NPT (full flow)
Outlet Range: 5 - 125 psi



Compact

Ports1/4"
SCFM 50



Standard

Ports3/8"-1/2"-3/4"
SCFM..... 75 -150

Combination Regulator - Lubricator

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4609	4612

Parts & Accessories

Body Size	40 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Reg. Repair Kit	Rplc. Knob	Fill Plug
1/4"	4087	4056	4057	4759	4757	4791	4798

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure – Transparent Bowl: 150 psig
Metal Bowl: 250 psig
Maximum Temperature – Transparent Bowl: 125°F
Metal Bowl: 175°F
Gauge Port: 2-1/8" NPT (full flow)
Outlet Range: 5 - 125 psi

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	3/8"	4620A-99	4621A-99
1/2"	1/2"	4630	
1/2"	3/4"	4640	4641

Parts & Accessories

Body Size	40 µm Element	Poly Bowl	Metal Bowl	Mounting Bracket	Reg. Repair Kit	Body Size	Rplc. Knob	Bowl O-Ring	
3/8"	4066A-99	4265A-99	4269	4162A	4167A	3/8"	4792	4795	4782
1/2"	4093	4285	4286	4770	4776	1/2"	4793	4796	4783

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure – Transparent Bowl: 150 psig
Metal Bowl: 250 psig
Maximum Temperature – Transparent Bowl: 125°F
Metal Bowl: 175°F
Gauge Port: 2-1/4" NPT (full flow)
Outlet Range: 5 - 125 psi

Filters, Regulators, Lubricators

Gauges Sold Separately.



Compact

Ports1/4"-3/8"
SCFM50



Standard

Ports1/4"-3/8"-1/2"-3/4"
SCFM 75 -150

Regulator/Filter - Lubricator

Body Size	Port Size	Poly Bowl	Metal Bowl
1/4"	1/4"	4709	4712

Body Size	Port Size	Poly Bowl	Metal Bowl
3/8"	1/4"	4710A-99	4711A-99
3/8"	3/8"	4720A-99	4721A-99
1/2"	1/2"	4730	4731
1/2"	3/4"	4740	4741

Parts & Accessories

Body Size	40 µm Element	Mounting Bracket	Reg. Repair Kit	Rplc. Knob	Fill Plug
1/4"	4087	4760	4757	4791	4798

Body Size	FILTER		LUBRICATOR	
	Poly Bowl	Metal Bowl	Poly Bowl	Metal Bowl
1/4"	4056	4057	4058	4059

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure –
Transparent Bowl: 150 psig
Metal Bowl: 250 psig
Maximum Temperature –
Transparent Bowl: 125°F
Metal Bowl: 175°F
Gauge Port: 2-1/8" NPT (full flow)
Outlet Range: 5 - 125 psi

Parts & Accessories

Port Size	40 µm Element	Mounting Bracket	Reg. Repair Kit	Rplc. Knob	Bowl O-Ring	Fill Plug
3/8"	4066A-99	4162A-99	4167A	4792	4782	4795
1/2"	4093	4770	4776	4793	4783	4796

Port Size	FILTER		LUBRICATOR	
	Poly Bowl	Metal Bowl	Poly Bowl	Metal Bowl
3/8"	4074A-99	4079A-99	4265A-99	4269
1/2"	4095	4094	4285	4286

Specifications

Fluid: Compressed Air
Maximum Inlet Pressure –
Transparent Bowl: 150 psig
Metal Bowl: 250 psig
Maximum Temperature –
Transparent Bowl: 125°F
Metal Bowl: 175°F
Gauge Port: 2-1/8" NPT (full flow)
Outlet Range: 5 - 125 psi