

Camel No. Description

Nonflammable Boot Cement

- 12-070 **Liquid Buffer/Universal Cement.** 2 fl. oz. tubes.
 12-075 **Boot Cement.** 1/2 pint can. For use on boots and tire patches used with inner tubes.
 12-077 **Universal Cement.** 2 fl. oz. tube.
 12-082 **Universal Cement.** 1 gallon can. For shops that use refillable cement cans.
 12-085 **Universal Cement.** 1/4 pint (4 fl. oz.) can.
 12-086 **Universal Cement.** 1/2 pint (8 fl. oz.) can.
 12-089 **Universal Cement.** 1 quart. Can fits 14-149 dealer cabinet.

Cam-Cure® Heavy-Duty Nonflammable Cement. For use on heavy-duty applications. Must be Cam-Cure® Repair Units to insure a permanent bond.

- 12-087 **1/2 Pint.**
 12-088 **1 Quart Can.** Convenient size for busy tire shops.
 12-100 **Cement Dispenser.** All aluminum construction with twist-on cap and large cement brush.

Cam-Cure® Black Nonflammable Vulcanizing Cement. Black cement is the preferred cement for use in build-ups and installation of repair units when heat is used.

- 12-101 1 Quart black brush type cement.

Cam-Cure® Flammable Cement. For professional use.

- 12-287 1/2 Pint chemical Vulcanizing, flammable.
 12-288 1 Quart Chemical Vulcanizing, flammable.

Cam-Cure® Flammable Black Cement. Recommended for professional use only. Used to reduce drying time of cement. For use with all Cam-Cure repair units and build-up materials. Use with heat vulcanization.

- 12-290 1 Quart black, brush type flammable.



12-100

12-088

12-088

12-070

12-075

12-082

12-086

12-087

CAUTION: Use in well ventilated area. Avoid prolonged breathing or inhalation of vapors. Chlorinated solvent is an eye and skin irritant. If splashed in eyes, flush with water for 15 minutes. If ingested, do not induce vomiting. Call physician or Poison Control Center immediately.



12-090



12-092



12-093



12-095




12-097



17-250



12-074



12-072



12-078



12-079



12-094

Camel No. Description

Chemicals

12-090 Bead Sealer. Quart can with brush in cap. Prevents bead leaks and eases tire installation.

12-092 Nonflammable Liquid Buffer/Cleaner. Quart can with "squirt top." Used to clean rubber so patches will adhere properly. Use prior to all power buffing.

12-093 Nonflammable Spray Liquid Buffer. 16 oz. aerosol can.

12-095 "Stuf" Concentrated Tire Mounting Lubricant with Rust Inhibitor. Eight lb. pail makes five gallons when mixed with warm water. Stops rubber squeaks, easy to use and safe.

12-096 Rubber Lubricant and Preservative. Large 40 pound pail. Same product as 12-095.

12-097 Rubber Lubricant. Cleans and preserves tires, rubber parts, floor mats and vinyl tops. One gallon bottle.

17-250 Tire Talc. One pound shaker can. Prevents tube from sticking to tire during installation.

17-252 Tire Talc. Five pound bag for large tire shops.

Sealants

Camel Seal Tire Sealant: The solution to bead leaks, small tire punctures and slow leaks. Will not dry out, separate, damage the wheel, or freeze to -32°F. Seal small leaks up to 1/8" in diameter. Great for farm and industrial tractors, construction equipment and off-road tires.

12-072 Tire Sealant. One gallon bottle with pump.

12-074 Precision Metering Hand Pump. Pump exactly the amount needed. Plastic see-through column is graduated. Pump is used with Camel 12-081 five gallon pail.

12-078 Tire Sealant. Convenient 8 fl. oz. squeeze bottle. Perfect size for small trailers, wheelbarrows and other small tire vehicles.

12-079 Tire Sealant. The 16 fl. oz. squeeze bottle is just the right amount for lawn tractors, golf carts, trailers and ATVs.

12-081 Tire Sealant. Five gallon pail. Use with 12-074 hand pump for tractor and other large tires.

12-094 Camel Jack Inflator & Sealer. "The spare tire in a can!" The most advanced emergency tire repair system available today. Seals and inflates tire with up to 16" rims quickly and safely. No jacks or tools required - vulcanizes on contact to provide durable seal. Use on passenger cars, vans, light trucks, trailers, lawn tractors and ATVs. *Do not use in high performance, "Z-rated" or motorcycle tires.*

CAUTION: Use in well ventilated area. Avoid prolonged breathing or inhalation of vapors. Chlorinated solvent is an eye and skin irritant. If splashed in eyes, flush with water for 15 minutes. If ingested, do not induce vomiting. Call physician or Poison Control Center immediately.