

Hose ID	NPT	Camel No.	Amflo No.	Schrader No.
---------	-----	-----------	-----------	--------------

### Solid Brass Male Hose Barb Fittings

Select fitting to match hose inside diameter.  
**\*All packages contain 10 fittings.** Amflo part numbers with D suffix indicate display packs.

1/8"	1/8"		399	
3/16"	1/8"		400	
1/4"	1/8"	52-493	404	
1/4"	1/4"		401	6363
1/4"	1/4"	52-039	401D	
5/16"	1/4"	52-038	405D	6362
3/8"	1/4"	52-037	406	6361
1/2"	1/4"	52-036	408	
1/4"	3/8"		604	
3/8"	3/8"	52-492	606	
1/4"	3/8"-24		398	
1/2"	3/8"		608	
3/8"	1/2"		806	
1/2"	1/2"	52-491	808	
1/2"	3/4"		813	
3/4"	3/4"		814	
1"	3/4"		816	
1"	1"		818	

### Male Ball Swivels

Fitting may swivel and rotate without kinking or twisting of hose.

1/4"	1/4"	444S
3/8"	1/4"	446S

### Male Swivel Fittings

Permits rotation of fitting without kinking or twisting of hose.

1/4"	1/4"	401S
3/8"	3/8"	606S
1/2"	1/2"	808S

### Hi-Volume Male Swivel Fittings

5/16"	1/4"	405S
3/8"	1/4"	406S

Hose ID	NPT	Camel No.	Amflo No.
---------	-----	-----------	-----------

### Solid Brass Female Fittings

1/4"	1/4"	52-042	441
5/16"	1/4"		451
3/8"	1/4"		461
3/8"	3/8"		661
1/2"	3/8"		681

### Two Piece Swivel Female Fittings

1/4"	1/4"	442
5/16"	1/4"	452
3/8"	1/4"	462D
3/8"	3/8"	662L

Hose O.D. Range	Clamp Width	Camel No.	Amflo No.
-----------------	-------------	-----------	-----------

### Hose Clamps

Gear type clamps permit quick hose repair with simple tools. Stainless band, plated steel screw. 10 pack.

1/4" to 5/8"	5/16"	580
3/8" to 7/8"	5/16"	581
1/2" to 1-1/4"	5/16"	582
3/4" to 1-3/4"	9/16"	583

### Hose Size

Camel No.	Amflo No.
-----------	-----------

### Hose Splicer and Clamps Kits

Use to repair hose in-line repairs or install new hose end fittings.

1/4" Large Kit	410D
1/4" D-I-Y Kit	52-464 417D
3/8" Barb w/ clamp	411D
3/8" Hose Repair Kit	412D



401



580



608



444S



681



463



442



502

Hose ID	NPT	Camel No.	Amflo No.	Schrader No.
---------	-----	-----------	-----------	--------------

### One Piece Female Swivel Fittings

Permits rotation of fitting without kinking or twisting of hose.

1/4"	1/4"	443
3/8"	1/4"	463

### Solid Brass Hose Splicers

1/4"	52-046	402	7676
5/16"	52-045	502	
3/8"	52-044	602	7674
1/2"	52-047	802	

**CAUTION:** Fittings must be secured to hose with either hose clamps or crimped-on ferrules with a hose crimper.

Hose barbs are intended for use on compressed air only with a maximum working pressure of 300 PSI.

Hose O.D.	Hose I.D.	NPT	Camel No.	Amflo No.
<b>Male Pipe Thread</b>				
1/2"	1/4"	1/4"		418
9/16"	1/4"	1/4"		439
19/32"	1/4"	1/4"	52-439	419
5/8"	1/4"	1/4"	52-438	420
5/8"	5/16"	1/4"		520
5/8"	3/8"	1/4"		620
21/32"	3/8"	1/4"		621
23/32"	3/8"	1/4"	52-435	623
21/32"	3/8"	3/8"		624
23/32"	3/8"	3/8"		625
7/8"	1/2"	1/2"		828

<b>Female Pipe Thread</b>				
1/2"	1/4"	1/4"		418F
9/16"	1/4"	1/4"		439F
5/8"	5/16"	1/4"		520F
21/32"	3/8"	1/4"		621F
23/32"	3/8"	1/4"		623F
21/32"	3/8"	3/8"		624F

<b>Hose Splicers</b>				
21/32"	3/8"			621S
23/32"	3/8"	52-434		623S

Male NPT	Male NPT	Camel No.	Amflo No.
----------	----------	-----------	-----------

<b>Male Pipe Couplings</b>			
Solid brass NPT.			
1/8"	1/4"		324
1/4"	1/4"	52-495	344
3/8"	1/4"		346
3/8"	3/8"		366
1/2"	1/2"		388
3/4"	3/4"		389

Male NPT	Female NPT	Amflo No.
----------	------------	-----------

<b>Bushings and Adaptors</b>		
Solid brass.		
1/4"	1/8"	324F
1/8"	1/4"	342F
3/8"	1/4"	346F
1/2"	1/4"	348F
1/4"	3/8"	364F
1/2"	3/8"	368F
3/4"	1/2"	389F

<b>Pipe Coupling Female NPT</b>	
---------------------------------	--

Solid brass.	
1/4" x 1/4"	344F

**CAUTION:** Check hose O.D. and I.D. accurately before ordering. All packages contain 10 fittings.



439



621F



621S



344



346F



344F