

Hose ID	NPT	Camel No.	Amflo No.	Schrader No.
---------	-----	-----------	-----------	--------------

Hose O.D. Range	Clamp Width	Camel No.	Amflo No.
-----------------	-------------	-----------	-----------

Solid Brass Male Hose Barb Fittings

Select fitting to match hose inside diameter.
***All packages contain 10 fittings.** Amflo part numbers with D suffix indicate display packs.

1/8"	1/8"		399	
3/16"	1/8"		400	
1/4"	1/8"	52-493	404	
1/4"	1/4"		401	6363
1/4"	1/4"	52-039	401D	
5/16"	1/4"	52-038	405D	6362
3/8"	1/4"	52-037	406	6361
1/2"	1/4"	52-036	408	
1/4"	3/8"		604	
3/8"	3/8"	52-492	606	
1/4"	3/8"-24		398	
1/2"	3/8"		608	
3/8"	1/2"		806	
1/2"	1/2"	52-491	808	
1/2"	3/4"		813	
3/4"	3/4"		814	
1"	3/4"		816	
1"	1"		818	

Hose Clamps

Gear type clamps permit quick hose repair with simple tools. Stainless band, plated steel screw. 10 pack.

1/4" to 5/8"	5/16"	580
3/8" to 7/8"	5/16"	581
1/2" to 1-1/4"	5/16"	582
3/4" to 1-3/4"	9/16"	583

Hose Size

Hose Splicer and Clamps Kits

Use to repair hose in-line repairs or install new hose end fittings.

Hose Size	Camel No.	Amflo No.
1/4" Large Kit		410D
1/4" D-I-Y Kit	52-464	417D
3/8" Barb w/ clamp		411D
3/8" Hose Repair Kit		412D

Male Ball Swivels

Fitting may swivel and rotate without kinking or twisting of hose.

1/4"	1/4"	444S
3/8"	1/4"	446S

Male Swivel Fittings

Permits rotation of fitting without kinking or twisting of hose.

1/4"	1/4"	401S
3/8"	3/8"	606S
1/2"	1/2"	808S

Hi-Volume Male Swivel Fittings

5/16"	1/4"	405S
3/8"	1/4"	406S

Hose ID	NPT	Camel No.	Amflo No.	Schrader No.
---------	-----	-----------	-----------	--------------

Hose ID	NPT	Camel No.	Amflo No.	Schrader No.
---------	-----	-----------	-----------	--------------

Solid Brass Female Fittings

1/4"	1/4"	52-042	441
5/16"	1/4"		451
3/8"	1/4"		461
3/8"	3/8"		661
1/2"	3/8"		681

One Piece Female Swivel Fittings

Permits rotation of fitting without kinking or twisting of hose.

1/4"	1/4"	443
3/8"	1/4"	463

Two Piece Swivel Female Fittings

1/4"	1/4"	442
5/16"	1/4"	452
3/8"	1/4"	462D
3/8"	3/8"	662L

Solid Brass Hose Splicers

1/4"	52-046	402	7676
5/16"	52-045	502	
3/8"	52-044	602	7674
1/2"	52-047	802	



401



580



608



444S



681



463



442



502

CAUTION: Fittings must be secured to hose with either hose clamps or crimped-on ferrules with a hose crimper.

Hose barbs are intended for use on compressed air only with a maximum working pressure of 300 PSI.

Brass Hose Fittings

Lock-On Hose Barbs. Designed to use with Amflo's special lock-on hose. No ferrules or hose clamps are required. Not to be used with conventional hose. All lock-on packages contain 10 fittings unless otherwise marked.



401L

442L

446SL



602L



846



344X



366T



3404



3403 RET



344R90



366R



344U



930



265

Flow Passage NPT Amflo No.

Tank Safety Valve

Safety valve is furnished with relief pressure preset.

1/4"	1/4" NPT (125 PSI)	265-RET
1/4"	1/4" NPT (165 PSI)	267-RET

Hose ID NPT Thread Amflo No.

Lock-On Hose Barb Male

1/4"	1/4"	401L
3/8"	1/4"	406L
3/8"	3/8"	606L
1/2"	1/2"	808L

Lock-On Hose Barb 2PC Female

1/4"	1/4"	442L
3/8"	3/8"	662L

Lock-On Hose Barb Male Ball Swivel

1/4"	1/4"	444SL
3/8"	1/4"	446SL

Lock-On Hose Barb Splicers

1/4"	402L
3/8"	602L

Lock-On Hose Barb Kit. 35 piece kit. Assortment.
1/4" & 3/8" 846

Female Crosses

Excellent for running several air lines from a common supply hose. Solid brass.

1/4" NPT	344X
3/8" NPT	366X

Female Tees

Run two lines from a common feed. Solid brass.

1/4" NPT	344T
3/8" NPT	366T

Three-Way Manifold

Strong machined aluminum construction. Each manifold accepts three outlet hoses or couplers. * 3404 and 3406 available in display packs.

1/4" NPTF	1/4" NPTF	3404*
3/8" NPTF	1/4" NPTF	3406*
1/2" NPTF	1/4" NPTF	3408

Flat Brass Construction.

3/8" NPTF	1/4" NPTF	3403RET
-----------	-----------	---------

Angle Swivels

Stop hoses from kinking or for use in pneumatic equipment applications. Brass.

1/4" male / female swivels	344R90
----------------------------	--------

Brass In-Line Swivels

1/4" male / female NPT	344R
3/8" male / female NPT	366R

Uniswivel

360° swivel action. 300 PSI.

1/4" NPTF x 1/4" NPTM	344U
	344U-1

Flow Passage NPT Amflo No.

Brass Drain Cocks

1/4"	1/4"	930
1/16"	1/8"	931

Hose O.D.	Hose I.D.	NPT	Camel No.	Amflo No.
Male Pipe Thread				
1/2"	1/4"	1/4"		418
9/16"	1/4"	1/4"		439
19/32"	1/4"	1/4"	52-439	419
5/8"	1/4"	1/4"	52-438	420
5/8"	5/16"	1/4"		520
5/8"	3/8"	1/4"		620
21/32"	3/8"	1/4"		621
23/32"	3/8"	1/4"	52-435	623
21/32"	3/8"	3/8"		624
23/32"	3/8"	3/8"		625
7/8"	1/2"	1/2"		828

Female Pipe Thread				
1/2"	1/4"	1/4"		418F
9/16"	1/4"	1/4"		439F
5/8"	5/16"	1/4"		520F
21/32"	3/8"	1/4"		621F
23/32"	3/8"	1/4"		623F
21/32"	3/8"	3/8"		624F

Hose Splicers				
21/32"	3/8"			621S
23/32"	3/8"	52-434		623S

Male NPT	Male NPT	Camel No.	Amflo No.
----------	----------	-----------	-----------

Male Pipe Couplings			
Solid brass NPT.			
1/8"	1/4"		324
1/4"	1/4"	52-495	344
3/8"	1/4"		346
3/8"	3/8"		366
1/2"	1/2"		388
3/4"	3/4"		389

Male NPT	Female NPT	Amflo No.
----------	------------	-----------

Bushings and Adaptors		
Solid brass.		
1/4"	1/8"	324F
1/8"	1/4"	342F
3/8"	1/4"	346F
1/2"	1/4"	348F
1/4"	3/8"	364F
1/2"	3/8"	368F
3/4"	1/2"	389F

Pipe Coupling Female NPT	
---------------------------------	--

Solid brass.	
1/4" x 1/4"	344F

CAUTION: Check hose O.D. and I.D. accurately before ordering. All packages contain 10 fittings.



439



621F



621S



344



346F



344F