

Camel No. Amflo No.

Vacuum Gauge

- 1024-30V** Gauge has 1/4" NPT lower connection. Dial is 2 1/2" in diameter.
Range is 0 to 30 Hg. (inches of mercury)



1027

In-Line Filter

- 1025** Large 2 square inch porous bronze element removes solids and moisture from compressed air lines. Button relief valve for draining trapped liquid from reservoir. 1/4" NPS swivel female outlet



1212

Disposable In-Line Filter

- 1027** Simple, one-piece aluminum housing with 40 micron porous bronze element. 1/4" NPTF inlet and 1/4" NPTM outlet.

In-Line Oiler

- 56-080 1212** Automatically lubricates air tools by feeding a measured amount of oil mist each time the tool is cycled. Maximum line pressure 175 PSI. 1/4" NPT.
- 1213** **In-Line Oiler.** Same as above except inlet, outlet threads are 3/8" NPT.



1220-1

Lubricants

- 1220-1** **Light Pneumatic Tool Oil.** 92 SUS at 75 F 1 pt.
1220-4 **Light Pneumatic Tool Oil.** 92 SUS at 75 F 4 oz.
1220-8 **Light Pneumatic Tool Oil.** 1 gallon U.S.
1220WW-1 **Air Tool Oil (Winter Weight)** 1 pint.
1420 **Compressor Oil** 1 quart



1420

Amflo No.

Amflo No.

Tamperproof In-Line Regulators

- Tamperproof Fixed Pressure Setting.** Preset at the factory. Can be installed with safety in mind.
- Balanced Popet Design.** Will not chatter or drift. Factory outlet setting will not change even when inlet pressure varies 100 PSI. Regulator inlet rating 400 PSI. Unit only delivers line pressure. Delivery pressure is a function of flow.
- High Flow Capability.** Can be restricted for low flow requirements.
- Streamlined Low Profile Shape.** For neat installation and space saving requirements (1/4" NPTF).
- Easy to Install.** No brackets or special tools required. Regulator will function in any position.
- High Strength Aluminum Alloy.** Anodized for corrosion protection, also color coded. Other settings available upon request.

1/4"	2109 (40lbs)	Blue Band	2112 (90 lbs)	Red Band
	2110 (60 lbs)	Black Band	2113 (100 lbs)	Silver Band
	2111 (70 lbs)	Gold Band	2114 (110 lbs)	Brass Band
3/8"	2209 (40lbs)	Blue Band	2212 (90lbs)	Red Band
	2210 (60 lbs)	Black Band	2213 (100 lbs)	Silver Band
	2211 (70 lbs)	Gold Band	2214 (110 lbs)	Brass Band

WARNING: These air regulators are intended for use in compressed air systems only. Do not use where pressure or temperature can exceed rated operating conditions. See specifications. These air regulators are not designed for use with fluids other than air, for non-industrial applications, or for life support systems.



54-510



57-401



57-402



880N



57-403



57-404

Camel
No.

Amflo
No.

Large Capacity Portable Air Tank

Heavy-duty construction, 12-1/4" diameter by 20-3/8" long. Has 6 gallon capacity at 125 PSI. Includes: pressure gauge, filler valve and 4 feet of hose with ball foot chuck. **Cannot be sold in New Jersey in compliance with state laws.**

54-510

Replacement Dial Gauge. For 54-510 air tank.

54-515 1012-160

Replacement Hose and Fittings.

54-516

Replacement Manifold and Fittings.

54-517

Driveway Signal Bell

Bell rings when auto tire passes over the hose. Easy to install and wire for 110 volt, 3 wire ground cord. UL Listed.

57-401 880

Control Switch

Includes bracket and dust cover.

57-402

Late Bell Switch.

57-403 880CS

Coil Striker Assembly.

57-404 880CP

Hose Anchor-End Plug

880N

Camel
No.

Amflo
No.

Hose
Length

Signal Bell Hose

Durable rubber hose.

57-410		50'
57-411	494-100	100'
	494-500	500'

Amflo
No.

Barb
Size

Brass Bicycle Pump Fitting

Screw-on swivel chuck for most hand operated tire pumps.

705	3/16"
706	1/4"

706