

Camel No. Amflo No.

## Combo Coupler®

The solution for coupler confusion. Now one coupler fits 1/4" Aro Style, 1/4" Automotive Standard and 1/4" Industrial Interchange plugs. Convenient push-to-connect brass design. Temperature range -40°F to +240°F. Made in the USA.

<b>61-240</b>	<b>C60</b>	1/4" Series 1/4" NPT female
	<b>C60-23</b>	1/4" Series 3/8" NPT female
<b>61-241</b>	<b>C61</b>	1/4" Series 1/4" NPT male
	<b>C61-03</b>	1/4" Series 3/8" NPT male

**Combo Coupler® Merchandisers.** Can be placed on counter or hung on pegboard. Includes 16 couplers.

**29-240** 16 Female couplers.

**WARNING:** Use only on compressed air lines at a maximum pressure of 250 PSI for Combo Coupler®. For safety, do not exceed the pressure limitation of the hose and or air operated device you are using. Not for use with food stuffs or ingestible products.

Thread Type	NPT Size	Type Metal	COUPLERS			PLUGS		
			Camel No.	Amflo No.	Schrader No.	Camel No.	Amflo No.	Schrader No.

### 1/4" Series Lincoln Long Nose Type "A"

Plated steel couplers have hardened steel balls and stainless steel springs. Coupler plugs are heat treated to reduce wear on critical mating surfaces. The Lincoln Series of plugs are easily identified by the long plug end. The couplers are identified with one narrow and one wide groove on the sleeve. Couplers interchange with Lincoln as well as units produced by other manufacturers. **Maximum working pressure 300 PSI.**

Male	1/4"	Steel	<b>61-486</b>	<b>C27</b>	<b>3527</b>	<b>61-550</b>	<b>CP27</b>	<b>3531</b>
Female	1/4"	Steel	<b>61-548</b>	<b>C28</b>	<b>3528</b>	<b>61-551</b>	<b>CP28</b>	<b>3532</b>

Retail Pack (blister card) **61-555** One female 1/4" NPT Coupler, One Male 1/4" NPT

### 1/4" Series (Aro Series) Type "B"

Plated steel couplers have hardened steel balls and stainless steel springs. Coupler plugs are heat treated to reduce wear on critical mating surfaces. The Aro Series of plugs are easily identified by the distinct appearance of the plug. The couplers are identified with one wide groove on the sleeve. Couplers interchange with Aro 210 series as well as units produced by other manufacturers. **Maximum working pressure**

Male	1/4"	Steel	<b>61-527</b>	<b>C37</b>	<b>3525</b>	<b>61-528</b>	<b>CP37</b>	<b>3529</b>
Male	1/4"	Brass		<b>C37B</b>			<b>CP37B</b>	
Male	3/8"	Steel		<b>C37-03</b>			<b>CP37-03</b>	
Male	1/4"	Steel	<b>61-526</b>	<b>C38</b>	<b>3526</b>	<b>61-529</b>	<b>CP38</b>	<b>3530</b>
Female	1/4"	Brass		<b>C38B</b>			<b>CP38B</b>	
Female	3/8"	Steel		<b>C38-23</b>			<b>CP38-23</b>	
Female	1/4"	Steel		<b>C38-42</b>			<b>CP37-42</b>	
Hose Barb	3/8"	Steel		<b>C38-44</b>				
Hose Barb	3/8"	Brass					<b>CP37-44B</b>	
Hose Barb	1/4"	Steel		<b>C38-42L</b>			<b>CP37-42L</b>	
Lock-On Barb	3/8"	Steel					<b>CP37-44L</b>	

See price sheet for packaging options.



C60



C61



C27



C28



C37



C38

**WARNING:** Use only on compressed air lines at a maximum pressure of 300 PSI. For safety, do not exceed the pressure limitation of the hose and/or air operated device you are using. Not for use with food or ingestible products. If this product has a hose barb, make sure hose barb size matches the inside diameter of the hose you are using. All hose barb fittings must be secured to the hose with a hose clamp or crimped-on ferrule. Failure to follow these directions exactly may result in injury and/or property damage.

# Couplers & Plugs



C45



C46



C35



C36



CP37



CP36



C1



CP1



C2



CP2



C2-44

Camel No. Amflo No.

## 1/4" Series (Aro Series) Type "B" Coupler and Plug Set

Retail pack of one female 1/4" NPT coupler and one male 1/4" NPT plug on an attractive blister card.

61-530 C38AU

Thread Type	NPT Size	Type Metal	COUPLERS			PLUGS		
			Camel No.	Amflo No.	Schrader No.	Camel No.	Amflo No.	Schrader No.

## 1/4" Series (Aro Push-to-Connect) Type "B"

Push-to-connect couplers are automatically connected by pushing the plug into the coupler. Especially useful for hooking up implements. Allows one hand operation. Maximum working pressure 300 PSI.

Male	1/4"	Steel	61-581	C45	3525	CP37
Female	1/4"	Steel	61-518	C46	3526	CP38

## 3/8" Aro Series (Maximum working pressure 300 PSI)

Male	3/8"	Steel		C35		CP35
Female	3/8"	Steel		C36		CP36

## 1/4" Automotive Standard Series Type "C"

Plated steel couplers have hardened steel balls and stainless steel springs. Coupler plugs are heat treated to reduce wear on critical mating surfaces. The Automotive Series couplers interchange with Tru-Flate 10 and 100 type series as well as units produced by other manufacturers. Maximum working pressure 300 PSI.

Male	1/4"	Steel	61-524	C1	3503	61-538	CP1	3506
Male	1/4"	Brass		C1B			CP1B	
Male	3/8"	Steel		C1-03			CP1-03	
Female	1/4"	Steel	61-523	C2	3504	61-539	CP2	3507
Female	1/4"	Brass		C2B			CP2B	
Female	3/8"	Steel		C2-23			CP2-23	
Female	3/8"	Brass		C2-23B			CP2-23B	
Hose Barb	1/4"	Steel		C2-42			CP1-42	
Hose Barb	1/4"	Brass		C2-42B				
Hose Barb	3/8"	Steel		C2-44			CP1-44	
Lock-On Barb	1/4"	Steel		C2-42L			CP1-42L	
Lock-On Barb	3/8"	Steel		C2-44L			CP1-44L	

See price sheet for packaging options.