

"Pencil Type" Pressure Gauges

Properly inflated tires can:

- Improve gas mileage up to 10%
- Improve tire life up to 30%
- Reduce chances of blowouts
- Always check tire pressure when tires are cold

Camel No. Amfco No. Quantity

Pocket Gauges

Pocket Gauge. Calibrated from 10 to 50 PSI in 1 PSI increments. Nylon indicator bar and gold anodized barrel with brand logo. Refill for 40-425 and 918.

40-100 5 pack

Pocket Gauge. Calibrated from 10 to 50 PSI in 1 PSI increments and 75 to 325 in KPA increments. Nylon indicator bar. Chrome plated barrel.

40-400 901D* 5 pack

40-400-100 100 pack

10 pack

PSI / Metric Pocket Gauge. Calibrated from 10 to 75 PSI in 1 PSI increments and 70 to 500 in KPA increments. Chrome plated barrel and nylon indicator bar.

40-401 1 pack

High Pressure Truck Gauge. Calibrated 20 to 120 PSI in 2 PSI increments and 150 to 800 in KPA increments. Silver anodized finish.

40-406 906AD* 1 pack

40-406-100 100 pack

Straight-On Pocket Gauge. Calibrated from 10 to 50 PSI in 1 PSI increments and 75 to 325 in KPA increments. Silver anodized barrel with push-on head and nylon indicator bar.

40-408 1 pack

Dial Gauges

Economy Dial Gauge. Calibrated from 1 to 50 PSI and also in KPA. Imported. Not for speed rated tires.

40-205 1 pack

High Pressure Tire Gauge. Calibrated from 20 to 120 PSI.

40-412 5 pack

Low Pressure Dial Gauge. For go-carts, air shocks, all low pressure tires, racing tires and other low pressure applications. Rubber bumper protects dial case. Slide valve allows locking-in tire pressure after removal from tire. Calibrated 0-16 PSI and in KPA.

40-415 961D 1 pack

Dial Gauge with Bleeder. 0-60 PSI.

40-435 10 pack

Dial Gauge. 0-100 PSI.

40-440 10 pack

Mini Dial Gauge. Calibrated from 1 to 60 PSI.

54-518 1 pack

Camel No. Amfco No. Schrader No. Quantity

High Pressure Bicycle Gauge

Our finest bike and cycle gauge. Calibrated from 20 to 120 PSI in 2 PSI increments. Silver anodized barrel. 1 pack.

40-411 8101A (10 pack)

Economy Gauges

Automotive Gauge. 10-100 PSI.

40-200 10 pack

40-200-1000 1000 pack

Pencil Gauge. 10-50 PSI.

40-201-100 100 pack

Pencil Gauge. 10-50 PSI, anodized.

40-202 100 pack

40-202 (Imprintable*) 100 pack

Private label available with orders over 500 pieces.

*One time setup charge of \$125 applies.



Camel No. Amfco No. Schrader No. Quantity

Economy Cycle Gauge

Calibrated from 10 to 50 PSI. Imported.

40-211 (1 pack) 7780A (10 pack)

Low Pressure Gauge

Use with air shocks and low pressure tires. Calibrated from 1 to 20 PSI in 1/2 PSI increments and 10 to 130 in KPA increments. Nylon indicator bar and anodized barrel.

40-399 905AD 1 pack

Tread Depth Gauge

Steel indicator bar. Calibrated from 0 to 1" in 1/32". With pocket clip.

40-395 925D* 1 pack

Athletic Ball Inflation Check Gauge

Calibrated 1 to 20 PSI in 1/2 lb. increments. For maximum performance out of your sports ball.

40-300 5 pack

Replacement needle.

40-301 (3) 5 pack

40-301-10 10 pack

Heavy-Duty Pressure Gauges

Heavy-Duty Pressure Gauges



Camel No. Amflo No. Schrader No. Quantity

Truck and Bus Pressure Gauge

Our best selling heavy duty gauge with dual foot chuck. Calibrated 10 to 150 PSI in 2 PSI increments on nylon bar.

40-403	902D (5 pack)	1250A (5 pack)	1 pack
40-403-100			100 pack
40-250 (epoxy)			5 pack
Same as above, but has unbreakable aluminum indicator bar.			
40-430	903D*	7188BH	1 pack
40-430-100			100 pack

Pocket Type Dual Head Gauge. Calibrated from 20 to 120 PSI, in 2 PSI increments, durable chrome plated finish.

40-407	908D*	8102A	1 pack
40-407-100			100 pack
40-260 (epoxy)			5 pack

Pocket Size Truck Gauge. Calibrated from 20 to 120 PSI and 150 to 800 KPA increments. Baked Epoxy Powder Finish.

Reverse 30° dual foot head makes it easy to read pressure on inner dual wheels. Calibrated 10 to 150 PSI, with metal bar. Chrome finish.

40-050			1 pack
40-050-100 (100 pack)		7188L (1 pack)	100 pack
40-255 (epoxy)			5 pack

Reverse 30° dual foot head makes it easy to read pressure on inner dual wheels. Calibrated 10 to 150 PSI, with metal bar. Chrome finish. Carded.

40-052			1 pack
--------	--	--	--------

Master Pressure Gauge

Our most accurate gauge. Used to check other gauges. Dual foot construction with 6" extension. Calibrated 10 to 165 PSI. Black matte finish with chrome plating. 1 pack.

40-410	909D*		
--------	-------	--	--

Dial Gauges

High Pressure Dial Gauge. Calibrated 0 to 60 in PSI and KPA. Locking sleeve design. 1 pack.

40-420	962D*		
--------	-------	--	--

Air/Liquid Tractor Gauge. For tractor tires that contain ballast. Calibrated 10-50 PSI, silver anodized finish.

40-402	904D*		1 pack
40-402-100		9350	100 pack
		9350-D	10 pack

Dual Range Dial Gauge. 0-160 PSI in 2 PSI increments. Similar to 980 series (below). 1 pack.

40-409	980-160D*		
--------	-----------	--	--

Amflo No.	Range PSI	Smallest Division	Range KPA	Smallest Division
-----------	--------------	----------------------	--------------	----------------------

980 Series Dual Range Master Dial Gauges

Swivel dual foot with hose. Extremely accurate. Dual calibrated in PSI and KPA. Available boxed or on display card.

980-15	0-15	1/4 PSI	0-100	2 KPA
980-60	0-60	1 PSI	0-400	10 KPA
980-160D*	0-160	2 PSI	0-1100	20 KPA

*Display Package

WARNING: For best results check tire pressure when the tires are cold or when the vehicle has not been driven for several hours. Readings taken after prolonged driving at high speeds will increase tire pressure causing a false reading. Check tire pressure at least once a week or as necessary. Consult your Owner's Manual for the recommended air pressure for your tires. These gauges have been accurately calibrated and inspected. For continued accuracy, take care of them as you would any precision instrument.

980-160D

40-420

Gauge Displays / Digital Gauges

Camel No. Amflo No. Schrader No.

Flashing Tire Gauge Display

Flashing display, loaded with gold finished gauges grabs customer's attention.

40-424 917 7770

Bucket of Gauges

Counter merchandiser is a time proven best seller. Includes 18 gauges for the cost of 14 and the display. Sets up in seconds. Uses only a few square inches of counter space. Gauges are calibrated 10-50 PSI in 1 PSI increments. 1 pack.

40-425 918

The Executive Series

Key chain and gauge. Easy disconnect/reconnect key chain. Tire gauge calibrated from 10-50 psi.

40-450 Gold
40-460 Chrome

Digital Tire Pressure Gauges

Easy to use and easy to read, even at night. Advanced engineering offers maximum performance and precision accuracy. Lithium Battery.

40-705 Digital Key Chain Tire Gauge 5-60 PSI (1 lb units)
40-710 Standard Digital Tire Gauge 5-99 PSI (1/2 lb units)
40-715 Pro Digital Tire Gauge 5-150 PSI (1/2 lb units)
40-720 The Mechanic's Digital Pressure Gauge 5-150 PSI (1/2 lb units)
40-725 The Mechanic's Digital Tire Gauge 5-99 PSI (1/2 lb units)

Tire Gauge Displays

Eye catching displays includes 10 or 20 standard tire gauges in vibrant colors – red, blue, black, chrome and metallic green. Designed to accommodate peg hook or counter top display, wherever your store traffic is heaviest. The gauges are calibrated on 4 sides 10-50 PSI in 1 lb.

40-800 10 Piece Gauge Display
40-850 20 Piece "Increase Your Gas Mileage" Gauge Display
40-855 20 Piece "USA" Gauge Display

40-715



40-725



40-855



40-850



40-425

40-450



40-720



40-705



40-710



Tire Service Tools

Tire Service Tools



41-067



41-469



41-444



41-466



5262



41-506

Camel No.	Amflo No.	Schrader
-----------	-----------	----------

4-Way Tire Valve Repair Tool

Repairs core and stem threads. Has core screwdriver and broken core extractor. 1 pack.

41-067*	922D*	
41-067-20 (20 pack)	922 (Amflo 10 pack)	3522

Valve Core Extracting Tool

All metal construction. 1 pack.

41-469*	921D*	
41-469-20 (20 pack)	921 (Amflo 10 pack)	2688

Valve Core Extractor With Plastic Handle

41-444 (1 pack)

Tube Deflating Aspirator

Removes air quickly by creating a vacuum effect when air is applied to threaded chuck. 1 pack.

41-460	926	5262
--------	-----	------

Valve Fishing Tool

Centers valve in rim hole while mounting tires. For use on .453" and .625" rim holes. 1 pack.

41-466	923D*	353A
--------	-------	------

Tubeless Tire Inserting Tool

Used for installation and removal of rubber snap-in valves. 1 pack

41-506	990D*	992
41-506-5	990	

Double Use Tool

For deflating tire tube and core removal. 1 pack

41-068	924D*	7657
41-068-20	924 (Amflo 10 pack)	

Cap and Core Tool

Grip and holds core bridge and cap to provide means of inserting cores in hard to reach valves.

*Display Package

8769A



8769A

41-068

Camel No. Amflo No.

Camel No. Amflo No. Schrader No.

Standard Series

(Amflo 150 type.) Features chrome plated castings with brass internal parts for long life. Solid brass bar is calibrated 10 to 90 PSI in 2 PSI increments.

Straight-On Tapered Chuck Inflator. With 12" hose. Standard unit for commercial applications. 1 pack.

40-575 150D
150 (boxed)

Swivel Dual Foot Chuck Inflator. With 12" hose. Use on motor homes and other vehicles with smaller dual wheels. 1 pack.

151

Swivel Angle Chuck Inflator. For cars and light trucks with wheel covers. 12" rubber hose. 1 pack.

152D
152 (boxed)

Inflator with Straight Chuck. Has 36" hose with bleeder valve. 1 pack.

154

Heavy-Duty Series

(Amflo 100 type.) Heavy chrome plated castings with protective sleeve over dial tube. Plated steel handle is riveted to body. Solid brass bar is calibrated 10 to 120 PSI in 2 PSI increments.

Straight-On Tapered Chuck Inflator. With 12" hose.

100D
100 (boxed)

Swivel Dual Foot Chuck Inflator. Has 12" hose. For use on motor homes and other vehicles with smaller dual wheels.

40-591 101D
101 (boxed)

Safety Inflator. Use on trucks especially with split rims. Long 36" hose permits operator to stand clear while inflating or deflating tire. Lock-on chuck and bleeder valve add safety and convenience. 1 pack.

40-592 129

Same as 40-592 (above) except has 72" hose. 1 pack.

40-594

130 Same as 40-129 except with 12" Hose. 1 pack.

Dual Foot Chuck Safety Inflator. For use on trucks with split rims. Has 36" hose and dual inflators that permit operator to stand clear while inflating or deflating tire. Lock-on chucks and bleeder valve add safety and convenience. 1 pack.

128

Safety Inflator with Clip-On Chuck. Has long 36" rubber hose and brass bleeder valve. 1 pack.

40-593 160

Same as above except with 72" hose. 1 pack.

40-598 171

Highly Accurate Dial Inflator. Easy to read dial is calibrated 0 to 160 PSI. Unit is protected with a heavy rubber cushion "bumper." The tapered chuck and swivel dual foot make getting into tight spots easy. A must for racing tires and truck fleets. 1 pack

135

Same as above, except with 6" extension. 1 pack.

135-2

Inflator Gauge with Sight Glass. Calibrated 12 to 120 PSI. Sturdy cast aluminum body. Hose is 12" long with plated dual foot chuck. 1 pack.

40-665 180D 3651-D

Cartridge for sight glass (as listed above). 1 pack.

40-608




171



180D


135



150



151



152




100



101



128



129

Use ONLY oil free and water free compressed air. Maximum pressure of air source should NOT exceed 220 PSI. DO NOT use for inflating or checking pressure on air/liquid tires or other tires containing corrosive materials.

WARNING: For best results, check tire pressure when tires are cold or when vehicle has not been driven for several hours. Readings taken after prolonged driving at high speeds will increase tire pressure causing a false reading. Check tire pressure at least once a week or as necessary. Consult your owner's manual for the recommended air pressure for your tires. Gauges have been accurately calibrated and inspected. For continued accuracy, take care of them as you would any precision instrument.

Inflator Gauges, Hoses & Pressure Equalizer

Camel No. Amflo No.

Master Air & Replacement Hose

Standard Bore Inflating Gauge	3910S	Inflates and checks pressure of passenger cars, motorcycles and trucks. Has a five foot hose length. Dual calibrated 10 to 170 PSI and .7 to 12 bar. Calibrated in two pound increments. 1 per box.
Replacement Hose	3911	

110

1120

40-701

40-704

40-706

40-762

40-763

40-765

110

1120

161

116

113

153

159

- 12" whipend no chuck 1/4" NPT swivel end.
- 12" hose with straight chuck. Display package.
- 72" hose with lock-on chuck and bleed valve.
- 12" hose with lock-on chuck.
- 36" hose with ball foot lock-on chuck and bleed valve.
- 72" hose with ball foot lock-on chuck and bleed valve.
- 36" hose with bleed valve and lock-on chuck.
- 12" hose with dual foot chuck.
- Replacement indicator bar for (150 series) inflator gauge. 1 pack.
- Replacement valve unit for (150 series) inflator gauge. 1 pack.

3910S

161

116

Visualizer II® Pressure Equalizer

Visualizer II, - Dual Tire Pressure Equalizer - Extend Tread Life up to 30%

Visualizer II, state-of-the-art tire pressure equalizer allows air to flow freely between dual tires to maintain equal inflation. Visualizer II connects tire valves to an equalization module that equalizes pressure between inside and outside tires. Unit allows vehicle operator to visually check for correct tire pressure.

- Chrome plated housing
- Heavy-duty construction
- Factory preset tire inflation levels
- Provides accurate callibration
- Easy installation
- Single valve inflation
- Automatic safety cut-off
- Color-coded pressure indicators
- Stainless steel braided hose with nickel-plated fittings

Eliminate costly maintenance and wear problems. Install Visualizer II dual tire equalizer on tractors, trailers and medium-duty trucks, even ones with chrome hub caps. Visualize the benefits of proper and balanced dual tire inflation on your fleet.

- Increases fuel mileage
- Reduces blowout risk
- Decreases tire maintenance
- No valve core removal required
- Extends tread life
- Improves traction
- System removal not required for tire service

Unit is color-coded to provide proper inflation information. RED under inflation, GREEN indicates proper inflation and YELLOW over inflation.













Without Visualizer II
As tires heat up, tire pressures increase unequally



With Visualizer II
Equal tire pressures maintained for optimal performance



Visualizer II offers specialized kits to meet the requirements of most vehicles.

Kit No.	Description	
1125 Kit 3	Stainless steel replacement hose kit.	
1125 Kit 5	Center axle mount for Fruehauf Pro Par trailer axles.	
1125 Kit 6	Strap bracket for Mack, International tractors and others with 3/4" axle bolts.	
1125 Kit 10	Tractor and trailer axles with hubodometer.	
1125 Kit 11	General-purpose trailer bracket for axles with 5/16" axle hub bolt holes.	
1125 Kit 12	5/8" universal application strap bracket	
1125 Kit 13	Center hub mount for tractor and truck axles with 1/2" bolt holes.	
1125 Kit 14	Center hub mount for tractor and truck axles with 9/16" bolt holes.	
1125 Kit 15	Center hub mount for most tractor and trailer axles with 5/8" hub bolt holes including Kenworth, Peterbilt, Navistar and others.	
1125 Kit 16	Center hub mount for tractor and truck axles with 3/4" bolt holes including Mack, International, GMC and others.	
1125 Kit 18	Wheel mount for all wheels with hub-piloted wheel bolts and chrome hub caps or hubodometer with 7/8" bolt holes.	
1125 Kit 19	Wheel mount for all wheels with stud piloted wheel bolts and chrome hub caps or hubodometer with 1 1/8" bolt holes.	
1125 Kit 21	For truck and trailer axles with oil seals.	

How to Order Visualizer II®

Visualizer II is available in 5 pound increments – from 60 psi to 120 psi.

- Specify the psi setting required: 1125-60, 1125-65, 1125-70, 1125-75, 1125-80, 1125-85, 1125-90, 1125-95, 1125-100, 1125-105, 1125-110, 1125-115 or 1125-120.
- Includes two hoses to connect both tires to Visualizer II.
- For more Visualizer II information, contact Schrader-Bridgeport customer service.

LIMITED WARRANTY: Schrader-Bridgeport warrants its products to be free from defects in material and workmanship for a period of 30 days from the date of purchase. This warranty shall be null and void if product is improperly installed or altered.

Air Chucks

	Air Line Chucks for Live Air Lines Only Chucks have a built in shut-off valve and will not work on inflator gauges.			Air Line Chucks for Inflator Gauges Only Chucks have no shut-off valve and will not work on live air lines.		
	Camel No.	Amflo No.	Schrader No.	Camel No.	Amflo No.	Schrader No.
Combination Chuck W/401 1/4" I.D. hose barb. 	50-061					
1/4" NPTF Ball Foot Chuck 	50-062 50-962 (20 pack)	1040 (Brass) 104 (10 pack) 104ZND (Zinc) 104ZN (10 pack) 104M (Brass male)	5499		104G (Brass 10 pack)	
1/4" NPTF Ball Foot w/ Clip 	50-621 50-961 (20-pack)	104CAZND (Zinc 1 pack) 104CAD (Brass) 104CA (Brass 10 pack)	6739	50-622	104GCA (Brass 10 pack)	7000-6
1/4" NPTF Angle Chuck 		105L (10 pack)			105 (10 pack)	
1/4" NPTF Lock-On Chuck 	50-459	119D 119 (10 pack)	5265		120 (10 pack)	
1/4" NPTF Dual Safety Lock-On Chuck 		118D 118 (1 pack)			117 (1 pack)	
1/4" NPTF Straight Chuck 		126 (10 pack)			127 (10 pack) 106 (Barb)	
Chuck Lock-On Clip (Fits all ball foot chucks.) 	50-429	104CD	6529	50-429	104CD	6529
European Style Air Chuck 				50-066 (3/16") 50-067 (1/4")		1137-6
1/4" NPTF Dual Foot Chucks - Angled 	50-065 50-965 (20 pack) 50-700 (epoxy)	109		Angled 50-651 50-702 (epoxy)	107 (1 pack) 107D	8340B
1/4" NPTF Dual Foot Straight Chuck 	50-435 50-704 (epoxy)	108 121 (12")		50-706 (epoxy)		
1/4" Long Reach Chuck w/Angled & Straight-on 14" Long	50-708 (epoxy)			50-710 (epoxy)		
Repair Kits Dual foot repair kit, 1 kit per bag, 10 bags per box. Dual foot washers, 10 bags of 10. Ball foot chuck repair kit, 10 bags per box. Ball foot washers, 10 bags of 10.				50-030 50-016 50-031 50-017		