

Quantity	Camel No.	Schrader No.
----------	-----------	--------------

Chrome Sleeve Snap-In Valves.

Used for .453" diameter rim holes. Do not use on tires that exceed 65 PSI or on rims that exceed .156" thickness.

TR 413. 1-1/4" Effective length.

4 pack*	30-136	
50 pack	30-136-50	413SC-50
500 pack	30-136-500	413SC-500

TR 418. 2" Effective length.

2 pack*	30-186	
50 pack	30-186-50	418SC-50
500 pack	30-186-500	418SC-500

Snap-In Valves for .453" Rim Holes

TR 412 Snap-In Valve

Fits smaller wheel sizes like hand trucks, wheelbarrows, golf carts, and other specialty vehicles with .453" diameter rim hole. Effective length 7/8". Maximum inflation pressure 60 PSI.

2 pack	30-412-2	
50 pack	30-412-50	412-50
500 pack	30-412-500	412-500

TR 413. 1-1/4" Effective length.

2 pack*	30-413-2	
10 pack	30-413-10	
50 pack	30-413-50	413-50
500 pack	30-413-500	413-500

TR 414. 1-1/2" Effective length.

2 pack*	30-414-2	
10 pack	30-414-10	
50 pack	30-414-50	414-50
500 pack	30-414-500	414-500

TR 418. 2" Effective length.

2 pack*	30-418-2	
10 pack	30-418-10	
50 pack	30-418-50	418-50
500 pack	30-418-500	418-500

TR 423. 2-1/2" Effective length.

4 pack*	30-423-4	
10 pack	30-423-10	
50 pack	30-423-50	423-50
500 pack	30-423-500	423-500

WARNING:

Do not use snap-in valves on tires that exceed a cold inflation pressure of 60 PSI. Do not use on rims that exceed .156 thickness.

Quantity	Camel No.	Schrader No.
----------	-----------	--------------

Snap-In Valves for .625" Rim Holes

TR 415. 1-1/4" Effective length.

2 pack*	30-415-2	
10 pack	30-415-10	
50 pack	30-415-50	415-50
500 pack	30-415-500	415-500

TR 425. 2" Effective length.

4 pack*	30-425-4	
10 pack	30-425-10	
50 pack	30-425-50	425-50
500 pack	30-425-500	425-500

Special Purpose, High Pressure Snap-In Valve

TR 600 "HP" Tubeless High Pressure Snap-In Valve. Rated to 100 PSI, includes core and cap. .453", 1.27" effective length. Not for rims over 205" thick.

2 pack*	30-600-2	
10 pack	30-600-10	
50 pack	30-600-50	600HP-50
500 pack	30-600-500	600HP-500

TR 801.

.625" rim hole and 1.31 effective length.
500 pack 30-801-500 801HP-500

Chrome Sleeve and Nut Dress-up Kits.

Used to dress-up rubber snap-in valves. Includes 4 sleeves and 4 chrome nuts. Display packed.

4 pack*	30-316-4	(Fits TR413)
4 pack*	30-318-4	(Fits TR418)

TUBELESS SNAP-IN TIRE VALVES

WARNING: The conventional tubeless tire snap-in valves on this page should not be used with tubeless tires where cold inflation exceeds (or may exceed) 65 PSI. Do not use these valves in rims exceeding .156" in thickness. For thicker applications use a high pressure snap-in or a clamp-in valve. To protect you and your tires, all tire valves should be replaced when cracks first appear. New tire valves are recommended each time new tubeless tires are installed...also when snow tires are mounted or removed.

*Display Package.



Clamp-In Valves

Camel No.	Schrader No.	TR No.	A	B REF.	Y°	Cap	Core	O-Ring
-----------	--------------	--------	---	--------	----	-----	------	--------

Truck Tubeless Valves - 540 Series

Designed for use with 9.7 cm (.328") rim hole. Rubber O-Ring forms a seal when valve is clamped to rim by tightening hex nut. Designed specifically for use in aluminum wheels.

32-541-10	543	543	2.31		0	7572	5405	543-3
32-543-10	543D	543D	2.31	1.38	60	7572	5405	543-3
32-545-10	543E	543E	2.31	1.38	75	7572	5405	543-3
32-544-10	544D	544D	2.86	1.94	60	7572	5405	543-3
32-547-10	545D	545D	3.50	2.60	60	7572	5405	543-3



543D

Schrader No.	Fits Valve Hole Dia.	For Use On	Standard Pack
--------------	----------------------	------------	---------------

O-Rings

543-3	.328"	TR 540 Series	100
-------	-------	---------------	-----



595-3

Camel No.	Schrader No.	TR No.	Fits Valve Hole Dia.	For Use On	Standard Pack
-----------	--------------	--------	----------------------	------------	---------------

Grommets

30-469-100	9939-3	RG-39	.625"	TR 416	10 per env., 10 env./box
	5976-5	RG-54	.453"	TR 416	10 per env., 10 env./box
32-985-100	595-3	RG-15	.625"	TR 570 Series	10 per env., 10 env./box
32-946-100	509-3	RG-46	.625"	TR 509, TR 510	10 per env., 10 env./box

Camel No.	Schrader No.	TR No.	Effective Length
-----------	--------------	--------	------------------

Tubeless Double Bend Clamp-In Valve

Use on one piece drop center rims with 13/16" rim holes. First bend is 90°, the second is 25°.

32-304-10	504A	3-3/8"
32-305-10	505A	3-3/4"



32-305

Tubeless Single Bend Clamp-In Valve

For one piece drop center **aluminum** disc wheels with 5/8" rim holes. Has 90° bend.

32-309-10	509-10	509	4-3/4"
32-309-100		509	4-3/4"
32-309-250		509	4-3/4"
32-310-2*		510	5-1/2"
32-310-10	510-10	510	5-1/2"
32-310-100		510	5-1/2"
32-310-250		510	5-1/2"



32-309

Quantity	Camel No.	Schrader No.	TR No.
----------	-----------	--------------	--------

TR 430 Tubeless Clamp-in Motorcycle Valve

Fully threaded stem for use on many rim thicknesses. "O" ring seal. Effective length 1-3/16", fits .327" valve hole.

10 pack	30-430-10	6205	430
---------	-----------	------	-----



30-430

TR 417 Clamp-In Valve for Front Wheel Drive

Use on Cadillac El Dorado and Oldsmobile Toronado through 1978.

5 pack	30-472-5	5976A 5976-5	417
--------	----------	-----------------	-----



30-472

Camel No.	Schrader No.	Packaging
-----------	--------------	-----------

5991B High Performance Tire Valve

Chrome plated clamp-in valves are easily installed in all types of passenger car wheels with .453" or .625" valve holes.

30-445		4 per 1 card	<i>Amflo # 703</i>
30-445-50	5991B-50	50 per box	
	5991B-500	500 per box	

Camel No.	Amflo No.	Schrader No.	TR No.	Effective Length	Packaging
-----------	-----------	--------------	--------	------------------	-----------

Clamp-In Tubeless Tire Valves

Nickel plated metal valves can be installed in all passenger cars, light trucks and industrial rims with .453" or .625" valve holes. Rubber grommet forms a seal when valve is clamped to rim by tightening hex nut. Maximum inflation pressure is 130 PSI. Includes 2 rubber grommets.

30-463	702D*		416	1-1/4"	1 per box
	702		416	1-1/4"	10 per box
30-463-50	702-50	3640-50	416	1-1/4"	50 per box
30-463-500		3640-500	416	1-1/4"	500 per box
		3641-50	416	2"	50 per box

Hex Nut. TR No. HN-4. Fits tread .406"-28. For use on TR 416. 500 pack.

Replacement grommet for .453" hole

5976-5
Replacement grommet for .625" hole
9939-3

These products, as well as all tire tools should only be used by trained individuals according to O.S.H.A. Regulation #29CFR 1910.177 entitled "Servicing Single Piece and Multi-Piece Wheels."



30-445



30-463



CAUTION:

Due to production techniques, the rim valve hole should be checked for burrs and cleaned if necessary.

* Display Packs

Truck, Bus Valves



32-200



32-204



32-205



32-600

Camel No. Schrader No. TR No. Effective Length Hex Nut

Straight Clamp-in Valve

For use in one piece drop center rims with 5/8" diameter side mount valve holes.


32-200-2*			500	2"	595-4
32-200-10	595-10		500	2"	595-4
32-200-100	595-100		500	2"	595-4
32-200-250			500	2"	595-4
32-201-10	570-10		570	3-1/8"	595-4
32-201-100	570-100		570	3-1/8"	595-4
32-201-250			570	3-1/8"	595-4
32-202-2*			571	3-3/8"	595-4
32-202-10	571-10		571	3-3/8"	595-4
32-202-100	571-100		571	3-3/8"	595-4
32-202-250			571	3-3/8"	595-4
32-203-10	572-10		572	3-3/4"	595-4
32-203-100	572-100		572	3-3/4"	595-4
32-203-250			572	3-3/4"	595-4
32-204-2*			573	4-3/8"	595-4
32-204-10	573-10		573	4-3/8"	595-4
32-204-100	573-100		573	4-3/8"	595-4
32-204-250			573	4-3/8"	595-4
32-205-10	501-10		501	1-1/2"	595-4
32-205-100	501-100		501	1-1/2"	595-4
32-205-250			501	1-1/2"	595-4
32-207-10	5538-10		575	1-1/8"	595-4
32-207-100	5538-100		575	1-1/8"	595-4
32-207-250			575	1-1/8"	595-4
32-208-50	574-10		574	5"	595-4
32-208-100	574-100		574	5"	595-4
32-208-250			574	5"	595-4

These valves may be bent to the desired configuration in accordance with tubeless valve dimension chart in section eight (8) of Tire and Rim Book, made to order.

*Display pack

Import Truck Tubeless Valves (ETRO)

Used on Volvo, Mack and Iveco imported trucks. Fits .382 dia. (9.7mm) rim hole. Includes O ring, nut, core and cap. 10 pack. (See chart on right.)



Camel No.	Michelin No.	Schrader No.	Etro No.	DIN NO.	A*	B*	C*	D
--	--	1080	--	65MS9.7	.98/25	.98/25		27°
32-600-10	964	1083	V3-20-1	41MS9.7	.98/25		1.42/36	0°
32-604-10	1500	1129	V3-20-7	65MS9.7	.98/25	1.97/50		27°
32-608-10	1485	1130	V3-20-4	87MS9.7	.98/25	2.36/60		27°
--	--	1131	--	95MS9.7	.98/25	2.76/70		27°
32-612-10	1437	1132	V3-20-6		.98/25	3.35/85		27°

* Inches and Millimeters



Schrader No. Effective Length Packaging

Chrome Truck Valves

Chrome Plated Clamp-In Type Truck and Bus Tubeless Tire Valves. For .625" side hole valve mountings.

501CR-100	1-1/2"	100 per box
572CR-100	3-3/4"	100 per box
573CR-100	4-3/8"	100 per box

Camel No. TR No. Length

Tube/Screw on Valves

33-150-5 TR 150 Hand Bendable Valve. Used in light truck tubes. May be applied with vulcanizer or cement. Effective length 3-1/2" shank diameter .615". Available in packs of 5 and 100.

Standard Tube Convertible Valves. Valves can be bent as needed. May be applied with heat vulcanization or Universal Cement.

33-304-5	77A	4-29/32"
33-306-5	78A	5-25/32"
33-306-10	78A	5-25/32"
33-310-5	175A	5-9/32"
33-310-100	175A	5-9/32"
33-314-5	179A	6-11/32"

Replacement Hex Nut. For use with standard convertible valves for truck tires.

33-075 (25 pk.) Schrader No. **595-4** (1000 pk.)

Screw-On Repair Valves. Convertible from single bend to double bend. Includes bridge washer. These repair valves permit replacing damaged cured-in or cured-on valves without cutting out old valve base. Schrader 7799 VALVE HOLDING TOOL is recommended for gauging cut-off length of damaged valve to proper length for attaching these valves. Dimensions are the same as original valves. Repair valves are supplied in single-bend form with bridge washers.

33-000-10	1075A	3"
33-004-10	1077A	4-1/8"
33-006-10	1078A	5"
33-006-50	1078A	5"
33-010-2	1175A	4-1/2"
33-010-10	1175A	4-1/2"
33-012-10	1177A	3-3/4"
33-014-5	1179A	5-9/16"

Camel No. Michelin No. Bend Length

Michelin Type Truck Tube Repair Valves

Includes standard valve core which fits housings manufactured to I.S.O. specifications.

33-118-5 751 Single 5-1/4"

33-399 Special flat washers must be used with repair valves. (above). 5 pack.

Camel No. Schrader No.

Specialty Truck Valves

Oval Slot Valve. Designed for Firestone 16 x 6 KS and 16 x 6-1/2 LS wheels. Completely assembled with grommets, washers, hex nut, valve core and valve cap. 10 pack. (See caution below)

32-400-10 **1161**

CAUTION: Due to production techniques, the rim valve hole should be checked for burrs and cleaned if necessary.



Special Valves



1468L-6

1498L-6



38-900

645L-6



9166L-8

38-906



5007



701-2



556/2755



6116

Tank Valves

WARNING: Product is designed for use with compressed air tanks. Be certain the tank valve is securely threaded into the vessel or tank wall. Read air tank manufacturer's caution statement regarding maximum air pressure. Do not attempt to over fill tank. Failure to follow these specifications and directions exactly may result in personal injury and/or property damage.

Tank Valves

For air tanks, steel barrels, compressors, and other pneumatic containers where dependable automatic air valves are needed. Valves are equipped with standard valve core and sealing caps for operating pressures to 200 PSI. These valves have NPT male threads and allow for external length variations by use of short core only or internal protrusion of core housing into container.

Schrader No.	Descr.	Standard Pack	Stem	Core	Cap	NPT	Stem Material
645L-6	Tank Valve	25	645-1	8500T	6300C	1/8"	Brass/NP
9166L-8	Short Tank Valve	25	9166-1	8500T	7572	1/8"	Brass/NP
1468L-6	Tank Valve	25	1468-1	8500T	6300C	1/8"	Brass/NP
1498L-6	Tank Valve	25	1498-1	8500T	6300C	1/4"	Brass


Camel No.	Amflo No.	NPT	Effective Length	Pack
38-900-10	700	1/8"	29/32"	1 pack
38-906-10	701-2	1/8"	17/32"	10 pack
	701-42	1/4"	3/4"	10 pack
		1/4"	barbed	10 pack

*Display Package +Amflo No. 700 is available in 10 pk.

High Pressure Valves

These valves are constructed of special stainless steel bodies and are intended for use in high pressure air-charged units such as shock absorber struts, hydraulic pressure accumulators, surge cylinders, and pneumatic systems. These valves have a special feature which warns of unreleased air pressure when the valve is being separated from the outlet. Contact our customer service department for further information on military and commercial adaptations. 1/2"-20 U.N.F.-3A threads for connection to container.

Schrader No.	AN/MS No.	Cap	Core	Working Pressure
7607AH	AN-812-1	2525	2300T	2,000
4361S	AN-6287	2525	2300T	3,000
798	MS28889-2	2525		5,000



High-Pressure Inflating Connections

These high-pressure inflating connections attach securely by hand or wrench to the valve cap threads of high-pressure valves. Can be fitted to gauging and inflating devices by a variety of methods. Various angles permit easy attachment to hard to reach valves.

Schrader No.	Fits Thread Size	Air Line Connection	Max. Pressure Rating (PSIG)	Configuration	Recommended Max. Torque To Valve Mouth*	Remarks
556	.305-32	1/8" NPT Male	3,000	Air line connection 90° to axis of valve	50 in.-lb.	Has core depressor pin copper sealing washer
2755	.305-32	3/8"-24 thread for 3/16" flare tube fitting, meets MS 33656E3	3,000	Air line connection 90° to axis of valve	50 in.-lb.	Has core depressor pin, copper sealing washer
5007	.305-32	7/16"-20 thread for 1/4" flare tube fitting, meets MS 33656E4	15,000	Straight	75 in.-lb. for steel valves	Copper sealing washer
6116	.305-32	1/8" NPT Female	3,000	Air line connection 70° to axis of valve	30 in.-lb.	Hard fiber sealing washer
5784	.305-32	7/16"-20 thread for 1/4" flare tube fitting, meets MS 33656E4	5,000	Air line connection 70° to axis of valve	30 in.-lb.	Hard fiber sealing washer

It may be necessary to replace sealing washers after a number of uses to insure sealing on valve mouth.

Camel No. Schrader No. Standard Pack

Hi-Performance Valve

For 1987-88 model year Corvette. Black chrome finish. 1-1/4" Effective length.

30-400-10 10 pack



30-400

Rubber Washer Repair Kit

Ten assorted rubber washers for 30-463. 1 kit/bag, 10 bags/box.

30-468 9939-3
5976-5



30-468

Tube Type Passenger Valves

Special compound cushion gum base allows bonding of valve to the tube using hot or cold (chemical bond). 5 per pack.

Camel No.	Shank Diameter	Effective Length	TR No.
31-013-5	.406	1-3/8"	13
31-015-5	.651	1-3/8"	15
31-251-5	.651	1-15/16"	25

Camel No.

TR1 Bicycle Tube and Industrial Valves

Rubber base tube valves are for replacement on implement, scooters, and trailer tubes. May be applied with either "hot" or "cold" vulcanizing.

31-194-10



31-013

Rim Hole Bushing

Camel No.

Used to reduce the size of large rim holes so TR-13 valve fits more snugly. 100 per pack.

31-336-100

Schrader No. Fits Valve Hole Dia. For Use On Standard Pack

O-Rings

543-3 .328" TR 540 Series 100

*Display Package.



31-194



31-336



31-015

Standard Bore Air-Liquid/Agricultural Valves



5880



6008B



5789



9252



5370A



5791C

Camel No.	Schrader No.	TR No.	Effective Length	Pack
-----------	--------------	--------	------------------	------

Tubeless Type Air-Liquid Valves

Clamp-in valves feature a removable 5789 core housing to permit fast filling of tires with liquid ballast solution. Fits .625" valve hole.

5880	618A	1 5/16"	5 per box
------	------	---------	-----------

Air-Liquid Core Housings & Accessories

Tractor Front Wheel Valve. Low profile tubeless valve offers minimum protrusion above rim hole. Brass finish. Fits .625" rim hole.

6008B	9/16"	10 per box
6008BS (same as 6008B except it fits .453" rim hole.)		10 per box

Core Housing. Screws into air-liquid valves and extensions shown here. Features O-ring seal.

34-963	5789 (TR-CH-3)	10 per box
--------	----------------	------------

Core Housing. Screws onto base of old TR218 and TR220 tube valves.

34-952	9252 (TR-CH-1)	10 per box
--------	----------------	------------

Nylon Rim Nut.

34-282	5370A	100 per box
--------	-------	-------------

Fluid Adapter

Fits standard bore air-water valves (tube & tubeless), after core housing is moved to extension mouth.

Fluid Adapter Set. Permits fast filling of tires for ballast. Fits tube and tubeless valves and extensions shown here (core housing removed). Includes extra bushings listed for standard bore valves and old 9251-type valves. Button valve on side releases air displaced by fluid. Hose connection is 3/4" standard garden hose.

34-955	5791C	1 per box
--------	-------	-----------

Schrader valve extensions provide a seal against contaminants while extending the valve mouth for convenient access. Fits standard .305-32" valve cap threads.

Packaging	Camel No.	Amflo No.	Schrader No.
-----------	-----------	-----------	--------------

Passenger Car Extensions

Double Sealing Extensions. Valves have two O-rings for high pressure applications.

50 pack	38-313-50		1046-50
100 pack	38-313-100		
250 pack			1046-250
500 pack	38-313-500		
1,000 pack			1046-1000

Chrome Plated Brass 3/4" Extensions. Long lasting chrome finish.

4 pack*	38-314-4		
50 pack	38-314-50		3680C-10
500 pack	38-314-500		

Chrome Plated Brass 1-1/4" Extensions. Long lasting chrome finish.

4 pack*	38-315-4	944D	
50 pack	38-315-50		3680G-10
500 pack	38-315-500		

Black Nylon 3/4" Extensions.

4 pack*	38-324-4		
10 pack	38-324-10		
50 pack	38-324-50		5066C-50
500 pack	38-324-500		

Black Nylon 1-1/4" Extensions.

4 pack*	38-325-4		
10 pack	38-325-10		
50 pack	38-325-50		5066G-50
500 pack	38-325-500		

Black Plastic 1-1/2" Extensions.

4 pack*	38-326-4		
10 pack	38-326-10		
50 pack	38-326-50		
500 pack	38-326-500		

* Display package



1046



38-314



38-324



38-326

Valve Extensions



38-400



38-430



38-436



7742A

Camel No.	Schrader No.	Effective Length	Packages
-----------	--------------	------------------	----------

Dual Wheel Valve Extension

Rubber 6.3" flexible extensions provide easy access to inner dual wheels on motor homes and other vehicles with small dual wheels. Includes clamp to secure hose to wheel. Installs with simple hand tools in minutes.

38-400		7"	Display pack of 2
38-400-10	1001-7	7"	Bulk pack of 10
	1001-9	9"	Bulk pack of 10
	1001-11	11"	Bulk pack of 10

Camel No.	Schrader No.	Length
-----------	--------------	--------

Standard Truck Extensions

Screws onto standard .305" - 32 valve cap threads to make valve mouth more accessible for air service.

38-430-2*		3-1/16"
38-430-10	7381	3-1/16"
38-432-2*		6-1/16"
38-432-10	7383	6-1/16"
38-436-2*		5-1/16"
38-436-10	7382	5-1/16"
38-471-10	7744	1"
38-472-10		1-3/8"
38-473-10		2-1/4"
38-474-10	4820	4-7/16"
	6358	1-13/32"
	6284	2-7/32"
	4414	3-1/8"
	4430	4-1/8"

Schrader No.	Length	Angle	Quantity
--------------	--------	-------	----------

Bent Metal Extensions

8028	1-3/8"	45°	10
7742A	1-1/2"	95°	10

*Display package



6358

7382

Camel No.	Amflo No.	Schrader No.	Operating Pressure Range (PSI)	Operating Temp. Range (°F)	Opening Pressure (PSIG)	Sealing Material Plug / Plunger	Pack Size
-----------	-----------	--------------	--------------------------------	----------------------------	-------------------------	---------------------------------	-----------

Standard Valve Cores

These valve cores all have .206"-36 threads and are compatible with existing USA, ETRTO and ISO standards.

Recommended for all truck, bus and commercial applications. Meets specification ZZ-V-25 and TR C-1.

		5405V	0-200 psia peaks of 300	-65 to +300 peaks of +400	90	Red Teflon	White Silicone	100
--	--	--------------	----------------------------	------------------------------	----	---------------	-------------------	-----

General purpose valve use. Meets specifications ZZ-V-25 and TR-C-1.

38-790-4	945D**		0-200 psia peaks of 300	-40 to +225	60	Green Teflon	Black Nitrile	4*
-----------------	---------------	--	----------------------------	-------------	----	-----------------	------------------	----

38-790-100	945-100	8500TV	0-200 psia peaks of 300	-40 to +225	60	Green Teflon	Black Nitrile	100
-------------------	----------------	---------------	----------------------------	-------------	----	-----------------	------------------	-----



5405

Special Valve Cores

Aircraft shock strut and hydraulic accumulator use. Meets specifications AN-809-1 and MIL-C-5499.

		2300TV	0-2000 psig (oiled) 70-2000 psig (dry)	0 to +165	100+	Molded Nitrile	Black Nitrile	100
--	--	---------------	---	-----------	------	-------------------	------------------	-----

Hydraulic accumulator use.

		9914A	0-2000 psig (oiled) 70-2000 psig (dry)	0 to +165	70	Natural Teflon	Black Nitrile	100
--	--	--------------	---	-----------	----	-------------------	------------------	-----



38-790/8500

Airplane

General purpose high-pressure, heat-resisting applications. Meets specification MIL-V-27317 and TRC-4.

		6035	0-400 psig peaks of 500	-65 to +350 peaks of +500	70	Natural Teflon	White Silicone	100
--	--	-------------	----------------------------	------------------------------	----	-------------------	-------------------	-----

Large Bore Core

This valve core has .305"-32 threads and is compatible with existing USA standards for large bore valve housings.

General purpose. Meets specification TR-C-2.

37-828-10		6231	0-200 psia	-65 to +300	55	Natural Teflon	White Silicone	100
------------------	--	-------------	------------	-------------	----	-------------------	-------------------	-----

* 5 pack.

** Display pack.

CAUTION: These products should not be used in applications which do not fully comply with recommended operating specifications. For use other than specified, or with media other than air or inert gases when not specified, consult for manufacturer approval.



9914A



← Plunger Pin

← Plug Gasket

← Spring Inside

← Plunger Seat Washer



6035

Valve Caps



7572



2316C

Camel No.	Amflo No.	Schrader No.	TR Number	Sealing Washer Material	Operating Pressure Range (PSIA)	Operating Temperature Range (°F)	Pack Size	Description	Finish
-----------	-----------	--------------	-----------	-------------------------	---------------------------------	----------------------------------	-----------	-------------	--------

Standard Valve Caps

Fit .305"-32 Threads on Standard Type Valves

38-772-4*			VC3	Nitrile	0-200	-40 to +165	4*	Same as No. 7572V	N/P
38-772-100	941-100	7572V	VC3	Nitrile	0-200	-40 to +165	100	Dome-shaped top and guide on skirt for easy application to valve threads.	N/P
		7572B	VC3	Nitrile	0-200	-40 to +165	100	Same as No. 7572V	Black
		7572S		Nitrile	0-200	-40 to +165	100	Same as No. 7572V, but has shorter skirt.	N/P
38-600-4*			VC2	Nitrile	0-200	-40 to +165	4*	Same as No. 2316C	N/P
38-600-100	940-100		VC2	Nitrile	0-200	-40 to +165	100	All purpose cap with screw-driver top for removing and inserting valve cores. Has guide on skirt for easy application to valve threads.	N/P
		2316C	VC2	Nitrile	0-200	-40 to +165	100		Black

Heavy Duty and Heat Resisting Caps

		440V		Nitrile	0-250	-40 to +200	100	Heavy-duty cap with special heat resistant rubber washer. Has guide on skirt for easy application to valve threads.	N/P
		2525	VC 5	Neoprene	0-5000	-65 to +160	100	Made from hexagon rod for wrench application. Maximum torque 10 inch-pounds. Has special sealing washer for high pressure use. Conforms to Military Spec. MIL-C-5000 and MS-20813.	Yellow
38-712-4*				Nitrile	0-250	-40 to +200	4*	Same as No. 5998	Chrome
38-712-100	949-100	5998		Nitrile	0-250	-40 to +200	100	For use on chrome sleeve and high performance valves.	Chrome

Plastic Caps

38-505*	943D**		VC 8		0-100	0 to +100	4*	Same as No. 660V	Black
38-505-100	943-100	660V	VC 8		0-100	0 to +100	100	Black flexible plastic cap has no sealing unit.	Black
		1155			0-200	-40 to 165	100 ¹		Black
38-505-500			VC 8		0-100	0 to +100	500	Same as No. 660V	Black

* Display pack. **5 pack. ¹Has sealing unit. For use on cars, trucks and commercial applications.

CAUTION: These products should not be used in applications which do not fully comply with recommended operating specifications. For use other than specified, or with media other than air or inert gases when not specified, consult for manufacturer approval.



38-712



1155



7572S



38-505



2525