

Equipment

Coll-O-Crimp Pumps

T-402-2 • Air/Hydraulic Pump



For use with T-400-1.

(Some models have air port on right side)

Note: It is recommended that a filter, regulator, lubricator and air pressure gauge be installed in the air line as close as possible to the pump. Filter, Regulator and Lubricator units not included.

Pump Specifications:

Dimensions: 5-1/4" high, 12-1/2" long, 5" wide

Weight: 18 lbs.

Operation Pressure: 4000-4200 PSI

Reservoir Capacity: 1 pint

Hydraulic Oil: Use Enerpac Oil ONLY

Outlet Port Size: 3/8" NPT

Inlet (Air) Port Size: 1/4" NPT

Inlet Air Pressure Required: 60 to 120 PSI

Filter: F23A3T02

Regulator: R23RGL02

Lubricator: L43MPL02

T-403-2 • Hand Pump



For use with T-400-1.

Pump Specifications:

Dimensions: 7 high, 21" long, 4-3/4" wide

Weight: 9 lbs.


Operation Pressure: 4000-4200 PSI

Reservoir Capacity: 1 qt.

Outlet Port Size: 3/8"

NPT Hydraulic Oil: Use Enerpac Oil ONLY

T-411 • Electric Pump (220 volt)



For repair and replacement items for the following pumps please contact an Enerpac Distributor at www.enerpac.com: T-402-2, T-403-2, T-460-2, T-462-2, T-480-2, T-480-3, T-481-110 & T-482-2.

Replacement pump for T-410-1 C-O-C II Press ONLY.

Replacement Parts:

CATALOG NUMBER	DESCRIPTION
Newer Pumps:	
T-421-FP	220v 4 wire Female electrical receptacle. See page 245 for illustration.
Older T-411 Pumps:	
T-411-B	By-pass module
T-411-G	Release Handle Spring (Models prior to 1982)
T-411-S	Micro-Switch (Models prior to 1982)
Older T-401-1 Pumps:	
T-401-1B	Replacement Gasket between motor and square reservoir
T-401-1BC	Breather Cap for Fenner-Stone pumps
T-401-1G	Relief Handle Spring (Models prior to 1982)
T-401-1S	Toggle Switch
T-401-SVF	Fenner Shuttle Valve
140-06761	Relay for T-421U or T-421U-BC pumps

Equipment

Coll-O-Crimp Pumps

T-462-2 • Air/Hydraulic Pump



For use with T-462.

The Weatherhead T-462-2 power unit is a air/hydraulic pump designed for use with the T-462 portable system. Ideal if you have the availability of compressed air in your shop or in the field via a portable compressor.

Pump Specifications:

Dimensions: 4" high, 13" long

Weight: 8 lbs.

Operation Pressure: 0-10,000 PSI

Reservoir Capacity: 10 cu in.

Relief Valve Setting: 10,000 PSI

Hydraulic Oil: Use Enerpac Oil ONLY

Regulator to be set for 100-120 PSI inlet air.

T-480-2 • Two-Stage Hand Pump



For use with T-480-HP.

Pump Specifications:

Dimensions: 7-3/16" high x 21-1/64" long x 4-3/4" wide

Weight: 9 lbs.

Operation Pressure: 0-10,000 PSI

Hydraulic Oil: Use Enerpac Oil ONLY

T-480-3 • Turbo Air/ Hydraulic Pump



For use with T-480-TA.

Pump Specifications:

Dimensions: 8-1/4" High x 12-3/8" long x 8" wide

Weight: 16-1/2 lbs.

Operation Pressure: 0-10,000 PSI

Hydraulic Oil: Use Enerpac Oil ONLY

For repair and replacement items for the following pumps please contact an Enerpac Distributor at www.enerpac.com: T-402-2, T-403-2, T-460-2, T-462-2, T-480-2, T-480-3, T-481-110 & T-482-2.